



2WLJP00751PBLF

Item #: S8197660

HARSH ENVIR INKJT W PET/751 PERMANENT ADHESIVE/3.4 MIL LASER LINER
Approximate weight per MMSI: 290 lbs. Standard core size is 6 inches. Total caliper: 7.6 mils +/- 10%

FACESTOCK

3.5 mil white matte polyester. It is a multi-purpose sheet for both laser and inkjet printing. The smooth surface allows graphics to really stand out on both black and white, and color printers.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Basis Weight	lbs/25X38-500	66.0	grams/sq meter	97.7	TAPPI T410
Caliper - Average	mil	3.500	um (micrometer)	88.9	TAPPI T411
Brightness	%	94.4	%	94.4	TAPPI T452

ADHESIVE

A tackified acrylic with good adhesion to many substrates. Excellent die-cutting and stripping on wide web VIP applications. Good mandrel hold.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Caliper - Calculated	mils	0.7	um(micrometer)	17.3	
Shear (1 x 1/2 x 1 kg)	hours	18.0	hours	18.0	CPD-55
Peel - 180 D SS 20 min	lb/inch	2.1	grams/25 mm	937.5	CPD-52
Loop Tack Stain Steel	oz/sq inch	52	kg/645 sq mm	1.5	CPD-16
Loop Tack Glass	oz/sq inch	60	kg/645 sq mm	1.7	CPD-16
Min. App. Temp.	F	45	C	7	
Service Temp.	F	-65 TO 200	C	-54 TO 93	
FDA Compliance	21 CFR	175.105			

LINER

A premium, 50# (82 g/m²) white kraft liner that is designed for roll-to-sheet and fan fold applications. Ideal for smooth feeding in desktop laser and inkjet printers. Suitable for die cutting both paper and film.

Test Property	Units	Typical Value	Metric Units	Metric Value	Test Method
Basis Weight	lbs/24X36-500	50.3	grams/sq meter	82.0	TAPPI T410
Caliper - Average	mil	3.4	um (micrometer)	86.4	TAPPI T411
Tear-MD	grams	58.1	mN	569.8	TAPPI T414
Tear-CD	grams	68.3	mN	669.8	TAPPI T414
Tensile-MD	lb/inch	41.1	kN/m	7.2	TAPPI T494
Tensile-CD	lb/inch	17.7	kN/m	3.1	TAPPI T494
Brightness	%	84.0	%	84.0	TAPPI T452

Notes

Please see the usage guidelines in Recommendations for Storage and Handling of Layflat Label Material located in the Ink Jet/Laser section of the Product Guide.

Issued: 09/21/17

The information presented in this publication is believed to be accurate and is not intended to constitute a specification. The values given reflect average material characteristics. All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose. No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

La información presentada en esta publicación se considera correcta; no debe ser interpretada como una especificación. Los valores dados reflejan las características regulares de los materiales. Todos los informes, fichas técnicas, y recomendaciones de los productos de Green Bay Packaging Inc. están basados en pruebas que se consideran confiables, pero no constituyen ningún tipo de garantía. Todos los productos se venden con el entendimiento de que el comprador ha determinado independientemente la conveniencia de estos productos para su uso final. Ningún vendedor, representante, ni agente de Green Bay Packaging Inc. está autorizado para dar ningún tipo de garantía, ni hacer representación alguna contraria a lo susodicho. Los Términos y Condiciones vigentes que regulan toda relación comercial de Green Bay Packaging Inc. - Coated Products Operations son los que se encuentran impresos en inglés en el último Libro de Precios. (Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book.)

SPECIALISTS IN COATED SELF-ADHESIVE MATERIALS

ESPECIALISTAS EN MATERIALES AUTO-ADHESIVOS

3250 South Ridge Road • P. O. Box 19017 • Green Bay, WI 54307-9017 • USA
Phone: 001-(920)-337-1800, 800-445-4269, WI: 800-472-4442 • FAX: 001-(920)-337-1797, 800-705-0111