Smart Partners ... Smarter Solutions



# Product Guide

Coated Products Operations

www.gbpcoated.com

1-800-445-4269 USA and Canada 001-920-337-1800 *Outside USA* 



#### PRESSURE-SENSITIVE LABEL STOCK STORAGE CONDITIONS AND SHELF LIFE

#### **Storage Conditions**

- The storage and converting conditions should be as close to TAPPI standards of 73°F (23°C) and 50% relative humidity as possible.
- Products should be stored in their original stretch wrap until the time they will be used on press.
- The material should be allowed to acclimate to your press room's environment for 24 hours before the stretch wrap is removed and the roll is loaded onto the press.
- Keep rolls off the concrete floors and away from any other sources of moisture contamination.
- Rotate your stock. Use the oldest inventory first.

#### **Shelf Life**

- Pressure-sensitive label material should be used within one year from date of purchase, unless otherwise stated on the data sheet.
- The one-year shelf life is part of our standard conditions of sale on all products. Green Bay Packaging will not accept any claims for pressure-sensitive material older than one year.
- The label stock should retain its functional performance after a year. The acrylic adhesive is chemically stable and will not oxidize or lose tack, and the silicone release level should remain the same.
- After application, the adhesive should not degrade or lose tack over time. However, in some applications, including very high moisture and temperature for example, adhesive performance may suffer.

#### LAYFLAT LABEL MATERIAL RECOMMENDATIONS

- Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60°F and 80°F (16°C and 27°C) and the relative humidity is between 40% and 60%.
- The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- Rotate your stock. Use oldest inventory first.
- Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- We are not able to guarantee layflat performance of labelstock produced with some removable adhesives.



#### ORDERING INFORMATION: U.S. STANDARD

**MINIMUM ORDER QUANTITY** 

INVENTORY CUSTOM 1 MMSI 3 MMSI

TAILORED INVENTORY PROGRAM (TIP)
(delivery only within the continental USA)
SHORT LENGTH UPCHARGE

3" Minimum on all TIP Items

For items not on the Short-Length TIP program, master rolls may be cut into shorter rolls **if** the order meets the minimum quantity of 1 MMSI for inventoried products or 3 MMSI for custom runs.

| Roll Length      | <u>Charge</u> |
|------------------|---------------|
| 1,250' to 2,499' | \$.05/MSI     |
| 500' to 1,249'   | \$.10/MSI     |
| 150' to 499'     | \$.15/MSI     |

CUSTOM REWINDING/SPLICING UPCHARGE

**SLITTING UPCHARGE** 

**SLITTING TOLERANCE** 

CORE SIZES

OVERRUN / UNDERRUN FINISHING ALLOWANCES

.03/MSI

0-17 cuts, no upcharge 18+ cuts .02/MSI 2" minimum slit width

+/- 1/32"

For core size, see the Data Sheet for your specific item.

TIP +/- 5%
Inventory +/- 5%
Custom Single Pass +/- 10%
Piggybacks +/- 15%
Special Materials +/- 20%

Product shelf life is one year unless otherwise stated on the component data sheet.

In addition to +/- % on overall order quantity, roll length may also be +/- % of ordered length. Customers may designate "exact roll length" on non-trimless items only. Additional splices may be required to meet exact roll length requests.

CAN'T FIND IT? CALL 1 - 800 - 445 - 4269



#### **ORDERING INFORMATION: METRIC SYSTEM**

**MINIMUM ORDER QUANTITY** 

INVENTORY CUSTOM

645 sq. Mts 1935 sq. Mts

TAILORED INVENTORY PROGRAM (TIP)
(delivery only within the continental USA)
SHORT LENGTH UPCHARGE

76.2mm Minimum on all TIP Items

For items not on the Short-Length TIP program, master rolls may be cut into shorter rolls **if** the order meets the minimum quantity of 1 MMSI for inventoried products or 3 MMSI for custom runs.

| Roll Length        | <u>Charge</u> |
|--------------------|---------------|
| 380 to 761 Meters  | \$.05/MSI     |
| 152 to 379 Meters  | \$.10/MSI     |
| 45.7 to 151 Meters | \$.15/MSI     |

CUSTOM REWINDING/SPLICING UPCHARGE

**SLITTING UPCHARGE** 

**SLITTING TOLERANCE** 

CORE SIZES

OVERRUN / UNDERRUN FINISHING ALLOWANCES

.05/sq. Mts

0-17 cuts, no upcharge 18+ cuts .03/sq. Mts 51mm minimum slit width

+/- 0.7mm

For core size, see the Data Sheet for your specific item.

Inventory +/- 5%
Custom Single Pass +/- 10%
Piggybacks +/- 15%
Special Materials +/- 20%

Product shelf life is one year unless otherwise stated on the component data sheet.

In addition to +/- % on overall order quantity, roll length may also be +/- % of ordered length. Customers may designate "exact roll length" on non-trimless items only. Additional splices may be required to meet exact roll length requests.

#### **TERMS AND CONDITIONS**

- 1. **Entire Agreement.** These Terms and Conditions shall constitute the entire agreement (the "Agreement" or "Terms and Conditions") of Green Bay Packaging Inc. ("Seller") and Buyer with respect to the subject matter hereof. These Terms and Conditions are controlling and shall supersede any prior or contemporaneous agreements, understandings or representations, oral or written, relating to the subject matter hereof. These Terms and Conditions shall govern in the event of any conflict between these Terms and Conditions and any provision contained in any subsequent Purchase Order or otherwise, the terms of which, whether conflicting, supplemental or otherwise, are hereby expressly rejected.
- 2. **Shipment, Title and Risk of Loss.** Unless otherwise mutually agreed in writing, shipment shall be F.O.B. Origin. Title and risk of loss pass from Seller to Buyer upon delivery to a carrier.
- 3. **Freight.** Shipments are F.O.B. Origin, with full freight allowed on shipments of 9 MMSI or more. Inventory and non-inventory items may be combined to meet the 9 MMSI minimum requirement for full freight allowed shipments, provided entire order is shipped at one time from one location to one destination. For all shipments fewer than 9 MMSI terms are F.O.B. Origin, freight prepaid and added, in which the shipping and handling charges shall be added to the face amount of the invoice.
- 4. **Payment.** Net 30 days following the date of invoice. 1% discount on payments received within 10 days of date of invoice. Amounts not paid in full within 30 days of date of invoice will be subject to a service charge of 1% per month on the unpaid balance to be included on each month's statement until paid in full.
- 5. **Taxes and Other Charges.** In addition to any price herein provided, Buyer shall be liable for any tax, fee or other charge imposed on Seller at any time upon the sale and/or shipment of the goods sold hereunder, now imposed by federal, state, municipal or any other governmental authorities or hereafter becoming effective for or during the period hereof.
- 6. Cancellation or Default by Buyer. This order may not be cancelled in whole or in part by Buyer except with Seller's written consent. If at any time, in Seller's opinion, Buyer's credit is impaired, or if Buyer shall fail to pay to Seller any amount when due, under this Agreement or any other agreement, or if at any time Buyer shall indicate an intention to refuse to perform or on an inability to perform its obligation hereunder, Seller may at its option terminate this Agreement as regards further shipments and thereupon all obligations of Buyer with respect to shipments previously made shall become immediately due and payable. In the event of such termination, Buyer shall remain liable to Seller for any and all loss or damage sustained due to Buyer's default.
- 7. **Force Majeure.** Seller shall not be liable for any loss, damage, delays, changes in shipment schedules or failure to deliver caused by any event beyond its reasonable control, including, without limitation, accident, fire, actual or threatened strike or riot, explosion, mechanical breakdown (including technological or information systems), plant shutdown, unavailability of or interference with necessary transportation, any raw material or power shortage, compliance with any law, regulation or order, acts of God or public enemy, prior orders from others, or limitations on Seller's or its suppliers' products or marketing activities or any other cause or contingency beyond Seller's control. If by reason of any such circumstance, Seller's supply of the goods herein specified shall be insufficient to meet all requirements, including its own, Seller shall have the right, at its option and without liability, to allocate its available supply of goods among its present and future customers, including Seller's affiliated divisions and companies, in such manner as Seller deems equitable.
- 8. Limitation on Warranty and Remedies. Seller warrants that the goods to be sold hereunder will conform to the description on the face hereof, and any specifications provided in writing to Buyer and will be of Seller's standard quality. Buyer represents that it has used its own independent skill and expertise in connection with the selection and use of the goods purchased pursuant to this Agreement, and that it will independently determine the suitability for each use for which it is purchased. When UL recognition is provided to Buyer, goods will meet applicable guidelines of Underwriting Laboratories. THIS WARRANTY IS EXCLUSIVE, AND EXCEPT AS EXPRESSLY SET OUT IN THIS AGREEMENT, SELLER MAKES NO OTHER WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, AND DISCLAIMS ALL OTHER WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN THE EVENT THE GOODS ARE NOT IN COMPLIANCE WITH SELLER'S WARRANTY HEREUNDER, BUYER'S SOLE REMEDY SHALL BE A CREDIT FOR THE COST OF SUCH GOODS OR, AT SELLER'S OPTION, REPLACEMENT OF SUCH GOODS. SELLER SHALL UNDER NO CIRCUMSTANCES, WHETHER FOR A FAILURE OF ITS LIMITED REMEDY OR OTHERWISE, BE LIABLE TO BUYER OR OTHERWISE FOR SPECIAL, INCIDENTAL, DIRECT, PUNITIVE, OR CONSEQUENTIAL DAMAGES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN OFFICER OF SELLER. All warranties and certifications are made by Seller to Buyer and to no other parties including, but not limited to, Buyer's customers and any other end users.
- 9. **Limitation of Actions.** Any claim must be made in writing within 10 days after receipt of goods, if for quantity, or within 30 days after receipt of goods, if for quality, loss of or damage to goods, and the goods must be held available at Buyer's place of business for Seller's inspection. Any action for breach of this Agreement, other than for non-payment hereunder, must be commenced within one year of the date of shipment, or due date of delivery in the event of non-delivery, of the particular shipment upon which such claim is based. No claim may in any event be made after goods have in any way been used or processed by the Buyer. Buyer's remedies set forth herein are exclusive and the total liability of Seller for damages with respect to this Agreement, or anything done in connection therewith, shall be limited to the purchase price of the particular shipment with respect to which such damages are claimed.
- 10. **Returns and Transit Damage Claims.** No goods may be returned to Seller without Seller's written consent. Goods returned without Seller's prior written authorization will be refused. Buyer must note any shortage or damage on the delivery receipt at the time of delivery. Any concealed damage must be reported to the delivering carrier within 5 days, and the entire package must be retained at Buyer's place of business until after a damage inspection report is issued by the carrier. The following documents must accompany any transit damage claim: original paid freight bill; original or certified copy of the original bill of lading; copy of the invoice for the shipment; copy of the destination inspection report or delivery receipt noting the shortage or damage.
- 11. Governing Law. This Agreement shall be governed by and construed in accordance with the internal laws of the state of Wisconsin, U.S.A.
- 12. **Amendment.** This Agreement shall not be amended except by a writing signed by an officer of the Seller and specifically stating that it is an amendment.

| Title                                | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--------------------------------------|-------|--|-------------------------------|-------------------|
| WHITE PAPERS - HIGH-GLOS             | ss    |  |                               |                   |
| 57# CAST COATED<br>HIGH-GLOSS OPAQUE | 057HA | 57# (85 g/m²) high-gloss paper (057HG) with a gray barrier opaque coating for use as cover-up labels. Use this facer when covering images on a glossy surface.   | 3.7<br>95.0                   |                   |
| 57# CAST COATED<br>HIGH-GLOSS        | 057HG | 57# (85 g/m²) high-gloss sheet with a smooth, reflective surface designed for top-quality graphic reproduction.  | 3.7<br>95.0                   |                   |
| ENCORE GLOSS                         | 060EG | 61# (89 g/m²) super calendered high-gloss sheet. This C1S paper is designed for premium labeling applications. Non-cast coated paper featuring excellent gloss and suitable for process printing.  | 2.8<br>72.0                   |                   |
| WHITE PAPERS - SEMI-GLOS             | SS    |  |                               |                   |
| 53# SEMI-GLOSS OPAQUE                | 054SA | 53# (78 g/m²) semi-gloss with a gray opaque barrier coating on the back. Designed for cover up labels. Excellent opacity, so the errors will not be visible. Smooth print surface for attractive graphic reproduction. FSC®-certified paper.                   | 2.6<br>66.0                   |                   |
| 53# SEMI-GLOSS                       | 054SG | 53# (78 g/m²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.               | 2.6<br>66.0                   |                   |
| 54# WET STRENGTH<br>SEMI-GLOSS       | 054WS | 54# (80 g/m²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper. | 2.9<br>80.0                   |                   |
| SEMI-GLOSS PREFERRED<br>OPAQUE       | 060PA | 60# (88.8/m²) Semi-Gloss Preferred (060PR) with a gray opaque barrier coating. Designed for cover up labels. Excellent print surface with flexo, toner, or offset. FSC®-certified paper.   | 3.1<br>79.0                   |                   |
| SEMI-GLOSS PREFERRED                 | 060PR | 60# (88.8/m²) semi-gloss, multi-purpose paper with superior gloss and print qualities. A warm white color. Excellent print surface for flexo, toner, or offset. FSC®-certified paper.  | 3.1<br>79.0                   |                   |
| 58# SEMI-GLOSS                       | 060SG | 58# (87 g/m²) semi-gloss multi-purpose paper with superior gloss and print qualities. Bright blue-white shade. Excellent graphic results with flexo, offset, or toner-based printing. FSC®-certified paper.  | 3.0<br>76.0                   |                   |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code       | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|------------|---|-------------------------------|-------------------|
| WHITE PAPERS - SEMI-GLOS                       | SS (cont.) |   |                               |                   |
| 80# SEMI-GLOSS                                 | 080SG      | 80# (118 g/m²) semi-gloss multi-purpose paper with superior gloss and print qualities. Bright blue-white shade. Excellent print surface for flexo, toner, or offset. This heavier sheet offers greater stiffness and opacity. FSC®-certified paper.     | 4.2<br>107.0                  |                   |
| FSC® CERTIFIED 53#<br>SEMI-GLOSS PAPER         | F54SG      | 53# (78 g/m²) C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. Smooth surface provides excellent printing with flexo, toner, and offset methods. FSC®-certified paper.        | 2.9<br>74.0                   |                   |
| 60# SEMI-GLOSS WITH 30%<br>POST-CONSUMER WASTE | R60SG      | A 60# (89 g/m²)semi-gloss face stock with 30% post-consumer recycled fiber. Excellent strength characteristics enhance label converting and application. Smooth print surface for outstanding graphics. FSC®-certified paper.                           | 2.7<br>68.6                   |                   |
| WHITE PAPERS - MATTE                           |            |   |                               |                   |
| 60# LITHO MATTE                                | 060LM      | A 60# (89 g/m²) clay-coated matte smooth paper. Offers a great printing surface for excellent graphic reproduction. Its very matte appearance provides a unique look in package design. Perfect for flexo printing and in a variety of digital presses. | 3.8<br>97.0                   |                   |
| 60# DULL LITHO                                 | 061DL      | 60# (89 g/m²) high quality, dull finish litho offering excellent print and die-cut properties. Good for flexographic and offset printing. FSC®-certified paper.   | 3.0<br>76.0                   | $\checkmark$      |
| WHITE PAPERS - INDIGO TO                       | PCOATED    |   |                               |                   |
| INDIGO TOPCOATED 55#<br>SEMI-GLOSS             | D55SG      | 55# (81 g/m²) semi-gloss sheet designed for printing on HP Indigo presses. It has been certified by RIT for use on the ws4500 and ws6000 presses. Has a blue-white shade with high brightness and opacity. Exceptionally strong. FSC®-certified paper.  | 3.0<br>76.0                   |                   |
| TAG STOCK                                      |            |   |                               |                   |
| 8 POINT GLOSS WHITE<br>CLAY COATED TAG         | 008GB      | A glossy, bright white, 130# (192 g/m²) board with excellent print characteristics. Coated on both sides, allowing for multiple uses - as a tag, or in a pressure-sensitive structure. FSC®-certified paper.  | 8.0<br>203.0                  |                   |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------|--|-------------------------------|-------------------|
| EDP  |       |  |                               |                   |
| 50# EDP SMUDGE<br>RESISTANT                              | 050ED | A 50# (74 g/m²) general purpose uncoated paper. Bright white with excellent smudge resistance. Designed for high performance. FSC®-certified paper.  | 3.5<br>88.9                   | V                 |
| PHARMACEUTICAL   |       |  |                               |                   |
| PHENOL-FREE DIRECT<br>THERMAL PRESCRIPTION<br>VIAL LABEL | 021RX | This 48# (71 g/m²), phenol-free, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.  | 3.1<br>78.0                   |                   |
| 40# PHARMACEUTICAL<br>LITHO                              | 040PL | 40# (60 g/m²) lightweight C1S semi-gloss litho with good ink holdout. Candidate for pharmaceutical and nutritional labeling.   | 2.0<br>52.0                   | $\checkmark$      |
| FLUORESCENT PAPERS                                       |       |  |                               |                   |
| BLUE FLUORESCENT   | 054BZ | 57# (84 g/m²) blue matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper. | 3.9<br>99.0                   |                   |
| GREEN FLUORESCENT  | 054GZ | 57# (84 g/m²) green matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.  | 3.9<br>99.0                   | $\checkmark$      |
| ORANGE FLUORESCENT                                       | 054OZ | 57# (84 g/m²) orange matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.   | 3.9<br>99.0                   | $\checkmark$      |
| PINK FLUORESCENT   | 054PZ | 57# (84 g/m²) pink matte fluorescent coated paper. Designed for laser, price marking, inkjet, promotional and general roll label applications. FSC®-certified paper.   | 3.9<br>99.0                   | $\checkmark$      |
| RED FLUORESCENT  | 054RZ | 57# (84 g/m²) red matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.  | 3.9<br>99.0                   | $\checkmark$      |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                                  | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------|--|-------------------------------|-------------------|
| FLUORESCENT PAPERS (co                 | ont.) |  | ,                             |                   |
| YELLOW CHARTREUSE<br>FLUORESCENT       | 054YZ | 57# (84 g/m²) yellow chartreuse matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.  | 3.9<br>99.0                   | ✓                 |
| BEER & WINE LABEL                      |       |  |                               |                   |
| 54# WET STRENGTH<br>SEMI-GLOSS         | 054WS | 54# (80 g/m²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper. | 2.9<br>80.0                   | ✓                 |
| CLASSIC CREST* SOLAR<br>WHITE SMOOTH   | owcsw | 60# (89 g/m²) smooth, uncoated white paper with an excellent printing surface, high strength, and dimensional stability. Perfect for wine labels and other upscale products. FSC®-certified paper. *Registered Trademark of Neenah Paper, Inc.                 | 4.4<br>112.0                  | $\checkmark$      |
| ESTATE LABEL* #4 WHITE<br>LAID         | 0WEL4 | 60# (89 g/m²) white, laid, uncoated, wet strength paper. Maintains its visual integrity when wet. Perfect for wine and beer labels. Its high-end look matches well with upscale products. *Registered Trademark of Neenah Paper, Inc. FSC®-certified paper.    | 5.5<br>140.0                  | $\checkmark$      |
| ESTATE LABEL* #8 WHITE<br>SMOOTH       | 0WEL8 | 60# (89 g/m²) uncoated, white, wet strength paper. Maintains its integrity when wet. Designed for wine and other high-end labels, such as gourmet foods and cosmetics. *Registered Trademark of Neenah Paper, Inc. FSC®-certified paper.                       | 4.8<br>122.0                  | $\checkmark$      |
| ESTATE LABEL* #9 CREAM<br>LAID         | 0WEL9 | 60# (89 g/m²) uncoated cream wet strength paper. Maintains its integrity when wet. Perfect for wine and other upscale labels, such as gourmet foods and cosmetics. FSC®-certified paper. *Registered Trademark of Neenah Paper, Inc.                           | 5.4<br>137.0                  |                   |
| SILVER METALIZED WET<br>STRENGTH PAPER | 56MSW | 56# (83 g/m²) top coated silver metalized paper. Wet strength for use in moist environments including refrigerated foods and chilled beverages. The metallic look makes a product's graphics stand out.  | 2.8<br>71.0                   |                   |
| 70# BRIGHT WHITE FELT                  | 70BWF | 70# (103 g/m²) uncoated bright white, wet strength paper. Perfect for wine, beer, and other beverage labels. The rich weight and texture makes it ideal for upscale food, home, and personal care products. FSC®-certified paper.                              | 5.7<br>145.0                  | <b>V</b>          |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                              | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|------------------------------------|-------|--|-------------------------------|-------------------|
| BEER & WINE LABEL (cont.           | )     |  |                               |                   |
| 60# BLACK VELLUM                   | BKVLM | 60# (89 g/m²) uncoated, black, smooth, wet strength paper. Maintains its integrity when wet. While it was designed for wine, beer, and other beverage labels, its unique look will make any product stand out on store shelves. FSC®-certified paper.          | 4.8<br>122.0                  | <b>V</b>          |
| 50# KONA LIGHT ROAST               | KONAL | KONAL is a 50# (74g/m²), 100% PCW recycled wet strength product. A blend of repurposed coffee bean bag fiber and post-consumer waste material. Perfect for labeling any coffee-related product, or environmentally-friendly packaging. FSC®-certified paper.   | 4.1<br>104.0                  |                   |
| 60# 100% PCW WET<br>STRENGTH PAPER | PLRNB | A 60# (89 g/m²) FSC®-certified, 100% post-consumer waste paper with wet strength. Resistant to moisture, it's perfect for beverage applications, like wine, beer and chilled spirits. Its luxurious look will enhance upscale food and personal care products. | 4.3<br>109.0                  | $\checkmark$      |
| SPECIALTY PAPERS                   |       |  |                               |                   |
| 54# WET STRENGTH<br>SEMI-GLOSS     | 054WS | 54# (80 g/m²) C1S blue-white semi-gloss. Wet strength stands up to moisture. Ideal for chilled beverages, including beer and wine, or refrigerated foods. Smooth surface enhances print results with flexo, laser and other press types. FSC®-certified paper. | 2.9<br>80.0                   | V                 |
| BROWN NATURAL KRAFT                | 060GM | 60# (89 g/m²) brown natural kraft paper. The natural look makes it perfect for labeling organic or other earth-friendly products. It can also be used for cover-up labels on corrugated containers.  | 5.5<br>140.0                  | $\checkmark$      |
| 60# HEMP PAPER                     | 1HEMP | A 60# (89 g/m²) paper made with 25% hemp fibers and 75% post-consumer waste. Designed for labeling cannabis and other hemp products. With no virgin wood content and a natural look it is also a perfect match for organic and other eco-friendly products.    | 5.0<br>127.0                  | $\checkmark$      |
| TRANSLUCENT PAPER                  | 1TRCT | A 42# (62 g/m²) ultra-clear translucent paper. It is well-suited for wafer seal mailing tabs. Can be used for tamper-evident seals. Also provides a unique look for primary package decoration.  | 2.3<br>58.4                   |                   |
| DISSOLVABLE PAPER                  | H2ODP | A water-soluble paper. Coated with the dissolvable adhesive, 611, it disappears in seconds under running water. Leaves no residue on the container. Best dissolvable performance when printed with water-based inks. Keep wrapped until used. FSC®-certified.  | 3.5<br>89.0                   |                   |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

Target

MADE

| Title   | Code  | Description   | (MILS)<br>(Microns) | IN<br>USA    |
|---|-------|---|---------------------|--------------|
| SPECIALTY PAPERS (cont.)                          |       |   |                     |              |
| 50# KONA LIGHT ROAST                              | KONAL | KONAL is a 50# (74g/m²), 100% PCW recycled wet strength product. A blend of repurposed coffee bean bag fiber and post-consumer waste material. Perfect for labeling any coffee-related product, or environmentally-friendly packaging. FSC®-certified paper.    | 4.1<br>104.0        | $\checkmark$ |
| LAMINATED FOILS                                   |       |   |                     |              |
| BRIGHT GOLD FOIL                                  | 055BG | Top coated 70# (104 g/m²) bright gold laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.  | 3.6<br>91.0         | $\checkmark$ |
| BRIGHT SILVER FOIL                                | 055BS | Top coated 70# (104 g/m²) bright silver laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.  | 3.6<br>91.0         | $\checkmark$ |
| DULL GOLD FOIL                                    | 055DG | Top coated 70# (104 g/m²) dull gold laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.  | 3.6<br>91.0         | $\checkmark$ |
| DULL SILVER FOIL                                  | 055DS | Top coated 70# (104 g/m²) dull silver laminated foil. Suitable for water based, UV screen, UV flexo and embossing. FSC®-certified paper.  | 3.6<br>91.0         | $\checkmark$ |
| FOIL SUBSTITUTES                                  |       |   |                     |              |
| 1.85 MIL SILVER<br>METALIZED BOPP                 | 018MT | 1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer.  | 1.9<br>47.0         |              |
| 2.0 MIL SILVER METALIZED<br>BOPP                  | 021MU | A 2.0 mil BOPP metalized on the back side for a shiny silver appearance. Top coated for printability with a wide range of ink systems.  | 2.0<br>51.0         |              |
| HOLOGRAM PRISMATIC<br>DIFFRACTION: RAINBOW        | 056H5 | 64# (94 g/m²) decorative prismatic diffraction paper. Shim lines/seams are present in holographic material. This gap in the pattern will be up to 1/32" wide. The area between the shim lines measures 30" machine direction (MD) and 48" cross direction (CD). | 3.3<br>84.0         |              |
| HOLOGRAM PRISMATIC<br>DIFFRACTION:<br>LOTS-O-DOTS | 056H7 | 60# (89 g/m²) decorative prismatic diffraction paper. Shim lines/seams are present in holographic material. This gap in the pattern will be up to 1/32" wide. The area between the shim lines measures 30" machine direction (MD) and 48" cross direction (CD)  | 3.2<br>81.0         | <b>√</b>     |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------|--|-------------------------------|-------------------|
| FOIL SUBSTITUTES (cont.)                         |       |  |                               |                   |
| 56# SILVER METALIZED<br>PAPER                    | 057MS | 56# (83 g/m²) top coated silver metalized paper. Not recommended for HP Indigo Presses.  | 2.5<br>64.0                   | $\checkmark$      |
| SILVER METALIZED WET<br>STRENGTH PAPER           | 56MSW | 56# (83 g/m²) top coated silver metalized paper. Wet strength for use in moist environments including refrigerated foods and chilled beverages. The metallic look makes a product's graphics stand out.                          | 2.8<br>71.0                   |                   |
| THERMAL TRANSFER                                 |       |  |                               |                   |
| 2.6 MIL THERMAL<br>TRANSFER WHITE<br>LABEL-LYTE™ | 026TT | 2.6 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is required. Label-Lyte is a trademark of Jindal Films America.  | 2.6<br>66.0                   | $\checkmark$      |
| THERMAL TRANSFER<br>WHITE LABEL-LYTE™            | 030TT | 3.0 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is important. Label-Lyte is a Trademark of Jindal Films America. | 3.0<br>76.0                   | <b>V</b>          |
| HIGH SPEED COATED<br>THERMAL TRANSFER            | 050HS | 47# (70 g/m²) premium bright white, coated, ultra-smooth thermal transfer paper stock offering broad ribbon compatibility. FSC®-certified paper.   | 3.0<br>76.0                   | $\checkmark$      |
| 3.0 MIL TC MATTE WHITE<br>BOPP                   | 075WP | A 3.0 mil top coated matte white BOPP. A synthetic paper, it can be used with thermal transfer, flexography, screen, letterpress, and other print methods. It is moisture, chemical and tear resistant.                          | 3.0<br>75.0                   |                   |
| TOP COATED KIMDURA®<br>FPG 95                    | 095TK | A 4.2 mil Kimdura® BOPP specially top coated for thermal transfer, dot matrix, ion deposition and digital printing. Registered Trademark of Neenah Paper, Inc. © 2007 NPI All Rights Reserved.                                   | 4.2<br>107.0                  |                   |
| SELECT THERMAL<br>TRANSFER OPAQUE                | 0TTFA | A 44# (65 g/m²) gray opaque multi-purpose thermal transfer sheet. Designed for cover up labels, with excellent opacity. Premium coating for enhanced flexo graphics. FSC®-certified paper.                                       | 2.9<br>72.0                   |                   |
| SELECT THERMAL<br>TRANSFER                       | 0TTFP | A 44# (65 g/m²) multi-purpose thermal transfer sheet. Premium coating for enhanced flexo-printed graphics. FSC®-certified paper.   | 2.9<br>72.0                   | $\checkmark$      |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code  | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------|---|-------------------------------|-------------------|
| THERMAL TRANSFER (cont.)                                 | )     |   |                               |                   |
| MATTE WHITE BOPP   | 100WP | A 3.7 mil top coated matte white BOPP. UV resistant. A synthetic paper, it can be printed by thermal transfer, flexography, screen, and letterpress. Moisture, chemical and tear resistant. For drum label, outdoor and other demanding applications.         | 3.7<br>95.0                   |                   |
| VALUE THERMAL<br>TRANSFER                                | VALUT | A 42# (62 g/m²) top-coated, thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper.  | 2.8<br>71.0                   |                   |
| DIRECT THERMAL   |       |   |                               |                   |
| TOP COATED DIRECT<br>THERMAL PAPER                       | 015DT | A 38# (56.2 g/m²) high sensitivity, top coated direct thermal paper. This thinner caliper facer allows more labels per roll. Ideal for hand-applied mobile printing applications. FSC®-certified paper.   | 2.3<br>58.4                   |                   |
| NON-TOP COATED DIRECT<br>THERMAL PAPER                   | 024NT | A 47# (69.9 g/m²) medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.                   | 3.1<br>78.7                   |                   |
| PHENOL-FREE DIRECT<br>THERMAL PRESCRIPTION<br>VIAL LABEL | 021RX | This 48# (71 g/m²), phenol-free, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper. | 3.1<br>78.0                   |                   |
| RED FLUORESCENT<br>DIRECT THERMAL                        | 022FT | A 54# (80 g/m²) bright red direct thermal coated paper. Images black. Intended for attention-grabbing promotional point-of-purchase labels, or color coded warehouse tracking. FSC®-certified paper.  | 3.1<br>79.0                   | $\checkmark$      |
| 3.4 MIL NEAR IR PACKAGE<br>DELIVERY DIRECT<br>THERMAL    | 022PD | A 50# (74 g/m²) direct thermal paper top-coated for handling durability. Near IR designed for package delivery. PCS and scanning up to 670 nm. For high-heat environments. Resists imaging up to 100°C. Moderate to fast print speeds. FSC®-certified paper.  | 3.4<br>79.0                   |                   |
| PREMIUM TOP COATED TD                                    | 022TD | A 53# (78 g/m²) top coated direct thermal coated paper for more demanding applications and higher imaging speeds. FSC®-certified paper.   | 3.1<br>79.0                   | $\checkmark$      |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code  | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------|---|-------------------------------|-------------------|
| DIRECT THERMAL (cont.)                       |       | •   |                               |                   |
| ECONOMY TOP COATED DIRECT THERMAL PAPER      | 024DT | A 53# (78 g/m²) top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.               | 3.2<br>81.0                   | V                 |
| ECONOMY TOP COATED DIRECT THERMAL PAPER      | 025DT | A 47# (70 g/m²) top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.               | 3.1<br>79.0                   |                   |
| NON-TOP COATED DIRECT<br>THERMAL PAPER       | 025NT | A 51# (75 g/m²) medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.                     | 3.3<br>82.5                   |                   |
| 3.0 MIL SYNTHETIC MEDIUM SENSITIVITY FILM    | 070MK | A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.   | 3.0<br>76.0                   |                   |
| 3.3 MIL SYNTHETIC MEDIUM SENSITIVITY FILM    | 084MB | A 3.3 mil BOPP direct thermal film. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.    | 3.3<br>84.0                   |                   |
| SYNTHETIC MEDIUM<br>SENSITIVITY FILM         | 095RK | 4.1 mil white BOPP film with direct thermal coating. Top coated for durability. Medium degree of sensitivity.   | 4.1<br>104.0                  |                   |
| SYNTHETIC MEDIUM<br>SENSITIVITY FILM         | 096RK | 4.1 mil white BOPP film with direct thermal coating. Produces a dark image. Top coated for durability. Water and environmental resistant. Use for industrial labeling, ski lift tickets, baggage tags, product labels, and retail shelf labeling.             | 4.1<br>104.0                  | V                 |
| TOP-COATED VALUE<br>DIRECT THERMAL<br>OPAQUE | 24VTA | A 48# (71 g/m²) top coated direct thermal paper with a gray opaque backside coating. Designed for cover up labels. Good environmental resistance for weigh scale, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper. | 3.2<br>80.0                   |                   |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                                | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--------------------------------------|-------|--|-------------------------------|-------------------|
| DIRECT THERMAL (cont.)               |       | <u> </u>   | ,                             |                   |
| TOP COATED VALUE<br>DIRECT THERMAL   | 24VTB | A 48# (71 g/m²) top coated paper. Resists moisture, heat, humidity, fading, scuffing, chemicals, and plasticizers. Use for weigh scale applications, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.             | 3.2<br>80.0                   | ✓                 |
| 3.0 MIL CLEAR DIRECT<br>THERMAL FILM | 30CDT | A 3.0 mil top-coated direct thermal polypropylene film with exceptional clarity. Designed for variable image printed labels that highlight the product. Has environmental and water resistance. White should be printed behind any barcode for scannability. | 3.0<br>76.0                   |                   |
| INK JET / LASER                      |       |  |                               |                   |
| SUPER BRIGHT LASER JET               | 050LJ | 51# (75 g/m²) Exceptionally bright, uncoated, multi-purpose sheet for both laser and ink jet printing. FSC®-certified paper.   | 4.0<br>102.0                  | $\checkmark$      |
| BLUE FLUORESCENT                     | 054BZ | 57# (84 g/m²) blue matte fluorescent coated paper. Designed for laser, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper.       | 3.9<br>99.0                   |                   |
| GREEN FLUORESCENT                    | 054GZ | 57# (84 g/m²) green matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.   | 3.9<br>99.0                   | $\checkmark$      |
| ORANGE FLUORESCENT                   | 054OZ | 57# (84 g/m²) orange matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.  | 3.9<br>99.0                   |                   |
| PINK FLUORESCENT                     | 054PZ | 57# (84 g/m²) pink matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.  | 3.9<br>99.0                   | $\checkmark$      |
| RED FLUORESCENT                      | 054RZ | 57# (84 g/m²) red matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.   | 3.9<br>99.0                   | $\checkmark$      |
| YELLOW CHARTREUSE<br>FLUORESCENT     | 054YZ | 57# (84 g/m²) yellow chartreuse matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.   | 3.9<br>99.0                   | $\checkmark$      |
| 60# MATTE-COATED INK<br>JET          | 06INK | A 60# (88 g/m²) matte-coated, acid-free, inkjet sheet with an exceptionally bright, blue-white shade. It provides high resolution imaging, and excellent smear and water resistance. It is compatible with a broad array of inkjet printers. FSC®-certified. | 4.4<br>113.0                  |                   |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code                          | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |  |  |
|--|-------------------------------|---|-------------------------------|-------------------|--|--|
| INK JET / LASER (cont.)  |                               |   | , ,                           |                   |  |  |
| PREMIUM COATED MATTE<br>INK JET  | 06MIJ                         | A 61# (90 g/m²) matte-coated ink jet sheet with good opacity. It is waterfast and provides an extremely high level of smear resistance. This facer offers high resolution imaging and is compatible with a broad array of inkjet printers.                      | 4.6<br>107.0                  | Ø                 |  |  |
| 60# MATTE-COATED INK<br>JET  | 07INK                         | A 60# (88 g/m²) matte-coated, acid-free, inkjet sheet with an exceptionally bright, blue-white shade. It provides high resolution imaging, and excellent smear and water resistance. It is compatible with a broad array of inkjet printers. FSC®-certified.    | 4.5<br>114.3                  |                   |  |  |
| 59# GLOSS INKJET PAPER   | 1GINK                         | A 59# (87 g/m²) high gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. Not recommended for flexo printing. FSC®-certified.       | 4.1<br>104.0                  |                   |  |  |
| 65# SEMI-GLOSS IINKJET<br>PAPER  | SG2NK                         | A 65# (97 g/m²) semi gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. FSC®-certified.   | 4.5<br>97.0                   |                   |  |  |
| 3.4 MIL MATTE WHITE INK<br>JET BOPP  | 34WIJ                         | A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance. | 3.4<br>86.0                   |                   |  |  |
| 47# FSC®-CERTIFIED SUPER BRIGHT LASER JET  47# (70 g/m²) Exceptionally bright, uncoated, multi-purpose sheet for la and ink jet printing. Lighter weight for shipping savings. Thinner caliper space savings and reduced packaging. Offers the option of more labels a roll. FSC®-certified. |                               | 3.5<br>89.0   | Ø                             |                   |  |  |
| FILMS: POLYPROPYLENES (  | FILMS: POLYPROPYLENES (CLEAR) |   |                               |                   |  |  |
| 1.85 MIL CLEAR TOP<br>COATED BOPP  | 018CT                         | 1.85 mil clear top-coated BOPP is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, and beverage labeling.        | 1.9<br>47.0                   |                   |  |  |
| 2.0 MIL CLEAR TOP<br>COATED BOPP   | ·                             |   | 2.0<br>51.0                   |                   |  |  |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                                      | Code       | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|------------|---|-------------------------------|-------------------|
| FILMS: POLYPROPYLENES                      | (CLEAR) (c | ont.)   |                               |                   |
| 2.2 MIL FLEXICLEAR™ TC<br>CONFORMABLE BOPP | 022FC      | A 2.2 mil top coated clear BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiClear™ is a Trademark of Green Bay Packaging Inc.         | 2.2<br>56.0                   |                   |
| 3.6 MIL CLEAR TC BOPP                      | 036CG      | A 3.6 mil clear BOPP film. UV resistance and top coating suitable for UV screen, UV flexo and waterbased inks. Can be used for window graphics, or other applications where a more substantial film is needed.  | 3.6<br>91.0                   |                   |
| FILMS: POLYPROPYLENES                      | (WHITE)    |   |                               |                   |
| 2.2 MIL FLEXIWHITE™ TC<br>CONFORMABLE BOPP | 022FW      | A 2.2 mil top coated white BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiWhite™ is a Trademark of Green Bay Packaging Inc.         | 2.2<br>56.0                   |                   |
| 2.3 MIL TOP COATED<br>WHITE BOPP           | 023WB      | A 2.3 mil white top coated BOPP, backside coated to aid in adhesive anchorage. Excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.  | 2.3<br>58.0                   |                   |
| 2.3 MIL WHITE TOP<br>COATED BOPP           | 023WP      | A 2.3 mil white top coated BOPP with excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.  | 2.3<br>58.0                   |                   |
| 2.3 MIL WHITE<br>TOP-COATED BOPP           | 023WT      | 2.3 mil solid white top-coated BOPP. Compatible with UV and water-based flexo, and UV inkjet printing; also hot stamping. Exceptional opacity. Backside treated for adhesive anchorage. Great stiffness for auto application. Ideal for prime labeling. | 2.3<br>58.0                   |                   |
| 2.4 MIL TOP COATED<br>WHITE LABEL-LYTE™    | 024TL      | A 2.4 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.                         | 2.4<br>61.0                   | V                 |
| 2.6 MIL TOP COATED<br>WHITE LABEL-LYTE™    | 026TL      | A 2.6 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.                         | 2.6<br>69.0                   | $\checkmark$      |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title  | Code        | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------------|---|-------------------------------|-------------------|
| FILMS: POLYPROPYLENES                            | (WHITE) (co |   | ,                             |                   |
| 3.6 MIL WHITE TC BOPP                            | 036WG       | A 3.6 mil white BOPP film. UV resistance and top coating suitable for UV screen, UV flexo and waterbased inks. Can be used for window graphics, or other applications where a more substantial film is needed.  | 3.6<br>91.0                   |                   |
| 2.4 MIL WHITE<br>TOP-COATED BOPP                 | 24WCT       | 2.4 mil white top-coated BOPP. It is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Glossy look. Perfect for health and beauty aid, household care, and beverage labeling.                         | 2.4<br>61.0                   |                   |
| 2.6 MIL WHITE<br>TOP-COATED BOPP                 | 26WCT       | A 2.6 mil glossy white BOPP. It is top coated for dependable ink adhesion. Excellent compatibility with UV and water-based flexo ink systems, as well as UV inkjet. A perfect look for use on health and beauty aids, household care products, and beverages.   | 2.6<br>66.0                   |                   |
| 3.4 MIL MATTE WHITE<br>INKJET BOPP               | 34WIJ       | A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance. | 3.4<br>86.4                   |                   |
| FILMS: POLYPROPYLENES                            | (VARIABLE   | IMAGING)  |                               |                   |
| 2.6 MIL THERMAL<br>TRANSFER WHITE<br>LABEL-LYTE™ | 026TT       | 2.6 mil White Label-Lyte BOPP with a thermal transfer top coat. Designed for variable imaging applications where moisture resistance, or long-term performance, is required. Label-Lyte is a trademark of Jindal Films America.                                 | 2.6<br>66.0                   |                   |
| THERMAL TRANSFER<br>WHITE LABEL-LYTE™            | 030TT       | White Label-Lyte BOPP with a thermal transfer top coat. Label-Lyte is a Trademark of Jindal Films America.  | 3.0<br>76.0                   | $\checkmark$      |
| 3.0 MIL SYNTHETIC<br>MEDIUM SENSITIVITY FILM     | 070MK       | A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.   | 3.0<br>76.0                   |                   |
| 3.0 MIL TC MATTE WHITE<br>BOPP                   | 075WP       | A 3.0 mil top coated matte white BOPP. A synthetic paper, it can be used with thermal transfer, flexography, screen, letterpress, and other print   | 3.0<br>75.0                   |                   |
| 3.3 MIL SYNTHETIC<br>MEDIUM SENSITIVITY FILM     | 084MB       | A 3.3 mil BOPP direct thermal film. Top coated for durability. Medium degree of sensitivity. Use when moisture and environmental resistance are important. Good stiffness for ease of dispensing. Dark image for excellent ability to be read and scanned.      | 3.3<br>84.0                   |                   |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                                | Code      | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--------------------------------------|-----------|--|-------------------------------|-------------------|
| FILMS: POLYPROPYLENES                | (VARIABLE |  | ,                             |                   |
| SYNTHETIC MEDIUM<br>SENSITIVITY FILM | 095RK     | 4.1 mil white BOPP film with direct thermal coating. Top coated for durability. Medium degree of sensitivity.  | 4.1<br>104.0                  |                   |
| SYNTHETIC MEDIUM<br>SENSITIVITY FILM | 096RK     | 4.1 mil white BOPP film with direct thermal coating. Produces a dark<br>image. Top coated for durability. Water and environmental resistant. Use<br>for industrial labeling, ski lift tickets, baggage tags, product labels, and<br>retail shelf labeling.           | 4.1<br>104.0                  |                   |
| MATTE WHITE BOPP                     | 100WP     | A 3.7 mil top coated matte white BOPP. UV resistant. For use with thermal transfer and other print methods. Consider for drum label, outdoor and other demanding applications.   | 3.7<br>95.0                   |                   |
| FILMS: POLYPROPYLENES                | (METALIZE | D)   |                               |                   |
| 1.85 MIL SILVER<br>METALIZED BOPP    | 018MT     | 018MT 1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer. |                               |                   |
| 2.0 MIL SILVER METALIZED<br>BOPP     | 021MU     | A 2.0 mil BOPP metalized on the back side for a shiny silver appearance. Top coated for printability with a wide range of ink systems.   | 2.0<br>51.0                   |                   |
| FILMS: POLYSTYRENES                  |           |  |                               |                   |
| 1.5 MIL CLEAR<br>POLYSTYRENE         | 015PN     | A 1.5 mil corona treated clear polystyrene. Perfect for use as a base for peel-off coupons and booklets.   | 1.5<br>38.0                   |                   |
| 2.0 MIL CLEAR<br>POLYSTYRENE         | 020PN     | A 2.0 mil corona treated clear polystyrene. Stiffness allows easy converting and dispensing.   | 2.0<br>51.0                   |                   |
| 2.5 MIL CLEAR<br>POLYSTYRENE         | 025PN     | A 2.5 mil corona treated clear polystyrene. Stiffness allows easy converting and dispensing. Great for use as a mailing tab.   | 2.5<br>64.0                   | $\checkmark$      |
| 3.5 MIL WHITE SQUEEZE OPTICITE®      | 035WZ     | A 3.5 mil white squeezable OPTICITE® with a corona treated print surface. Trademark of The Dow Chemical Company  |                               | $\checkmark$      |



### Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                                  | Code  | Description   | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|--|-------|---|-------------------------------|-------------------|
| FILMS: POLYSTYRENES (co                | ont.) | ·   | ,                             |                   |
| 2.5 MIL WHITE<br>POLYSTYRENE           | 25PSW | A 2.5 mil corona treated white polystyrene. Stiffness allows easy converting and dispensing.  | 2.5<br>64.0                   | $\checkmark$      |
| FILMS: POLYESTERS                      |       |   |                               |                   |
| 1.0 MIL CLEAR PET<br>OVERLAMINATE FILM | 010PC | A 1.0 Mil PET clear overlaminate film with a glossy finish. Use it to protect printed graphics, or add durability to labels and integrated cards. Top coated for laser printing.  | 1.0<br>23.0                   | $\checkmark$      |
| 2 MIL CLEAR TOP COATED POLYESTER       | 020MY | A very clear, top coated polyester film. Top coating allows for printing with most standard flexo and UV letterpress inks.  | 2.0<br>51.0                   | $\checkmark$      |
| 2.0 MIL CLEAR PET<br>OVERLAMINATE FILM | 020PC | A 2.0 Mil clear PET overlaminate film with a glossy finish. Use it to protect printed graphics, or add durability to labels and integrated cards. Top coated for laser printing.  | 2.0<br>51.0                   | <b>V</b>          |
| 1.0 MIL CLEAR NTC<br>POLYESTER         | 1CLPT | A glossy, clear polyester overlaminate film. Good clarity. Effective in durable applications – resistant to heat and chemicals. High tear strength.   | 1.0<br>23.0                   | $\checkmark$      |
| 2.0 MIL MATTE PET<br>OVERLAMINATE FILM | 20MOL | A 2.0 Mil PET overlaminate film with a matte finish. Made with a matte resin for extra toughness. Use it to protect printed graphics, or add durability to labels and integrated cards. Top coated for laser printing. Ball point pen signature compatible. | 2.0<br>50.0                   |                   |
| 2.0 MIL VALUE WHITE<br>POLYESTER       | 2VWPT | A matte, white polyester film, top-coated for water-based and U.V. flexographic ink adhesion, and thermal transfer printing. Designed for durable applications – resistant to heat and chemicals. High tear strength.                                       | 2.0<br>50.0                   |                   |
| FILMS: OVERLAMINATES                   |       |   |                               |                   |
| 1.0 MIL CLEAR PET<br>OVERLAMINATE FILM | 010PC | A 1.0 Mil PET clear overlaminate film with a glossy finish. Use it to protect printed graphics, or add durability to labels and integrated cards. Top coated for laser printing.  | 1.0<br>23.0                   | $\checkmark$      |
| 2.0 MIL CLEAR PET<br>OVERLAMINATE FILM | 020PC | A 2.0 Mil clear PET overlaminate film with a glossy finish. Use it to protect printed graphics, or add durability to labels and integrated cards. Top coated for laser printing.  | 2.0<br>51.0                   | <b>V</b>          |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Title                                     | Code  | Description  | Target<br>(MILS)<br>(Microns) | MADE<br>IN<br>USA |
|---|---|--|-------------------------------|-------------------|
| FILMS: OVERLAMINATES (co                  |   | 2001, p.101  | (                             | <del>Cont</del>   |
| 1.0 MIL CLEAR NTC<br>POLYESTER            | 1CLPT   | A glossy, clear polyester overlaminate film. Good clarity. Effective in durable applications – resistant to heat and chemicals. High tear strength.  | 1.0<br>23.0                   |                   |
| 2.0 MIL MATTE PET<br>OVERLAMINATE FILM    | 20MOL   | A 2.0 Mil PET overlaminate film with a matte finish. Made with a matte resin for extra toughness. Use it to protect printed graphics, or add durability to labels and integrated cards. Top coated for laser printing. Ball point pen signature compatible.  | 2.0<br>50.0                   |                   |
| FILMS: CLEAR SPECIALTY                    |   |  |                               |                   |
| 2 MIL CLEAR ACETATE                       | 020AC   | A 2.0 mil clear acetate film with good clarity and printability. It is compostable. Has relatively low tear resistance and is good for tamperproof applications. Meets the ASTM D6400 compost standard.  | 2.0<br>51.0                   |                   |
| FILMS: INDIGO TOPCOATED                   |   |  |                               |                   |
| 2.3 MIL WHITE BOPP WITH INDIGO TOPCOATING | D23WP   | A 2.3 mil glossy white BOPP optimized for use with HP Indigo presses. It has been certified by RIT for use on the ws4500 and ws6000 presses. High stiffness for automatic dispensing. Great choice for prime labeling.                                       |                               |                   |
| FILMS: WHITE SPECIALTY                    |   |  |                               |                   |
| TYVEK®                                    | DuPont™ Tyvek® (1073D) is a 7.5 mil, strong, transluscent polyolefin with exceptional strength and moisture resistance.  DuPont™ and Tyvek® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company. |  | 7.6<br>191.0                  |                   |
| PIGGYBACKS                                |   |  |                               |                   |
| 60# DULL LITHO                            | 061DL   | 60# (89 g/m²) high quality, dull finish litho offering excellent print and die-cut properties. Good for flexographic and offset printing. FSC®-certified paper.  | 3.0<br>76.0                   |                   |
| VALUE THERMAL<br>TRANSFER                 | VALUT   | A 42# (62 g/m²) top-coated, thermal transfer sheet that offers high performance at a lower cost. Strength and opacity are comparable to conventional thermal transfer facers. Exceptional print quality, especially for flood coating. FSC®-certified paper. |                               | <b>V</b>          |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

| Minimum<br>Application Service Temp<br>Temp Range |                | •                                | Description  |
|---|----------------|----------------------------------|--|
| COLD-1  | ГЕМР           |                                  |  |
| 00552   | -20°F<br>-29°C | -65° to +120°F<br>-54° to +49°C  | Acrylic freezer adhesive used in many film wrapped meat and dairy applications, including the more difficult blast freeze environment.   |
| 00720   | -20°F<br>-29°C | -65° to +180°F<br>-54° to +82°C  | A soft, general purpose, all-temperature acrylic adhesive for paper and film labels. Adheres to a variety of packages in a broad range of temperatures. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.                        |
| 00853   | 0°F<br>-18°C   | -50° to +125°F<br>-46° to + 52°C | A cold-temperature acrylic adhesive, designed to run cleanly on press. Perfect for weigh scale applications.   |
| 0720M   | -20°F<br>-29°C | -65° to +180°F<br>-54° to +82°F  | A versatile cold-temperature acrylic adhesive that adheres to many packaging materials in a broad range of temperatures. Faster stripping than many cold-temp adhesives. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.       |
| PERMA   | NENT           |                                  |  |
| 00102   | +40°F<br>+4°C  | -40° to +160°F<br>-40° to +71°C  | A clear, water-resistant, acrylic film adhesive with high tack and peel. Adheres to a wide variety of surfaces. Offers a good balance between wet-out and repositionability. Meets APR Critical Guidance Recognition for HDPE containers with specific facers. |
| 00103   | +40°F<br>+ 4°C | -65° to +200°F<br>-54° to +93°C  | A soft, high performance film label acrylic adhesive with excellent clarity and adhesion to low energy surfaces, along with outstanding wet-out.   |
| 00406   | +10°F<br>-12°C | -40° to +300°F<br>-40° to +150°C | A permanent acrylic adhesive designed for film face stocks used in durable applications. Has high tack and excellent adhesion to low energy surfaces. An environmentally-friendly alternative to solvent adhesives.  |
| 00504   | +35°F<br>+ 2°C | -40° to +160°F<br>-40° to +71°C  | A general purpose acrylic emulsion used primarily with paper substrates.   |
| 00506   | +45°F<br>+ 7°C | -65° to +200°F<br>-54° to +93°C  | A general purpose acrylic emulsion adhesive with good UV stability. Non-yellowing, and generally used with film face stocks.   |
| 00508   | +45°F<br>+ 7°C | -65° to +200°F<br>-54° to +93°C  | A hard, acrylic adhesive. Useful for prime label pharmaceutical (pill bottles). Good for curved surfaces greater than 1/2" diameter requiring mandrel hold. Offers some reposition time on low-energy plastics. Glove friendly.                                |



### Green Bay Packaging Inc. Coated Products Operations

|       | Minimum<br>Application<br>Temp | Service Temp<br>Range             | Description   |
|-------|--------------------------------|-----------------------------------|---|
| PERMA | NENT (cont.)                   |                                   |   |
| 00515 | +40°F<br>+4°C                  | -40° to +250°F<br>-40° to +121°C  | A permanent, acrylic adhesive that has good water whitening resistance and adheres well to low surface energy plastics. Good combination of quick tack and high shear makes it ideal for mailing tabs.  |
| 00525 | +45° F<br>+7°C                 | -65°F to +200°F<br>-54°C to +93°C | A general purpose permanent, pharmaceutical acrylic adhesive. A higher coat weight version of 508. This adhesive is ideal for rough surfaces. Holds tight in difficult, small diameter applications. Repositionable on some surfaces.   |
| 00600 | -10°F<br>-23°C                 | -50° to +125°F<br>-46° to +52°C   | A permanent acrylic adhesive, which removes from glass bottles in a 100°F water bath. Designed for wine and other beverage labeling. Can be used in a wide range of temperatures, including cold applications. Removal times depend on facer and bottle type.   |
| 00700 | +35°F<br>+2°C                  | -65° to +200°F<br>-54° to +93°C   | A general purpose acrylic emulsion for paper. Repositions on many low energy plastics.  |
| 00747 | 0°F<br>-18°C                   | -65° to +200°F<br>-54° to +93°C   | A general purpose, acrylic permanent that displays excellent adhesion over a broad temperature range while providing aggressive performance. Perfect for wine labeling, as it can withstand ice bucket conditions.  |
| 00751 | +45°F<br>+7°C                  | -65° to +200°F<br>-54° to +93°C   | A paper and film compatible acrylic with good adhesion to many substrates. Excellent die-cutting and stripping. Exceptional mandrel hold.   |
| 00950 | 25°F<br>-4°C                   | -40° to +160°F<br>-40° to +71°C   | General purpose filmic adhesive designed for prime label applications. High shear properties leading to excellent press convertibility. Provides good open time for label repositioning. Performs at application temperatures as low as 25°F. Meets APR Preferred Design for Recycling on HDPE (colored) and PP substrates. |
| 00960 | 14°F<br>-10°C                  | -40° to +160°F<br>-40° to +71°C   | General purpose filmic adhesive designed for prime label applications. Excellent clarity and improved blush resistance. Higher shear film adhesive for improved press convertibility. Performs at application temperatures as low as 14°F. Meets APR Preferred Design for Recycling on HDPE (colored) and PP substrates.    |
| 0758M | +35°F<br>+2°C                  | -65° to +200°F<br>-54° to +93°C   | An acrylic general purpose permanent adhesive with great die-cutting and stripping properties. Adheres well to many substrates, including corrugated.   |
| 0776S | +25°F<br>-4°C                  | -65° to +200°F<br>-54° to +93°C   | A general-purpose acrylic adhesive designed for PET recycling. Will wash off PET clamshells, bottles, and other containers during recycling leaving no adhesive residue behind. When combined with specific facers it has APR Critical Guidance Recognition.  |



### Green Bay Packaging Inc. Coated Products Operations

Minimum

|       | Application<br>Temp | Service Temp<br>Range             | Description  |
|-------|---------------------|-----------------------------------|--|
| REMOV | /ABLE               |                                   |  |
| 00272 | +20°F<br>-7°C       | -10° to +120°F<br>-23° to +49°C   | Non-toxic paper removable microsphere acrylic adhesive with good clean removal. Great choice for kiddie stickers, business forms, and price labels.  |
| 00275 | +35°F<br>+2°C       | +20° to +120°F<br>-7° to +49°C    | Most universal acrylic microsphere adhering to corrugated, glass, metal, and plastics. No residue on glass or credit cards. Repositionable. Not recommended for small labels, or flood coated applications. Repulpable when applied to paper face stocks.    |
| 00278 | +20°F<br>-7°C       | -10 to +120°F<br>-23 to +49°C     | Ultra-removable microsphere acrylic adhesive for paper face stocks. Adheres to, and removes cleanly from, a variety of substrates. Perfect for kiddie stickers, and short-term labeling such as price marking, promotions, and logistics.                    |
| 00347 | +35°F<br>+2°C       | -40° to +180°F<br>-40° to +82°C   | Specialized removable acrylic for film face stocks. Has low peel and no-build properties. Designed for clean and easy removal from glass even after extended periods of time and temperature changes.  |
| 00531 | +40°F<br>+4°C       | 0° to +140°F<br>-18° to +60°C     | General purpose removable acrylic adhesive for use with paper or film face stocks. Removes from some glass, plastic, and textile surfaces.   |
| 00532 | +35°F<br>+2°C       | -40° to +160°F<br>-40° to +71°C   | Textile acrylic adhesive that removes cleanly from most fabrics. Not recommended for leather, suede or silk. Be sure to test. All textile applications are different.  |
| 00538 | +45°F<br>+7°C       | 0° to +160°F<br>-18° to +71°C     | A moderate-to-tight acrylic removable for use with films and strong paper face stocks.   |
| 00611 | +21°F<br>-6°C       | -40° to +172°F<br>-40° to +78°C   | A water dissolvable acrylic adhesive. It adheres to, and washes off, many substrates including most plastics, stainless steel and glass. Combined with the dissolvable facer, H2ODP, the label disappears in 30 seconds. Can be used with other face stocks. |
| 00633 | 30°F<br>-1°C        | -65° to +200° F<br>-54° to +93° C | An aggressive removable acrylic adhesive with a clean release for paper and film labels. It adheres to, and removes from, a wide variety of surfaces. Does not ghost. Good mandrel hold. Ideal for resealable closure labels.                                |
| 00805 | 0°F<br>-18°C        | -50° to +125°F<br>-46° to +52°C   | A lighter tack acrylic adhesive for kiddie stickers. Can also be used for other applications requiring short-term removability. Works in a wide range of temperatures.   |
| 80361 | 0°F<br>-18°C        | -50° to +125°F<br>-46° to +52°C   | Acrylic adhesive designed for short-term removability. Consider for kiddie stickers.   |



### Green Bay Packaging Inc. Coated Products Operations

|       | Minimum                                |                                   |  |
|-------|--|-----------------------------------|--|
|       | Application Service Temp<br>Temp Range |                                   | Description  |
| RECYC | LABLE                                  |                                   |  |
| 00611 | +21°F<br>-6°C                          | -40° to +172°F<br>-40° to +78°C   | A water dissolvable acrylic adhesive. It adheres to, and washes off, many substrates including most plastics, stainless steel and glass. Combined with the dissolvable facer, H2ODP, the label disappears in 30 seconds. Can be used with other face stocks.   |
| 00720 | -20°F<br>-29°C                         | -65° to +180°F<br>-54° to +82°C   | A soft, general purpose, all-temperature acrylic adhesive for paper and film labels. Adheres to a variety of packages in a broad range of temperatures. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.                        |
| 00757 | +32°F<br>+0°C                          | -58° to +199°F<br>-50° to +93°C   | A permanent acrylic adhesive with an aggressive bond to many surfaces, including low-energy plastics and corrugated. Harder adhesive for clean converting. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.                     |
| 0548S | +45°F<br>+7°C                          | -65° to +200° F<br>-54° to +93° C | A hard, repositionable acrylic adhesive. Good mandrel hold for small diameter applications. It meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.   |
| 0720M | -20°F<br>-29°C                         | -65° to +180°F<br>-54° to +82°F   | A hard, versatile cold-temperature acrylic adhesive that adheres to many packaging materials in a broad range of temperatures. Faster stripping than many cold-temp adhesives. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility. |
| 0760S | +35°F<br>+2°C                          | -65° to +200° F<br>-54° to +93° C | General purpose permanent acrylic adhesive. Adheres well to many substrates, including corrugated. Great die-cutting and stripping properties. Meets the TLMI Recycling Protocol TLMI-LRP-2 for paper recycling compatibility.                                 |
| 0776S | +25°F<br>-4°C                          | -65° to +200°F<br>-54° to +93°C   | A general-purpose acrylic adhesive designed for PET recycling. Will wash off PET clamshells, bottles, and other containers during recycling leaving no adhesive residue behind. When combined with specific facers it meets APR Critical Guidance protocol.    |



### Green Bay Packaging Inc. Coated Products Operations

### **LINER SELECTION GUIDE**

| Title                                    | Code  | Target<br>(Mils)<br>(Microns) | Description  |
|--|-------|-------------------------------|--|
| PAPER ROLL-TO-ROLL                       |       |                               |  |
| 1.7 MIL WHITE GLASSINE                   | 17GL  | 1.7<br>43.0                   | A 28# (45 g/m²) white glassine provides an excellent surface for die-cutting. The thinner gauge allows more labels on a roll, and the lighter weight provides lower shipping costs saving you and your customers time and money. |
| 2.4 MIL NATURAL KRAFT LINER              | 39NK  | 2.4<br>61.0                   | Produced without bleaching, this is a more environmentally-friendly, 39# (64 g/m²) super calendered densified kraft liner offering good die-cutting and stripping. Can be recycled with corrugated.                              |
| 2.4 MIL SEMI-BLEACHED<br>DENSIFIED KRAFT | 40SC  | 2.4<br>61.0                   | A white densified kraft sheet 41# (67 g/ $m^2$ ) with excellent point-to-point caliper control.  |
| 41# WHITE KRAFT LINER                    | 41WK  | 2.7<br>69.0                   | A premium, 41# (66 g/m²) white kraft liner that is designed for roll-to-roll and fan-fold applications. Outstanding performance die cutting both paper and film.   |
| 3.2 MIL SEMI-BLEACHED<br>DENSIFIED KRAFT | 50SC  | 3.2<br>81.0                   | A white densified kraft sheet 53# (86 g/m²) with excellent point-to-point caliper control.   |
| PAPER ROLL-TO-SHEET                      |       |                               |  |
| 3.4 MIL LASER LINER                      | 0PBLF | 3.4<br>87.0                   | A premium, 50# (82 g/m²) white kraft liner that is designed for roll-to-sheet and fan fold applications. Ideal for smooth feeding in desktop laser and inkjet printers. Suitable for die cutting both paper and film.            |
| 3.2 MIL CLAY COATED LAY FLAT             | 0PRLF | 3.2<br>82.0                   | A premium, 53# (87 g/m²) white kraft liner. Suitable for roll-to-sheet and fan fold applications. Designed for four-color process printing on the back side. Can be used for die cutting both paper and film.                    |
| 3.2 MIL KRAFT LAY FLAT                   | 32KLF | 3.2<br>81.0                   | Designed for roll-to-sheet and fan fold applications, 32KLF is a premium, white kraft 45# (73 g/m²) liner. It is back side printable. This liner can be used with both paper and film facestocks.                                |
| 2.7 MIL LASER LINER                      | 41LF  | 2.7<br>69.0                   | A premium, 41# (66 g/m²) white kraft liner that is designed for roll-to-sheet and fan fold applications. Ideal for smooth feeding in desktop laser and inkjet printers. Suitable for die cutting both paper and film.            |
| 3.2 MIL PRINTABLE LAY FLAT<br>LINER      | 53CRT | 3.2<br>81.0                   | A 54# (88 g/m²) blue-white kraft liner. Good dimensional stability for roll-to-sheet lay flat applications. Features a coated back side for a premium appearance and flexo printability. Suitable for charity mailing labels.    |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.

### **LINER SELECTION GUIDE**

| Title                                  | Code | Target<br>(Mils)<br>(Microns) | Description   |
|--|------|-------------------------------|---|
| PAPER ROLL-TO-SHEET (cont.)            |      |                               |   |
| 3.5 MIL CLAY COATED LAY FLAT           | 60LF | 3.5<br>88.0                   | A 56# (92 g/m²) liner with high white visual appeal. Ideal for sheeted or fan fold applications. Designed for four-color process printing on the back side.   |
| 4.6 MIL LAY FLAT LINER                 | 74LF | 4.6<br>117.0                  | A white 74# (121 g/m²) kraft liner that offers good dimensional stability for roll-to-sheet applications. Perfect for facer materials and applications that need extra rigidity to lay flat.  |
| FILM                                   |      |                               |   |
| 1.2 MIL CLEAR POLYESTER                | 12NB | 1.2<br>30.0                   | Clear polyester with an excellent surface for die-cutting. Great strength for high speed converting and application.  |
| 1.2 MIL CLEAR POLYESTER                | 12PE | 1.2<br>31.0                   | Clear polyester liner with a firm surface for die-cutting. Easy release for high speed converting and application.  |
| 1.4 MIL CLEAR POLYESTER                | 15PT | 1.4<br>36.0                   | Clear polyester liner with an excellent surface for die-cutting and high speed automatic applications.  |
| .92 MIL CLEAR POLYESTER                | 92NB | 0.9<br>23.0                   | Clear polyester with an excellent surface for die-cutting. Great strength for high speed converting and application. The benefits of this thinner gauge liner include reducing plastic use, decreasing shipping weight, and allowing more labels on a roll. |
| POLY KRAFT                             |      |                               |   |
| 3.1 MIL NATURAL<br>KRAFT/POLYPROPYLENE | 44PM | 3.1<br>72.0                   | A 44# (72 g/m²) natural kraft liner extrusion coated with polypropylene. Designed to prevent V-type tears and is an excellent choice for high speed automatic applications. Commonly used in wine label applications.                                       |



# Green Bay Packaging Inc. Coated Products Operations

All statements, technical information and recommendations about Green Bay Packaging Inc. products are based upon tests believed to be reliable, but do not constitute a guarantee or warranty. All products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purpose.

No salesperson, representative, or agent of Green Bay Packaging Inc. is authorized to give any guarantee, warranty, or make any representation contrary to the above. The company's standard Terms and Conditions (found in the current Green Bay Packaging Inc. - Coated Products Operations, Roll Printer Price Book) in effect at the time of the sale shall control.



| acer  | Adhesive  | Liner          | Item                           | Approx Wgt/<br>MMSI    | GB               | W WIN        | MIN        | ≤       |
|---|---|----------------|--------------------------------|------------------------|------------------|--------------|------------|---------|
| VHITE PAPERS - H                                    | IGH-GLOSS   |                |                                |                        |                  |              |            |         |
| 7# CAST COATED HIGH                                 | I-GLOSS OPAQUE  |                |                                |                        |                  |              |            |         |
| 57# (85 g/m²) high-gloss on a glossy surface.       | paper (057HG) with a gray b   | parrier opaqu  | ue coating for us              | se as cover-up labels. | . Use this facer | when cov     | ering ima  | ges     |
| 057HA   | 00720   | 40SC           | S8257960                       | 244                    | C                |              |            |         |
| 7# CAST COATED HIGH                                 |   |                |                                |                        |                  |              |            |         |
| 57# (85 g/m²) high-gloss                            | s sheet with a smooth, reflect  | tive surface ( | designed for top               | -quality graphic repro | duction.         |              |            |         |
| 057HG   | 00504   | 40SC           | S7823760                       | 248                    | C                |              | 1          |         |
| 057HG   | 00720   | 40SC           | S7824560                       | 244                    | I                | 1            | 1          | I       |
| 057HG   | 00747   | 40SC           | S7813760                       | 246                    | C                |              |            |         |
| 057HG   | 00751   | 40SC           | S8060260                       | 249                    | C                |              | 1          |         |
| 057HG   | 00751   | 40SC           | S8941560                       | 242                    | C                | 1            |            |         |
|   | ndered high-gloss sheet. Th<br>and suitable for process prin<br>00720 |                | S7146060                       | 252                    | C                |              | To paper   |         |
| VHITE PAPERS - S                                    | EMI-GLOSS   |                |                                |                        |                  |              |            |         |
| 3# SEMI-GLOSS OPAQU                                 |   |                |                                |                        |                  |              |            |         |
| 53# (78 g/m²) semi-gloss                            | with a gray opaque barrier of surface for attractive graphic          | _              | _                              |                        | . Excellent opa  | city, so the | e errors w | ill not |
| 054SA   | 00720   | 40SC           | S8820660                       | 232                    | 1                |              |            |         |
|   |   |                |                                |                        |                  |              |            |         |
|   |   |                |                                |                        |                  |              |            |         |
|   |   |                |                                |                        |                  |              |            |         |
|   |   |                |                                |                        |                  |              |            |         |
| ocations: GB - Green Bay, WI<br>WIN - Winchester, V |   |                | Atlanta, GA<br>.os Angeles, CA |                        |                  | I - Inventor |            |         |



| Facer      |  | Adhesive                                      | Liner        | Item                       | Approx Wgt/<br>MMSI | GB | MIN     | ¥ Z<br>Z<br>Z | ATL  | 4 |
|------------|--|---|--------------|----------------------------|---------------------|----|---------|---------------|------|---|
| WHITE      | PAPERS - SEMI  | -GLOSS  |              |                            |                     |    |         |               |      |   |
| 53# SEN    | MI-GLOSS   |   |              |                            |                     |    |         |               |      |   |
|            | 78 g/m²) C1S bright blue-<br>oth surface provides exce |   |              |                            |                     |    | ping ar | nd die-cutt   | ing. |   |
| 0548       | SG   | 00278   | 40SC         | S8164560                   | 226                 | 1  |         |               |      |   |
| 0548       | SG .   | 00508   | 40SC         | S7558760                   | 235                 | C  |         |               |      |   |
| 0548       | 6G   | 00515<br>00515                                | 12NB<br>40SC | S9075360                   | 318                 |    |         |               |      |   |
| 0548       | SG   | 00532   | 40SC         | S8280160                   | 230                 | C  |         |               |      |   |
| 0548       | SG   | 00552   | 40SC         | S9931260                   | 236                 | 1  |         |               |      |   |
| 0549       | SG   | 00633   | 40SC         | S9175160                   | 233                 | 1  |         |               |      |   |
| 0548       | SG   | 00700   | 40SC         | S7755860                   | 238                 | 1  |         |               |      |   |
| 0548       | SG .   | 00700   | 40SC         | S8861360                   | 235                 | C  |         |               |      |   |
| 0548       | SG .   | 00720   | 40SC         | S7724460                   | 231                 | 1  | 1       | 1 1           | 1    | 1 |
| 0548       | SG .   | 00720   | 12NB         | S8121860                   | 197                 | 1  | 1       |               |      | 1 |
| 0548       | SG .   | 00751   | 40SC         | S7748960                   | 238                 | 1  | 1       | 1 1           |      | 1 |
| 0548       | SG .   | 00751   | 40SC         | S8895960                   | 235                 | C  |         |               | 1    |   |
| 0548       | SG .   | 00805   | 0PRLF        | S8941160                   | 258                 | 1  |         |               |      |   |
| 0548       | SG .   | 0720M   | 40SC         | S8849360                   | 234                 | 1  | 1       |               | 1    | 1 |
| 0548       | SG .   | 0758M<br>0758M                                | 40SC<br>50SC | S7686660                   | 375                 | C  |         |               |      |   |
| 0548       | SG .   | 0758M<br>0758M                                | 40SC<br>40SC | S8027060                   | 354                 | 1  |         |               |      |   |
| 0549       | 6G   | 0758M   | 0PRLF        | S8082660                   | 262                 | 1  | 1       | 1             |      |   |
| 0548       | SG .   | 0758M   | 41LF         | S9176660                   | 234                 | 1  | 1       |               |      |   |
| 0548       | SG .   | 80361   | 0PRLF        | S8001560                   | 262                 |    |         |               |      |   |
| Locations: | GB - Green Bay, WI<br>WIN - Winchester, VA             | KC - Kansas City, MO<br>MIN - Minneapolis, MN |              | Atlanta, GA os Angeles, CA |                     |    | I - Inv | ventory       |      |   |

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

TIP Item



| acer                    | Adhesive  | Liner | Item     | Approx Wgt/<br>MMSI  | GB WIN MIN ATL                                      | 4   |
|-------------------------|---|-------|----------|----------------------|---|-----|
| WHITE PAPERS - S        | SEMI-GLOSS  |       |          |                      |   |     |
| 4# WET STRENGTH SE      | MI-GLOSS  |       |          |                      |   |     |
| , ,                     | white semi-gloss. Wet streng<br>oth surface enhances print re |       |          |                      | ges, including beer and wine, or ®-certified paper. |     |
| 054WS                   | 00747   | 40SC  | S8901460 | 238                  |   |     |
| 054WS                   | 00747   | 12NB  | S8906760 | 201                  | С   |     |
|                         |   | 12.10 | 00000700 |                      |   |     |
| EMI-GLOSS PREFERR       | ED OPAQUE   |       |          |                      |   |     |
|                         | ss Preferred (060PR) with a g                                 |       |          | Designed for cover u | up labels. Excellent print surface w                | ith |
| 60# (88.8/m²) Semi-Glos | ss Preferred (060PR) with a g                                 |       |          | Designed for cover u |   | ith |

| 060PR | 00272 | 40SC | S7018060 | 245 | • • • • • • |
|-------|-------|------|----------|-----|-------------|
| 060PR | 00275 | 41WK | S9156360 | 241 |             |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

toner, or offset. FSC®-certified paper.



| cer               | Adhesive   | Liner | Item              | Approx Wgt/<br>MMSI   | GB            | WIN WIN      | Σ      | ATL      |
|-------------------|--|-------|-------------------|-----------------------|---------------|--------------|--------|----------|
| VHITE PAPERS - SE | EMI-GLOSS  |       |                   |                       |               |              |        |          |
| 8# SEMI-GLOSS     |  |       |                   |                       |               |              |        |          |
|                   | multi-purpose paper with sud printing. FSC®-certified p  |       | and print qualiti | es. Bright blue-white | shade. Excell | ent graphi   | c resu | lts wit  |
| 060SG             | 00720  | 40SC  | S7804560          | 244                   | 1             | 1            |        | 1        |
| 060SG             | 00747  | 40SC  | S7813460          | 244                   | C             |              |        |          |
| 060SG             | 00751  | 40SC  | S7821360          | 249                   | C             |              |        |          |
| 060SG             | 0720M  | 40SC  | S8899160          | 244                   | 1             | 1 1          |        |          |
| 060SG             | 0758M  | 60LF  | S8003760          | 280                   | C             | I            |        |          |
| 0# SEMI-GLOSS     |  |       |                   |                       |               |              |        |          |
| , , ,             | multi-purpose paper with ser sheet offers greater stiffr |       |                   | 0                     | shade. Excel  | lent print s | surfac | e for fl |
| 080SG             | 00720  | 40SC  | S8153960          | 290                   | C             |              |        |          |
| 080SG             | 00751  | 60LF  | S8732360          | 331                   | C             |              |        |          |
| 080SG             | 0758M  | 40SC  | S8098160          | 294                   | C             |              |        |          |
|                   |  |       |                   |                       |               |              |        |          |

| F54SG | 00720 | 40SC | S8792860 | 234 | C |
|-------|-------|------|----------|-----|---|
| F54SG | 00747 | 40SC | S7739560 | 232 |   |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



|   | DIG LIVOUGIT I    | OSLINI | TOO, SWALL LI | VOOGIT TO KIVOW     | 100                                      |
|---|-------------------|--------|---------------|---------------------|--|
| Facer   | Adhesive          | Liner  | ltem          | Approx Wgt/<br>MMSI | GB WIN MIN ATL                           |
| WHITE PAPERS - SE                                       | MI-GLOSS          |        |               |                     |  |
| 60# SEMI-GLOSS WITH 30%                                 | 6 POST-CONSUMER V | VASTE  |               |                     |  |
| A 60# (89 g/m²)semi-gloss fapplication. Smooth print su |                   |        | ,             | 0                   | acteristics enhance label converting and |
| R60SG   | 00720             | 40SC   | S8187460      | 248                 | C  |
| R60SG   | 00720             | 39NK   | S8743660      | 246                 | CI                                       |
| WHITE PAPERS - MA                                       | TTE               |        |               |                     |  |

#### **60# LITHO MATTE**

A 60# (89 g/m²) clay-coated matte smooth paper. Offers a great printing surface for excellent graphic reproduction. Its very matte appearance provides a unique look in package design. Perfect for flexo printing and in a variety of digital presses.

| 060LM | 00720 | 40SC | S8842760 | 251 | C |  |
|-------|-------|------|----------|-----|---|--|
| 060LM | 00751 | 40SC | S8830560 | 251 | C |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



| Facer WHITE PAPERS - MATTE  | Adhesive        | Liner           | Item            | Approx Wgt/<br>MMSI    | GB                | N N          | MIN | 4 | _ |
|---|-----------------|-----------------|-----------------|------------------------|-------------------|--------------|-----|---|---|
| 60# DULL LITHO 60# (89 g/m²) high quality, dull finish litl FSC®-certified paper. | ho offering exc | ellent print ar | nd die-cut prop | erties. Good for flexo | ographic and offs | set printing | j.  |   |   |
| 061DL   | 00504           | 40SC            | S7754060        | 253                    | C                 |              |     |   |   |
| 061DL   | 00700           | 40SC            | S7746460        | 253                    | C                 |              |     |   |   |
| 061DL   | 00720           | 40SC            | S4331060        | 251                    |                   |              |     |   |   |
| 061DL   | 00751           | 40SC            | S7752260        | 253                    | C                 |              |     |   |   |
| 061DL   | 00751           | 32KLF           | S8047760        | 263                    | C                 |              |     |   |   |
| 061DL   | 0758M           | 0PRLF           | S8003060        | 277                    |                   |              |     |   |   |
| 061DL   | 0758M           | 40SC            | S8769360        | 245                    |                   |              |     |   |   |
| WHITE PAPERS - INDIGO TO  | PCOATED         | )               |                 |                        |                   |              |     |   |   |

#### **INDIGO TOPCOATED 55# SEMI-GLOSS**

55# (81 g/m²) semi-gloss sheet designed for printing on HP Indigo presses. It has been certified by RIT for use on the ws4500 and ws6000 presses. Has a blue-white shade with high brightness and opacity. Exceptionally strong. FSC®-certified paper.

| D55SG | 00720 | 40SC | S8142460 | 239 | C |  |
|-------|-------|------|----------|-----|---|--|
| D55SG | 00751 | 40SC | S8126960 | 237 | C |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



| cer   | Adhesive       | Liner | Item             | Approx Wgt/<br>MMSI | GB              | N N     | K      | Σ      | ATL    | _    |
|---|----------------|-------|------------------|---------------------|-----------------|---------|--------|--------|--------|------|
| AG STOCK  |                |       |                  |                     |                 |         |        |        |        |      |
| POINT GLOSS WHITE C                                       | LAY COATED TAG |       |                  |                     |                 |         |        |        |        |      |
| A glossy, bright white, 130# in a pressure-sensitive stru |                |       | characteristics. | Coated on both side | es, allowing fo | r multi | ple us | es - a | s a ta | g, d |
| 008GB   | 00504          | 40SC  | S9941860         | 398                 | 1               |         |        |        |        |      |
| 008GB   | 00532          | 40SC  | S9941260         | 395                 | C               |         |        |        |        |      |
| 008GB   | 00751          | 40SC  | S766660          | 400                 | C               | 1       |        |        |        |      |
|   |                |       |                  |                     |                 |         |        |        |        |      |

| 050ED | 00700          | 50SC         | S7032060 | 252 | C |
|-------|----------------|--------------|----------|-----|---|
| 050ED | 00720          | 40SC         | S6069060 | 228 |   |
| 050ED | 00720          | 50SC         | S6499060 | 249 |   |
| 050ED | 0758M          | 50SC         | S7648760 | 248 | C |
| 050ED | 0758M          | 40SC         | S7648960 | 231 | C |
| 050ED | 0758M<br>0758M | 40SC<br>40SC | S7725060 | 356 | C |

#### **PHARMACEUTICAL**

#### PHENOL-FREE DIRECT THERMAL PRESCRIPTION VIAL LABEL

This 48# (71 g/m²), phenol-free, top-coated paper resists chemicals, including cleaners, hand sanitizers and lotions. Holds up in heat and humidity. Vital drug information remains legible under most handling and storage conditions. FSC®-certified paper.

| 021RX | 00751 | 40SC | S9174660 | 229 |  |
|-------|-------|------|----------|-----|--|
|       |       |      |          |     |  |

| Locations: | GB - Green Bay, WI   | KC - Kansas City, MO  | ATL - Atlanta, GA    | I - Inventory       |
|------------|----------------------|-----------------------|----------------------|---------------------|
|            | WIN - Winchester, VA | MIN - Minneapolis, MN | LA - Los Angeles, CA | C - Custom TIP Item |
|            |                      |                       |                      | TH ICH              |



| cer   | Adhesive  | Liner                                 | ltem   | Approx Wgt/<br>MMSI                      | GB             | NIN NIN | Š<br>Š   | Z       | ATL     | ≤   |
|---|---|---------------------------------------|--|--|----------------|---------|----------|---------|---------|-----|
| HARMACEUTICAL   |   |                                       |  |  |                |         |          |         |         |     |
| # PHARMACEUTICAL LIT  | гно   |                                       |  |  |                |         |          |         |         |     |
| 40# (60 g/m²) lightweight C1  | 1S semi-gloss litho with go   | ood ink holdd                         | out. Candidate for   | or pharmaceutical a                      | nd nutritional | labelin | g.       |         |         |     |
| 040PL   | 00751   | 40SC                                  | S5545060   | 209                                      | C              |         |          |         |         |     |
| LUORESCENT PAPE   | ERS   |                                       |  |  |                |         |          |         |         |     |
| UE FLUORESCENT  |   |                                       |  |  |                |         |          |         |         |     |
| 57# (84 g/m²) blue matte flu  | orescent coated paper. Destand out. Offers another                      |                                       |  |  |                | al roll | label a  | applica | ations. |     |
|   |   |                                       | 0  |  |                |         |          |         |         |     |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl FSC®-certified paper.   | 00720   | 40SC                                  | S8122860   | 239<br>ce marking, promoti               | onal and gen   | eral ro | II label | appli   | cations | S.  |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl   |   | 40SC                                  | S8122860   |  | onal and gen   | eral ro | II label | appli   | cations | S.  |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl FSC®-certified paper.   | luorescent coated paper.  | 40SC  Designed for                    | S8122860   | ce marking, promoti                      | onal and gen   | eral ro | II label | appli   | cations | S.  |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl FSC®-certified paper.  054GZ  | luorescent coated paper.  | 40SC  Designed for 40SC               | \$8122860<br>Laser, inkjet, pri<br>\$6231060   | ce marking, promoti<br>239               | onal and gen   | eral ro | II label | appli   | cations | SS. |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl FSC®-certified paper.  054GZ  054GZ   | luorescent coated paper. 00720  | 40SC Designed for 40SC 40SC           | \$8122860<br>Sec., inkjet, pri<br>\$6231060<br>\$7656360                             | ce marking, promoti<br>239<br>239        | onal and gen   | eral ro | II label | appli   | cations | SS. |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl FSC®-certified paper.  054GZ  054GZ  054GZ  | 00720<br>00720<br>0758M   | 40SC  Designed for  40SC  40SC  0PBLF | \$8122860<br>Relaser, inkjet, pri<br>\$6231060<br>\$7656360<br>\$8189860             | ce marking, promoti<br>239<br>239<br>262 | C<br>I         |         |          | 1       |         |     |
| 054BZ  REEN FLUORESCENT 57# (84 g/m²) green matte fl FSC®-certified paper.  054GZ 054GZ 054GZ  RANGE FLUORESCENT 57# (84 g/m²) orange matte                           | 00720<br>00720<br>0758M   | 40SC  Designed for  40SC  40SC  0PBLF | \$8122860<br>Relaser, inkjet, pri<br>\$6231060<br>\$7656360<br>\$8189860             | ce marking, promoti<br>239<br>239<br>262 | C<br>I         |         |          | 1       |         |     |
| 054BZ  REEN FLUORESCENT  57# (84 g/m²) green matte fl FSC®-certified paper.  054GZ  054GZ  054GZ  RANGE FLUORESCENT  57# (84 g/m²) orange matte FSC®-certified paper. | luorescent coated paper. I 00720 00720 0758M  fluorescent coated paper. | 40SC  Designed for  40SC  40SC  0PBLF | \$8122860  Flaser, inkjet, pri  \$6231060  \$7656360  \$8189860  or laser, inkjet, p | 239 239 262 rice marking, promo          | C<br>I         |         |          | 1       |         |     |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

C - Custom
TIP Item



| cer   | Adhesive                   | Liner          | Item                           | Approx Wgt/<br>MMSI          | GB            | × ×          | Σ        | ATL     |
|---|----------------------------|----------------|--------------------------------|------------------------------|---------------|--------------|----------|---------|
| LUORESCENT PAP  | ERS                        |                |                                |                              |               |              |          |         |
| NK FLUORESCENT  |                            |                |                                |                              |               |              |          |         |
| 57# (84 g/m²) pink matte flu<br>FSC®-certified paper.             | uorescent coated paper. De | esigned for la | aser, price mark               | king, inkjet, promotion      | al and genera | al roll labe | l applio | cations |
| 054PZ   | 00720                      | 40SC           | S7748660                       | 239                          | C             |              |          |         |
| 054PZ   | 00720                      | 40SC           | S8034360                       | 239                          | 1             |              |          |         |
| 054PZ   | 0758M                      | 0PBLF          | S8190160                       | 262                          |               |              |          |         |
|   |                            |                |                                |                              |               |              |          |         |
| ED FLUORESCENT  |                            |                |                                |                              |               |              |          | _       |
|   | orescent coated paper. De  | esigned for la | ser, inkjet, price             | e marking, promotiona        | al and genera | l roll label | applic   | ations. |
| ED FLUORESCENT<br>57# (84 g/m²) red matte flu                     | orescent coated paper. De  | esigned for la | ser, inkjet, price<br>S6066060 | e marking, promotiona<br>239 | al and genera | l roll label | applic   | ations. |
| ED FLUORESCENT  57# (84 g/m²) red matte flu FSC®-certified paper. |                            |                | , ,                            |                              | al and genera | I roll label | applic:  | ations  |

57# (84 g/m²) yellow chartreuse matte fluorescent coated paper. Designed for laser, inkjet, price marking, promotional and general roll label applications. FSC®-certified paper.

| 054YZ | 00720 | 40SC  | S6237060 | 239 | 1 |  |
|-------|-------|-------|----------|-----|---|--|
| 054YZ | 00720 | 40SC  | S7748760 | 239 | C |  |
| 054YZ | 0758M | 0PBLF | S8189960 | 262 | 1 |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



| acer                        | Adhesive  | Liner | Item        | Approx Wgt/<br>MMSI | GB WIN WIN LA ATL                                      |
|-----------------------------|---|-------|-------------|---------------------|--|
| BEER & WINE LA              | BEL   |       |             |                     |  |
| 4# WET STRENGTH S           | EMI-GLOSS   |       |             |                     |  |
| , - ,                       | e-white semi-gloss. Wet streng<br>both surface enhances print res |       |             | _                   | ges, including beer and wine, or<br>®-certified paper. |
| 054WS                       | 00747   | 40SC  | S8901460    | 238                 |  |
| 054WS                       | 00747   | 12NB  | S8906760    | 201                 | C  |
| LASSIC CREST* SOL           | AR WHITE SMOOTH   |       |             |                     |  |
| , , , .                     | uncoated white paper with an eucts. FSC®-certified paper. *R      |       |             |                     | ensional stability. Perfect for wine labels            |
| 0WCSW                       | 00747   | 44PM  | S8741852    | 258                 |  |
| STATE LABEL* #4 WI          | HITF I AID  |       |             |                     |  |
| 60# (89 g/m²) white, lai    |   |       | _           | *                   | for wine and beer labels. Its high-end d paper.        |
| 0WEL4                       | 00747   | 44PM  | S8748260    | 258                 |  |
|                             |   |       |             | _                   | and other high-end labels, such as                     |
| 0WEL8                       | 00747   | 12NB  | S8756060    | 216                 | С  |
| STATE LABEL* #9 CR          | EAM LAID  |       |             |                     |  |
| ( 0 /                       | d cream wet strength paper. Ma<br>SC®-certified paper. *Register  |       | 0 )         |                     | d other upscale labels, such as gourme                 |
| 0WEL9                       | 00747   | 44PM  | S8742160    | 258                 |  |
|                             |   |       |             |                     |  |
|                             |   |       |             |                     |  |
|                             |   |       |             |                     |  |
|                             |   |       |             |                     |  |
| ocations: GB - Green Bay, \ | NI KC - Kansas City, MO   |       | Atlanta, GA |                     | I - Inventory  |



| Facer  | Adhesive                                      | Liner | Item                           | Approx Wgt/<br>MMSI    | GB MIN ATL ATL  |
|--|---|-------|--------------------------------|------------------------|---|
| BEER & WINE LABE   | L   |       |                                |                        |   |
| SILVER METALIZED WET : 56# (83 g/m²) top coated si beverages. The metallic loc | lver metalized paper. Wet                     | _     |                                | vironments including r | refrigerated foods and chilled                        |
| 56MSW  | 00720   | 40SC  | S8982560                       | 241                    | •   |
| 70# BRIGHT WHITE FELT  |   |       |                                |                        |   |
| 70# (103 g/m²) uncoated be makes it ideal for upscale for                      | -   |       |                                | _                      | abels. The rich weight and texture                    |
| 70BWF  | 00747   | 44PM  | S8903652                       | 279                    |   |
| 70BWF  | 00747   | 12NB  | S8903752                       | 237                    |   |
| 60# (89 g/m²) uncoated, bla<br>beverage labels, its unique                     |   |       |                                |                        | ras designed for wine, beer, and other er.            |
| BKVLM  | 00747   | 44PM  | S8936852                       | 258                    | C   |
| 50# KONA LIGHT ROAST   |   |       |                                |                        |   |
| KONAL is a 50# (74g/m²), material. Perfect for labelin                         |   |       |                                |                        | an bag fiber and post-consumer waste certified paper. |
| KONAL  | 00720   | 39NK  | S8796760                       | 228                    |   |
| KONAL  | 00747   | 40SC  | S8939760                       | 232                    | С   |
| 60# 100% PCW WET STRE  | NGTH PAPER                                    |       |                                |                        |   |
| A 60# (89 g/m²) FSC®-cert applications, like wine, bee                         |   |       |                                | _                      | sture, it's perfect for beverage al care products.    |
| PLRNB  | 00720   | 39NK  | S9089960                       | 249                    |   |
|  |   |       |                                |                        |   |
| Locations: GB - Green Bay, WI<br>WIN - Winchester, VA                          | KC - Kansas City, MO<br>MIN - Minneapolis, MN |       | Atlanta, GA<br>Los Angeles, CA |                        | I - Inventory C - Custom TIP Item                     |



| acer  | Adhesive   | Liner   | Item   | Approx Wgt/<br>MMSI                               | MIN WIN                                | MIN ATL             | ≤   |
|---|--|---|--|---|--|---------------------|-----|
| SPECIALTY PAPER   |  | 20  | item   | MINIO   |  |                     |     |
| 54# WET STRENGTH SE   | MI-GLOSS   |   |  |   |  |                     |     |
|   | white semi-gloss. Wet strengtoth surface enhances print res  |   |  |   | _                                      | and wine, or        |     |
| 054WS   | 00747  | 40SC  | S8901460   | 238   |  |                     |     |
| 054WS   | 00747  | 12NB  | S8906760   | 201   | C                                      |                     |     |
| BROWN NATURAL KRAI  | FT   |   |  |   |  |                     |     |
|   | ural kraft paper. The natural loon corrugated containers.  | ook makes i                                     | t perfect for labe                                   | ling organic or other e                           | earth-friendly prod                    | ucts. It can also b | е   |
| 060GM   | 00720  | 40SC  | S8083760   | 264   | C                                      |                     | 1   |
| 060GM   | 0758M  | 40SC  | S7649360   | 264   |  |                     |     |
| 60# HEMP PAPER  |  |   |  |   |  |                     |     |
|   | nade with 25% hemp fibers and tent and a natural look it is als  |   |  | -   | _                                      | ther hemp produc    | ts. |
| 1HEMP   | 00720  | 39NK  | S9111352   | 246   |  |                     |     |
| RANSLUCENT PAPER  |  |   |  |   |  |                     |     |
| A 42# (62 g/m²) ultra-clea<br>a unique look for primary                               | ar translucent paper. It is wel  | -suited for v                                   | vafer seal mailing                                   | g tabs. Can be used f                             | or tamper-evident                      | anda Alaa musuda    |     |
|   |  |   |  |   | or tampor ovidoni                      | seals. Also provid  | les |
| 1TRCT   | 00515  | 40SC  | S9204660   | 211   | C                                      | seals. Also provid  | les |
| 1TRCT   |  | 40SC<br>40SC                                    | S9204660<br>S9193960                                 | 211<br>207  |  | seals. Also provid  | les |
|   | 00515  |   |  |   | С                                      | seals. Also provid  | les |
| 1TRCT   | 00515<br>00751   | 40SC  | S9193960   | 207   | С                                      | seals. Also provid  | les |
| 1TRCT  1TRCT  DISSOLVABLE PAPER  A water-soluble paper. C                             | 00515<br>00751   | 40SC<br>40SC<br>thesive, 611                    | \$9193960<br>\$9189960<br>, it disappears in         | 207<br>208<br>seconds under runni                 | C C C                                  |                     |     |
| 1TRCT  1TRCT  DISSOLVABLE PAPER  A water-soluble paper. C                             | 00515 00751 00757 Coated with the dissolvable ac   | 40SC<br>40SC<br>thesive, 611                    | \$9193960<br>\$9189960<br>, it disappears in         | 207<br>208<br>seconds under runni                 | C C C                                  |                     |     |
| 1TRCT  1TRCT  DISSOLVABLE PAPER  A water-soluble paper. C container. Best dissolvable | 00515 00751 00757 Coated with the dissolvable acole performance when printed 00611  KC - Kansas City, MO | 40SC 40SC dhesive, 611 d with water- 40SC ATL - | S9193960 S9189960 , it disappears in based inks. Kee | 207 208 seconds under runni o wrapped until used. | C C C mg water. Leaves FSC®-certified. |                     |     |



| Facer   | Adhesive | Liner | ltem     | Approx Wgt/<br>MMSI | GB | N N | Š      | Z     | ATL    | 4   |
|---|----------|-------|----------|---------------------|----|-----|--------|-------|--------|-----|
| SPECIALTY PAPERS  |          |       |          |                     |    |     |        |       |        |     |
| <b>50# KONA LIGHT ROAST</b> KONAL is a 50# (74g/m²), 1 material. Perfect for labeling | ,        | 0 1   |          |                     | 0  |     | st-cor | nsume | er was | ste |
| KONAL   | 00720    | 39NK  | S8796760 | 228                 | 1  |     |        |       |        |     |
| KONAL   | 00751    | 39NK  | S8841160 | 228                 | C  |     |        |       |        |     |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item



| Facer                   | Adhesive                                     | Liner          | Item            | Approx Wgt/<br>MMSI   | GB             | NIN    | Š        | ATL      | ≤   |
|-------------------------|--|----------------|-----------------|-----------------------|----------------|--------|----------|----------|-----|
| LAMINATED FOILS         |  |                |                 |                       |                |        |          |          |     |
| BRIGHT GOLD FOIL        |  |                |                 |                       |                |        |          |          |     |
| Top coated 70# (104 g/m | <sup>2</sup> ) bright gold laminated foil.   | Suitable for   | water based, U  | IV screen, UV flexo a | and embossing  | . FSC® | -certifi | ed pape  | ∍r. |
| 055BG                   | 00720  | 40SC           | S6301060        | 276                   | 1              |        |          |          | 1   |
| BRIGHT SILVER FOIL      |  |                |                 |                       |                |        |          |          |     |
| Top coated 70# (104 g/m | <sup>2</sup> ) bright silver laminated foil. | Suitable fo    | r water based,  | UV screen, UV flexo   | and embossin   | g. FSC | ®-certi  | fied pap | er. |
| 055BS                   | 00720  | 40SC           | S6299060        | 276                   | 1              | 1      |          |          | I   |
| 055BS                   | 00751  | 40SC           | S5732060        | 281                   | C              |        |          |          |     |
| DULL GOLD FOIL          |  |                |                 |                       |                |        |          |          |     |
| Top coated 70# (104 g/m | <sup>2</sup> ) dull gold laminated foil. Su  | uitable for w  | ater based, UV  | screen, UV flexo and  | d embossing. F | SC®-c  | ertified | l paper. |     |
| 055DG                   | 00720  | 40SC           | S6300060        | 276                   | 1              |        |          |          |     |
| DULL SILVER FOIL        |  |                |                 |                       |                |        |          |          |     |
| Top coated 70# (104 g/m | <sup>2</sup> ) dull silver laminated foil. S | Suitable for v | water based, U\ | / screen, UV flexo ar | nd embossing.  | FSC®-  | certifie | d papeı  |     |
| 055DS                   | 00720  | 40SC           | S6306060        | 276                   | 1              | 1      |          |          | 1   |
| 055DS                   | 00751  | 40SC           | S4601060        | 281                   | C              |        |          |          | 1   |
| FOIL SUBSTITUTES        | •  |                |                 |                       |                |        |          |          |     |

# FOIL SUBSTITUTES

### 1.85 MIL SILVER METALIZED BOPP

1.85 mil clear BOPP metalized on the back for durability. Top coated for print compatibility with water-based and UV flexo, and UV inkjet. Great stiffness for automatic application. Ideal for bright label graphics that will catch the eye of the consumer.

| 018MT | 00102 | 40SC | S9129360 | 182 | C |
|-------|-------|------|----------|-----|---|
| 018MT | 00102 | 12NB | S9133760 | 148 | C |
| 018MT | 00720 | 40SC | S9036760 | 181 |   |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

C - Custom
TIP Item

Additional hologram patterns available: Minimum customer order Qty is 18 MMSI Please allow 4 to 6 weeks for delivery

| Facer   | Adhesive   | Liner                | Item                 | Approx Wgt/<br>MMSI     | GB WIN ATL                                    |
|---|--|----------------------|----------------------|-------------------------|---|
| FOIL SUBSTITUTES                                  | 5  |                      |                      |                         |   |
| 2.0 MIL SILVER METALIZ                            | -  |                      | _                    |                         |   |
| A 2.0 mil BOPP metalize                           | d on the back side for a shing                           | y silver appe        | earance. Top co      | ated for printability w | vith a wide range of ink systems.             |
| 021MU   | 00102  | 40SC                 | S8056060             | 188                     | C   |
| 021MU   | 00720  | 40SC                 | S8031460             | 186                     |   |
| 021MU   | 00751  | 40SC                 | S7345060             | 191                     | C   |
| HOLOGRAM PRISMATIC                                | DIFFRACTION: RAINBO                                      | DW W                 |                      |                         |   |
|   |  |                      |                      |                         | terial. This gap in the pattern will be up to |
| 1/32" wide. The area bet                          | ween the shim lines measure                              | es 30" mach          | ine direction (M     | D) and 48" cross dire   | ection (CD).                                  |
| 056H5   | 00751  | 40SC                 | S4607060             | 253                     |   |
| 056H7<br>056H7                                    | 00504<br>0758M<br>0758M                                  | 40SC<br>40SC<br>40SC | S2344060<br>S8265860 | 252<br>375              | С   |
| 56# SILVER METALIZED                              | PAPER  |                      |                      |                         |   |
| 56# (83 g/m²) top coated                          | silver metalized paper. Not r                            | ecommende            | ed for HP Indigo     | Presses.                |   |
| 057MS   | 00720  | 40SC                 | S6203060             | 241                     |   |
| 057MS   | 00751  | 40SC                 | S5841060             | 242                     | X = 0 = 0                                     |
| SILVER METALIZED WE                               | T STRENGTH PAPER   |                      |                      |                         |   |
|   | silver metalized paper. Wet look makes a product's graph | _                    |                      | vironments including    | refrigerated foods and chilled                |
| 56MSW   | 00720  | 40SC                 | S8982560             | 241                     |   |
|   |  |                      |                      |                         |   |
| Locations: GB - Green Bay, WI WIN - Winchester, V | •  |                      | Atlanta, GA          |                         | I - Inventory<br>C - Custom                   |

- Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA C - Custom
TIP Item

Additional hologram patterns available: Minimum customer order Qty is 18 MMSI Please allow 4 to 6 weeks for delivery



| acer  | Adhesive  | Liner            | Item                         | Approx Wgt/<br>MMSI                 | GB KG                 | MIN ATL       |
|---|---|------------------|------------------------------|-------------------------------------|-----------------------|---------------|
| THERMAL TRANSFE   | R   |                  |                              |                                     |                       |               |
| 2.6 MIL THERMAL TRANSF  | ER WHITE LABEL-LY1  | <b>ГЕ</b> ТМ     |                              |                                     |                       |               |
| 2.6 mil White Label-Lyte BO long-term performance, is r   |   |                  | 0                            | 0 0 11                              | ons where moisture re | esistance, or |
| 026TT   | 00747   | 40SC             | S8773660                     | 192                                 |                       |               |
|   |   |                  |                              |                                     |                       |               |
| HERMAL TRANSFER WH  | ITE LABEL-LYTE™   |                  |                              |                                     |                       |               |
| THERMAL TRANSFER WH  3.0 mil White Label-Lyte BO long-term performance, is in   | OPP with a thermal transfer   |                  | 0                            | 0 0 11                              | ons where moisture re | esistance, or |
| 3.0 mil White Label-Lyte B0   | OPP with a thermal transfer   |                  | 0                            | 0 0 11                              | ons where moisture re | esistance, or |
| 3.0 mil White Label-Lyte BC long-term performance, is in 030TT  | OPP with a thermal transfermportant. Label-Lyte is a T  | rademark of      | Jindal Films Am              | erica.                              |                       | esistance, or |
| 3.0 mil White Label-Lyte BC long-term performance, is in 030TT  | OPP with a thermal transfermportant. Label-Lyte is a T 00747  | rademark of      | S5213060                     | erica.                              | C                     | -             |
| 3.0 mil White Label-Lyte BC long-term performance, is in 030TT  HIGH SPEED COATED THE 47# (70 g/m²) premium brig        | OPP with a thermal transfermportant. Label-Lyte is a T 00747  | rademark of      | S5213060                     | erica.                              | C                     | -             |
| 3.0 mil White Label-Lyte BC long-term performance, is in 030TT  HIGH SPEED COATED THE 47# (70 g/m²) premium brig paper. | OPP with a thermal transfermportant. Label-Lyte is a T 00747  ERMAL TRANSFER iht white, coated, ultra-smo | 40SC oth thermal | S5213060  transfer paper str | erica.  199  ock offering broad rik | C                     | -             |

00747 40SC

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA  ${\bf C}$  - Custom TIP Item

S8149152

214

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

075WP



| Facer  | Adhesive            | Liner     | ltem               | Approx Wgt/<br>MMSI     | GB             | NIN      | 5      | Z    | ATL    | 4 |
|--|---------------------|-----------|--------------------|-------------------------|----------------|----------|--------|------|--------|---|
| THERMAL TRANSFER   | 7141100110          |           |                    | NIIIIOI                 |                |          |        |      |        |   |
| TOP COATED KIMDURA® FPG 95   |                     |           |                    |                         |                |          |        |      |        |   |
| A 4.2 mil Kimdura® BOPP specially<br>Neenah Paper, Inc. © 2007 NPI All I |                     |           | er, dot matrix, io | n deposition and digita | al printing. R | egiste   | red Tr | adem | ark of | f |
| 095TK  | 00506               | 40SC      | S3252060           | 256                     | 1              |          |        |      |        |   |
| 095TK  | 00506               | 50SC      | S3256060           | 272                     | C              |          |        |      |        |   |
| 095TK  | 00538               | 50SC      | S3286060           | 272                     | 1              |          |        |      |        |   |
| 095TK  | 00751               | 50SC      | S5391060           | 273                     | 1              |          |        |      |        |   |
| enhanced flexo graphics. FSC®-cer  | tified paper. 0758M | 40SC      | S7711260           | 218                     |                |          |        |      |        |   |
| SELECT THERMAL TRANSFER  |                     |           |                    |                         |                |          |        |      | —      | — |
| A 44# (65 g/m²) multi-purpose therm                                      | nal transfer sheet. | Premium c | oating for enhar   | nced flexo-printed grap | ohics. FSC®    | -certifi | ed pa  | per. |        |   |
| 0TTFP  | 00531               | 40SC      | S7843160           | 216                     | 1              |          |        |      |        |   |
| 0TTFP  | 00700               | 40SC      | S6745060           | 218                     | C              |          |        | 1    |        |   |
| 0TTFP  | 00720               | 40SC      | S7833160           | 214                     | 1              |          | 1      | 1    | 1      |   |
| 0TTFP  | 00751               | 40SC      | S6613060           | 216                     | C              |          |        |      |        |   |
| 0TTFP  | 0758M               | 40SC      | S7664660           | 215                     | 1              | 1        | 1      | 1    |        | 1 |

| Locations: | GB - Green Bay, WI<br>WIN - Winchester, VA | KC - Kansas City, MO<br>MIN - Minneapolis, MN | ATL - Atlanta, GA<br>LA - Los Angeles, CA | I - Inventory<br>C - Custom<br>TIP Item |
|------------|--|---|---|---|
|            |  |   |   |   |



| Facer   | Adhesive | Liner | Item     | Approx Wgt/<br>MMSI | GB | W KC      | MM      | ATL | 4 |
|---|----------|-------|----------|---------------------|----|-----------|---------|-----|---|
| THERMAL TRANSFER  |          |       |          |                     |    |           |         |     |   |
| MATTE WHITE BOPP  |          |       |          |                     |    |           |         |     |   |
| A 3.7 mil top coated matte white BC letterpress. Moisture, chemical and |          | , ,   |          |                     |    | aphy, scr | een, ar | nd  |   |
| 100WP   | 00720    | 40SC  | S8204960 | 227                 | C  |           |         |     |   |
| 100WP   | 00747    | 50SC  | S7604660 | 247                 | C  |           |         |     |   |
| 100WP   | 00747    | 40SC  | S7605960 | 229                 | 1  |           |         |     |   |
| 100WP   | 00751    | 40SC  | S7206060 | 226                 | C  |           |         |     |   |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



|   |                  |              |                    | Approx Wgt/              | MIN KC                          | ATL LA    |
|---|------------------|--------------|--------------------|--------------------------|---------------------------------|-----------|
| Facer   | Adhesive         | Liner        | Item               | MMSI                     | 5 2 2                           | 1         |
| THERMAL TRANSFER  |                  |              |                    |                          |                                 |           |
| VALUE THERMAL TRANSFER  |                  |              |                    |                          |                                 |           |
| A 42# (62 g/m²) top-coated, thermal traconventional thermal transfer facers.    |                  | Ü            |                    | 0                        | ' '                             | e to      |
| VALUT   | 00278            | 40SC         | S8175760           | 200                      |                                 |           |
| VALUT   | 00531            | 40SC         | S9109660           | 212                      |                                 |           |
| VALUT   | 00720            | 40SC         | S7851360           | 210                      |                                 | 1         |
| VALUT   | 00720            | 12NB         | S9178360           | 174                      |                                 |           |
| VALUT   | 00751            | 40SC         | S7841560           | 210                      | C                               |           |
| VALUT   | 00751            | 40SC         | S8278660           | 210                      | C                               |           |
| VALUT   | 00757            | 40SC         | S9013660           | 213                      |                                 |           |
| VALUT   | 0758M            | 40SC         | S7839660           | 210                      |                                 | 1         |
| VALUT   | 0758M<br>0758M   | 40SC<br>40SC | S8138960           | 338                      |                                 |           |
| VALUT   | 0758M            | 17GL         | S8777860           | 183                      | C                               |           |
| DIRECT THERMAL  |                  |              |                    |                          |                                 |           |
| TOP COATED DIRECT THERMAL PA  | APFR             |              |                    |                          |                                 |           |
| A 38# (56.2 g/m²) high sensitivity, top mobile printing applications. FSC®-cell | coated direct th | nermal paper | r. This thinner ca | aliper facer allows more | labels per roll. Ideal for hand | l-applied |
| 015DT   | 00720            | 40SC         | S9192179           | 249                      | C                               |           |
| NON-TOP COATED DIRECT THERM   | AL PAPER         |              |                    |                          |                                 |           |
| A 47# (69.9 g/m²) medium sensitivity r not exposed to solvents, water, oils, fa |                  |              |                    |                          | els or applications where the   | label is  |
| 024NT   | 00720            | 40SC         | S9195479           | 220                      |                                 |           |

| Locations: | GB - Green Bay, WI<br>WIN - Winchester, VA | KC - Kansas City, MO<br>MIN - Minneapolis, MN | ATL - Atlanta, GA<br>LA - Los Angeles, CA | I - Inventory C - Custom TIP Item |
|------------|--|---|---|-----------------------------------|
|            |  |   |   |                                   |



| Facer  | Adhesive                             | Liner         | Item                           | Approx Wgt/<br>MMSI   | GB NW              | Ş<br>Ş                              | ATL         | 4    |
|--|--------------------------------------|---------------|--------------------------------|-----------------------|--------------------|-------------------------------------|-------------|------|
| DIRECT THERMAL   |                                      |               |                                |                       |                    |                                     |             |      |
| PHENOL-FREE DIRECT THERMAL   | PRESCRIPTIO                          | N VIAL LA     | BEL                            |                       |                    |                                     |             |      |
| This 48# (71 g/m²), phenol-free, top-humidity. Vital drug information rema                                   |                                      |               |                                |                       |                    | lds up in h                         | eat and     |      |
| 021RX  | 00508                                | 40SC          | S9174760                       | 229                   | C                  |                                     |             | 1    |
| 021RX  | 00751                                | 40SC          | S9174660                       | 229                   |                    |                                     |             |      |
| RED FLUORESCENT DIRECT THEF<br>A 54# (80 g/m²) bright red direct ther<br>color coded warehouse tracking. FS0 | mal coated pape                      | _             | ack. Intended for              | attention-grabbing p  | promotional point  | -of-purcha                          | se labels   | , or |
| 022FT  | 00720                                | 40SC          | S9127860                       | 234                   | 1                  |                                     |             |      |
| 022PD  | 0758M                                | 40SC          | S8897252                       | 230                   | С                  |                                     |             |      |
| PREMIUM TOP COATED TD  |                                      |               |                                |                       |                    |                                     |             |      |
| A 53# (78 g/m²) top coated direct the  | rmal coated pape                     | er for more o | demanding applic               | cations and higher in | naging speeds. F   | SC®-certif                          | ied pape    | r.   |
| 022TD  | 00272                                | 40SC          | S7603560                       | 230                   | 1                  |                                     |             |      |
| 022TD  | 00275                                | 41WK          | S9156560                       | 226                   | 1                  |                                     |             |      |
| 022TD  | 00720                                | 40SC          | S6290060                       | 234                   | 1                  |                                     |             |      |
| 022TD  | 00747                                | 40SC          | S7552960                       | 236                   | C                  |                                     |             |      |
| 022TD  | 0758M<br>0758M                       | 40SC<br>40SC  | S7657960                       | 361                   | C                  |                                     |             |      |
| ECONOMY TOP COATED DIRECT  A 53# (78 g/m²) top coated direct the for weigh scale labels, pharmacy, sh        | rmal paper. Resi                     | stant to mois |                                |                       | er resistance at r | oom tempe                           | erature. Id | deal |
| 024DT  | 00720                                | 40SC          | S8814460                       | 232                   |                    | 1                                   |             | 1    |
| •  | Kansas City, MO<br>- Minneapolis, MN |               | Atlanta, GA<br>.os Angeles, CA |                       |                    | - Inventory<br>- Custom<br>TIP Item |             |      |



| Facer          | Adhesive | Liner | Item | Approx Wgt/<br>MMSI | GB | NIM | ¥ Q | Z | ATL | 4 |  |
|----------------|----------|-------|------|---------------------|----|-----|-----|---|-----|---|--|
| DIRECT THERMAL |          |       |      |                     |    |     |     |   |     |   |  |

### **ECONOMY TOP COATED DIRECT THERMAL PAPER**

A 47# (70 g/m²) top coated direct thermal paper. Resistant to moisture, oil and heat. Also has plasticizer resistance at room temperature. Ideal for weigh scale labels, pharmacy, shipping and warehousing applications. FSC®-certified paper.

| 025DT | 00531 | 40SC | S8975760 | 222 |   |
|-------|-------|------|----------|-----|---|
| 025DT | 00633 | 40SC | S9176860 | 218 | C |
| 025DT | 00720 | 40SC | S8975560 | 219 |   |
| 025DT | 00720 | 40SC | S9087260 | 222 | C |
| 025DT | 00751 | 40SC | S8976560 | 226 |   |

## **NON-TOP COATED DIRECT THERMAL PAPER**

A 51# (75 g/m²) medium sensitivity non-top coated direct thermal paper designed for short duration labels or applications where the label is not exposed to solvents, water, oils, fats or other similar materials. FSC®-certified paper.

| 025NT | 00531 | 40SC | S8274460 | 223 |    |
|-------|-------|------|----------|-----|----|
| 025NT | 00720 | 40SC | S8153252 | 224 |    |
| 025NT | 00720 | 40SC | S8153260 | 224 | C  |
| 025NT | 0758M | 40SC | S8155352 | 226 |    |
| 025NT | 0758M | 40SC | S8155360 | 226 | CI |

### 3.0 MIL SYNTHETIC MEDIUM SENSITIVITY FILM

A 3.0 mil BOPP direct thermal film. Medium degree of sensitivity. Top coated for durability. Use when moisture and environmental resistance are important. Dark image for excellent ability to be read and scanned.

| 070MK | 00720 | 40SC | S4335060 | 208 |   |
|-------|-------|------|----------|-----|---|
| 070MK | 00747 | 40SC | S7600260 | 210 | C |
| 070MK | 00853 | 40SC | S5065060 | 204 | C |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

C - Custom
TIP Item



| Facer   | Adhesive                  | Liner        | ltem                 | Approx Wgt/<br>MMSI | GB                | KC      | MIN     | ATL    | 4       |
|---|---------------------------|--------------|----------------------|---------------------|-------------------|---------|---------|--------|---------|
| DIRECT THERMAL  |                           |              |                      |                     |                   |         |         |        |         |
| 3.3 MIL SYNTHETIC MEDIUM  | M SENSITIVITY FILM        |              |                      |                     |                   |         |         |        |         |
| A 3.3 mil BOPP direct therma are important. Good stiffness                              | '                         | ,            | 0                    | *                   |                   | ronmen  | tal res | istanc | е       |
| 084MB   | 00278                     | 40SC         | S8872160             | 211                 | C                 |         |         |        |         |
| 084MB   | 00751                     | 40SC         | S8862460             | 221                 | C                 |         |         |        |         |
| 095RK<br>095RK  | 00720<br>00747            | 40SC<br>40SC | S4101060<br>S7549860 | 237<br>240          | 1                 |         |         | 1      |         |
| 095RK   | 00747                     | 40SC         | S7549860             | 240                 |                   |         |         |        |         |
| SYNTHETIC MEDIUM SENSI 4.1 mil white BOPP film with for industrial labeling, ski lift t | direct thermal coating. P |              | 0 1                  |                     | Water and enviror | nmental | resist  | ant. U | <br>Ise |
| 096RK   | 00504                     | 40SC         | S9194960             | 231                 | С                 |         |         |        |         |
| 096RK   | 00720                     | 40SC         | S9177360             | 225                 |                   |         |         |        |         |
| 096RK   | 00747                     | 40SC         | S9194760             | 229                 | C                 |         |         |        |         |

# TOP COATED VALUE DIRECT THERMAL

A 48# (71 g/m²) top coated paper. Resists moisture, heat, humidity, fading, scuffing, chemicals, and plasticizers. Use for weigh scale applications, cold storage, freeze/thaw food products, and industrial environments. FSC®-certified paper.

| 24VTB | 00720 | 40SC | S9030960 | 221 |  |
|-------|-------|------|----------|-----|--|
| 24VTB | 00853 | 40SC | S9169560 | 223 |  |
| 24VTB | 00853 | 40SC | S9170460 | 220 |  |





Facer Adhesive Liner Item Approx Wgt/
MMSI

# **INK JET / LASER**

# Recommendations for Storage and Handling of Layflat Label Material

- \* Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- \* The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- \* Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- \* Rotate your stock. Use oldest inventory first.
- \* Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- \* INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

### SUPER BRIGHT LASER JET

51# (75 g/m²) Exceptionally bright, uncoated, multi-purpose sheet for both laser and ink jet printing. FSC®-certified paper.

| 050LJ | 00720 | 0PBLF | S8214960 | 250 |   |
|-------|-------|-------|----------|-----|---|
| 050LJ | 00751 | 0PBLF | S8218060 | 255 |   |
| 050LJ | 0758M | 32KLF | S8048560 | 239 | C |
| 050LJ | 0758M | 0PBLF | S8165060 | 253 |   |
| 050LJ | 0758M | 41LF  | S8238360 | 233 |   |
| 050LJ | 0758M | 53CRT | S9184660 | 261 |   |

### **BLUE FLUORESCENT**

57# (84 g/m²) blue matte fluorescent coated paper. Designed for laser, price marking, promotional and general roll label applications. Unique color makes labels stand out. Offers another option when using color coded labels. FSC®-certified paper.

| 054BZ | 00720 | 40SC | S8122860 | 239 | 1 |  |
|-------|-------|------|----------|-----|---|--|
|-------|-------|------|----------|-----|---|--|

### **GREEN FLUORESCENT**

57# (84 g/m²) green matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

| 054GZ | 0758M | 0PBLF | S8189860 | 262 |  |
|-------|-------|-------|----------|-----|--|
|       |       |       |          |     |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

C - Custom
TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.



Facer Adhesive Liner Item Approx Wgt/
MMSI

## **INK JET / LASER**

# Recommendations for Storage and Handling of Layflat Label Material

- \* Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- \* The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- \* Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- \* Rotate your stock. Use oldest inventory first.
- \* Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- \* INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

### **ORANGE FLUORESCENT**

57# (84 g/m²) orange matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

**0540Z** 0758M 0PBLF **\$8190060** 262

### PINK FLUORESCENT

57# (84 g/m²) pink matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054PZ 0758M 0PBLF \$8190160 262

#### **RED FLUORESCENT**

57# (84 g/m²) red matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

054RZ 0758M 0PBLF \$8190260 262

### YELLOW CHARTREUSE FLUORESCENT

57# (84 g/m²) yellow chartreuse matte fluorescent coated paper. Designed for laser, price marking and general roll label applications. FSC®-certified paper.

**054YZ** 0758M 0PBLF **\$8189960** 262

### PREMIUM COATED MATTE INK JET

A 61# (90 g/m²) matte-coated ink jet sheet with good opacity. It is waterfast and provides an extremely high level of smear resistance. This facer offers high resolution imaging and is compatible with a broad array of inkjet printers.

**06MIJ** 00751 40SC **\$8087060** 255 **C** 

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.



Facer Adhesive Liner Item MMSI

## **INK JET / LASER**

## Recommendations for Storage and Handling of Layflat Label Material

- \* Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- \* The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- \* Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- \* Rotate your stock. Use oldest inventory first.
- \* Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- \* INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

#### **60# MATTE-COATED INK JET**

A 60# (88 g/m²) matte-coated, acid-free, inkjet sheet with an exceptionally bright, blue-white shade. It provides high resolution imaging, and excellent smear and water resistance. It is compatible with a broad array of inkjet printers. FSC®-certified.

| 07INK | 00720 | 40SC | S9206460 | 248 |   |
|-------|-------|------|----------|-----|---|
| 07INK | 00751 | 40SC | S9205860 | 252 | C |
| 07INK |       |      | S9206260 | 125 | C |

## **59# GLOSS INKJET PAPER**

A 59# (87 g/m²) high gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. Not recommended for flexo printing. FSC®-certified.

| 1GINK | 00720 | 0PBLF | S8264660 | 270 | C |
|-------|-------|-------|----------|-----|---|
| 1GINK | 00720 | 40SC  | S8721460 | 249 |   |
| 1GINK | 00751 | 40SC  | S8714360 | 245 | C |
| 1GINK | 0758M | 41LF  | S8718860 | 246 | C |

## 65# SEMI-GLOSS IINKJET PAPER

A 65# (97 g/m²) semi gloss inkjet paper. Offers high resolution imaging and is perfect for photorealistic prints. Is universally compatible with dye inks and printable with a range of pigment inks. FSC®-certified.

| SG2NK | 0720M | 40SC | S9189560 | 329 | 1 |  |
|-------|-------|------|----------|-----|---|--|
|       |       |      |          |     |   |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

C - Custom
TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.



Facer Adhesive Liner Item Approx Wgt/
MMSI

## **INK JET / LASER**

# Recommendations for Storage and Handling of Layflat Label Material

- \* Good layflat performance can be expected when label stock is converted in an environment where the temperature range is between 60 and 80 degrees Fahrenheit (16 and 27 degrees Celsius) and the relative humidity is between 40% and 60%.
- \* The material should be allowed to acclimate to your facility's environmental conditions for three days before it is converted.
- \* Keep rolls off of concrete floors and away from any other sources of moisture contamination.
- \* Rotate your stock. Use oldest inventory first.
- \* Avoid long-term storage. For best results, material should be utilized by the end-user within six months of manufacture.
- \* INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.

### 3.4 MIL MATTE WHITE INK JET BOPP

A 3.4 mil white matte BOPP that is a multi-purpose film for both water-based and pigment ink jet printing. Quick drying on press. The smooth surface allows graphics to really stand out on both black and white, and color printers. Good moisture resistance.

34WIJ 00720 40SC **S9177960** 201

### 47# FSC®-CERTIFIED SUPER BRIGHT LASER JET

47# (70 g/m²) Exceptionally bright, uncoated, multi-purpose sheet for laser and ink jet printing. Lighter weight for shipping savings. Thinner caliper for space savings and reduced packaging. Offers the option of more labels on a roll. FSC®-certified.

| F47LJ | 00757 | 41LF  | S9077660 | 226 | C |  |
|-------|-------|-------|----------|-----|---|--|
| F47LJ | 0758M | 41LF  | S9171560 | 226 |   |  |
| F47LJ | 0758M | 0PBLF | S9172060 | 248 | 1 |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

C - Custom
TIP Item

INK JET and LASER products are recommended on 6 inch O.D. cores to minimize core related curl. Layflat is affected by small cores. Customer accepts responsibility of curl if taken on 3 inch cores.



| Facer                   | Adhesive      | Liner | Item | Approx Wgt/<br>MMSI | GB | N N | Z | ATL | 4 |
|-------------------------|---------------|-------|------|---------------------|----|-----|---|-----|---|
| <b>FILMS: POLYPROPY</b> | LENES (CLEAR) |       |      |                     |    |     |   |     |   |

### TILMO. I OLTI KOI TELMES (CLL)

## 1.85 MIL CLEAR TOP COATED BOPP

1.85 mil clear top-coated BOPP is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Ultra clear for a no-label look. Perfect for health and beauty aid, household care, and beverage labeling.

| 018CT | 00102 | 39NK | S9064660 | 181 |   |
|-------|-------|------|----------|-----|---|
| 018CT | 00102 | 40SC | S9091760 | 182 | C |
| 018CT | 00102 | 12NB | S9092460 | 148 | C |
| 018CT | 00720 | 40SC | S9064560 | 181 |   |
| 018CT | 00751 | 40SC | S9092760 | 185 |   |
| 018CT | 00960 | 12NB | S9202560 | 143 |   |
| 018CT | 00960 | 40SC | S9213560 | 181 |   |
| 018CT | 00960 | 39NK | S9221960 | 180 |   |
| 018CT | 0720M | 40SC | S9090660 | 181 |   |
| 018CT | 0776S | 40SC | S9095260 | 178 |   |
| 018CT | 0776S | 12NB | S9106460 | 144 | C |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



| Facer   | Adhesive  | Liner | Item     | Approx Wgt/<br>MMSI | GB | X X       | MIN       | 4   |
|---|-----------|-------|----------|---------------------|----|-----------|-----------|-----|
| FILMS: POLYPROPYLENE  | S (CLEAR) |       |          |                     |    |           |           |     |
| 2.0 MIL CLEAR TOP COATED BOR  | PP        |       |          |                     |    |           |           |     |
| 2.0 mil clear top-coated BOPP offer no-label look. Perfect for health and | '         |       |          | ,                   |    | ng. Ultra | clear for | í a |
| 020CL   | 00102     | 40SC  | S8017560 | 188                 | 1  |           |           |     |
| 020CL   | 00102     | 12NB  | S8766160 | 154                 | C  |           |           |     |
| 020CL   | 00102     | 39NK  | S8777060 | 187                 | C  |           |           |     |
| 020CL   | 00103     | 40SC  | S8763760 | 187                 | C  |           |           |     |
| 020CL   | 00103     | 15PT  | S8779560 | 165                 | C  |           |           |     |
| 020CL   | 00720     | 40SC  | S8766360 | 187                 |    |           |           |     |
| 020CL   | 00751     | 40SC  | S8782260 | 191                 | C  |           | 1         |     |
| 020CL   | 00751     | 12NB  | S8838960 | 154                 | C  |           |           |     |
| 020CL   | 00960     | 40SC  | S9221160 | 187                 |    | - 1       | 1         | 1   |
| 020CL   | 00960     | 12NB  | S9222060 | 150                 |    |           |           |     |
| 020CL   | 0720M     | 40SC  | S8997360 | 187                 | C  |           |           | 1   |

### 2.2 MIL FLEXICLEAR™ TC CONFORMABLE BOPP

A 2.2 mil top coated clear BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiClear™ is a Trademark of Green Bay Packaging Inc.

| 022FC | 00102 | 40SC | S8104460 | 194 | C |
|-------|-------|------|----------|-----|---|
| 022FC | 00751 | 12NB | S8836560 | 160 | C |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item



| Facer   | Adhesive    | Liner | ltem     | Approx Wgt/<br>MMSI | GB            | NIW :    | S Z     | ATL    | ۲ |
|---|-------------|-------|----------|---------------------|---------------|----------|---------|--------|---|
| FILMS: POLYPROPYLEN   | IES (CLEAR) |       |          |                     |               |          |         |        |   |
| 3.6 MIL CLEAR TC BOPP  A 3.6 mil clear BOPP film. UV re graphics, or other applications w |             | 0     | ,        | UV flexo and waterb | ased inks. Ca | ın be us | sed for | window |   |
| 036CG   | 00347       | 50SC  | S6883060 | 269                 | 1             |          |         |        |   |
| 036CG   | 00347       | 74LF  | S9127360 | 316                 | 1             |          |         |        |   |
| FILMS: POLYPROPYLEN   | IES (WHITE) |       |          |                     |               |          |         |        |   |

# 2.2 MIL FLEXIWHITE™ TC CONFORMABLE BOPP

A 2.2 mil top coated white BOPP offering full wall-to-wall squeeze conformability. Glossy look with a superior print receptive top coating for excellent ink adhesion and print quality. FlexiWhite<sup>TM</sup> is a Trademark of Green Bay Packaging Inc.

| 022FW | 00102 | 12NB | S8165860 | 164 | C |
|-------|-------|------|----------|-----|---|
| 022FW | 00751 | 40SC | S8103360 | 198 |   |
| 022FW | 00751 | 12NB | S8840360 | 164 | C |

# 2.3 MIL TOP COATED WHITE BOPP

A 2.3 mil white top coated BOPP, backside coated to aid in adhesive anchorage. Excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.

| 023WB | 00633 | 12NB | S8167160 | 169 | C |  |
|-------|-------|------|----------|-----|---|--|
|       |       |      |          |     |   |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
C - Custom
TIP Item



| Facer                    | Adhesive    | Liner | Item | Approx Wgt/<br>MMSI | GB | NIN N | 5 | Z | ATL | 4 |  |
|--------------------------|-------------|-------|------|---------------------|----|-------|---|---|-----|---|--|
| FILMS: POLYPROPYLE       | NES (WHITE) |       |      |                     |    |       |   |   |     |   |  |
| 2.2 MIL WHITE TOP COATED | PODD.       |       |      |                     |    |       |   |   |     |   |  |

# 2.3 MIL WHITE TOP COATED BOPP

A 2.3 mil white top coated BOPP with excellent compatibility using UV curing inks or water based flexo ink systems. High stiffness for conversion and automatic dispensing. Great choice for prime labeling.

| 023WP | 00102 | 40SC | S7731160 | 204 |   |
|-------|-------|------|----------|-----|---|
| 023WP | 00103 | 40SC | S7000060 | 202 | C |
| 023WP | 00103 | 12NB | S7895760 | 169 | C |
| 023WP | 00720 | 40SC | S7630960 | 202 |   |
| 023WP | 00751 | 40SC | S7722460 | 207 |   |
| 023WP | 00751 | 12NB | S8823860 | 170 | C |
| 023WP | 00950 | 40SC | S9221260 | 202 |   |

### 2.3 MIL WHITE TOP-COATED BOPP

2.3 mil solid white top-coated BOPP. Compatible with UV and water-based flexo, and UV inkjet printing; also hot stamping. Exceptional opacity. Backside treated for adhesive anchorage. Great stiffness for auto application. Ideal for prime labeling.

| 023WT | 00102 | 40SC | S9126860 | 204 | CIII |
|-------|-------|------|----------|-----|------|
| 023WT | 00720 | 40SC | S9065960 | 202 | C    |
| 023WT | 00950 | 40SC | S9221560 | 202 | C    |
| 023WT | 0720M | 40SC | S9133560 | 202 |      |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

I - Inventory

C - Custom
TIP Item



| Facer                 | Adhesive | Liner | Item | Approx Wgt/<br>MMSI | GB | N<br>N | 8 | Z | ATL | LA |  |
|-----------------------|----------|-------|------|---------------------|----|--------|---|---|-----|----|--|
| FILMS: POLYPROPYLENES | (WHITE)  |       |      |                     |    |        |   |   |     |    |  |

## 2.4 MIL TOP COATED WHITE LABEL-LYTE™

A 2.4 mil glossy white BOPP top coated for ink adhesion. Has a distinctive pearlescent sheen. Excellent compatibility with UV curing inks and water based flexo ink systems. Label-Lyte is a Trademark of Jindal Films America.

| 024TL | 00102 | 92NB | S8276460 | 138 | С |     |   |
|-------|-------|------|----------|-----|---|-----|---|
| 024TL | 00102 | 12NB | S8724760 | 153 | С |     |   |
| 024TL | 00102 | 40SC | S8775660 | 185 | C | 1 1 | 1 |
| 024TL | 00720 | 40SC | S8773560 | 188 |   |     | 1 |
| 024TL | 00747 | 40SC | S8779660 | 190 | С | 1   |   |
| 024TL | 00751 | 40SC | S8787060 | 190 |   |     |   |
| 024TL | 00751 | 12NB | S8832660 | 153 |   |     |   |
| 024TL | 00950 | 92NB | S9215060 | 135 |   |     |   |
| 024TL | 00950 | 40SC | S9221060 | 185 | 1 | 1 1 | 1 |
| 024TL | 00950 | 12NB | S9222260 | 148 |   |     |   |
| 024TL | 0720M | 40SC | S9042760 | 190 | C |     |   |
| 024TL | 0776S | 40SC | S9070160 | 182 | С |     |   |
| 024TL | 0776S | 12NB | S9070260 | 148 | С |     |   |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item



Approx Wgt/

158

190

153

70

| Facer                 | Adhesive  | Liner | Item     | MMSI |  |
|-----------------------|---|-------|----------|------|--|
| FILMS: POLYPROPY      | YLENES (WHITE)  |       |          |      |  |
| 2.6 MIL TOP COATED WH | IITE LABEL-LYTE™  |       |          |      |  |
| 0 ,                   | PP top coated for ink adhesion cems. Label-Lyte is a Tradem |       |          |      | lent compatibility with UV curing inks and |
| 026TL                 | 00102   | 40SC  | S7802360 | 190  | C  |
| 026TL                 | 00102   | 12NB  | S8010760 | 158  | C III III III III                          |
| 026TL                 | 00103   | 40SC  | S6174060 | 190  |  |
| 026TL                 | 00633   | 40SC  | S8123660 | 189  | C  |
| 026TL                 | 00720   | 40SC  | S6173060 | 190  |  |
| 026TL                 | 00747   | 40SC  | S7600560 | 195  |  |
| 026TL                 | 00751   | 40SC  | S5384060 | 191  |  |
|                       |   |       |          |      |  |

S8825660

S9215460

S9222160

S6397560

### 3.6 MIL WHITE TC BOPP

026TL

026TL

026TL

026TL

A 3.6 mil white BOPP film. UV resistance and top coating suitable for UV screen, UV flexo and waterbased inks. Can be used for window graphics, or other applications where a more substantial film is needed.

00751

00950

00950

**12NB** 

40SC

**12NB** 

| 036WG | 00347 | 50SC | S6888060 | 278 |  |
|-------|-------|------|----------|-----|--|
| 036WG | 00347 | 74LF | S9157660 | 325 |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item



| Facer                 | Adhesive | Liner | Item | Approx Wgt/<br>MMSI | GB | N<br>N | 8 | Z | ATL | Z |  |
|-----------------------|----------|-------|------|---------------------|----|--------|---|---|-----|---|--|
| FILMS: POLYPROPYLENES | (WHITE)  |       |      |                     |    |        |   |   |     |   |  |

# 2.4 MIL WHITE TOP-COATED BOPP

2.4 mil white top-coated BOPP. It is compatible with water-based and UV flexo, and UV inkjet presses. Thinner for resource and shipping savings. Glossy look. Perfect for health and beauty aid, household care, and beverage labeling.

| 24WCT | 00102 | 40SC | S9110760 | 184 | C   |   | 1 | 1 |
|-------|-------|------|----------|-----|-----|---|---|---|
| 24WCT | 00102 | 12NB | S9113660 | 150 | 1   |   |   | 1 |
| 24WCT | 00103 | 40SC | S9131460 | 183 | C   |   |   |   |
| 24WCT | 00720 | 40SC | S9134360 | 182 |     |   |   | 1 |
| 24WCT | 00751 | 12NB | S9121060 | 150 | C   |   |   |   |
| 24WCT | 00751 | 40SC | S9123660 | 184 |     |   |   |   |
| 24WCT | 00950 | 40SC | S9215260 | 183 | 1 1 | 1 | 1 | 1 |
| 24WCT | 00950 | 12NB | S9221460 | 145 |     |   |   | 1 |
| 24WCT | 0720M | 40SC | S9119160 | 184 |     |   |   |   |
| 24WCT | 0776S | 40SC | S9120460 | 179 | I   |   |   | 1 |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item



| er   | Adhesive  | Liner                                   | ltem            | Approx Wgt/<br>MMSI | GB           | NIN N  | \$      | Z      | ATL    | _  |
|--|---|---|-----------------|---------------------|--------------|--------|---------|--------|--------|----|
| LMS: POLYPROP                                | (VLENES (WHITE)   |   |                 |                     |              |        |         |        |        |    |
| MIL WHITE TOP-COAT                           | TED BOPP  |   |                 |                     |              |        |         |        |        |    |
|  | PP. It is top coated for deperfect look for use on health a                   |   |                 |                     |              | r-base | ed flex | o ink  | syster | ms |
| 26WCT  | 00102   | 40SC                                    | S9021460        | 187                 | C            | 1      |         |        |        |    |
| 26WCT  | 00102   | 12NB                                    | S9121260        | 154                 | C            |        |         |        |        |    |
| 26WCT  | 00103   | 40SC                                    | S9123160        | 187                 | C            |        |         |        |        |    |
| 26WCT  | 00720   | 40SC                                    | S9121160        | 187                 | 1            |        |         |        |        |    |
| 26WCT  | 00747   | 40SC                                    | S9123260        | 191                 | C            |        |         |        |        |    |
| 26WCT  | 00751   | 40SC                                    | S9021560        | 188                 | 1            |        |         |        |        |    |
| 26WCT  | 00950   | 40SC                                    | S9215360        | 187                 | 1            | 1      |         |        |        |    |
| 26WCT  | 00950   | 12NB                                    | S9222360        | 150                 |              |        |         |        |        |    |
| 26WCT  |   |   | S9120660        | 67                  | C            |        |         |        |        |    |
|  | KJET BOPP PP that is a multi-purpose file really stand out on both bla        |   |                 |                     | _            | ng on  | press   | . The  | smoo   | th |
| LMS: POLYPROP                                | LENES (VARIABL  | E IMAGII                                | NG)             |                     |              |        |         |        |        |    |
| MIL THERMAL TRANS 2.6 mil White Label-Lyte E | SFER WHITE LABEL-LY SOPP with a thermal transfe required. Label-Lyte is a tra | <b>ΓΕ<sup>τΜ</sup></b><br>r top coat. D | esigned for var |                     | ions where m | noistu | re resi | stance | e, or  |    |
| 026TT  | 00747   | 40SC                                    | S8773660        | 192                 |              |        |         |        |        |    |
|  |   |   |                 |                     |              |        |         |        |        |    |

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

MIN - Minneapolis, MN

LA - Los Angeles, CA

WIN - Winchester, VA

C - Custom TIP Item



| acer   | Adhesive   | Liner   | Item   | Approx Wgt/<br>MMSI   | GB                               | N<br>N  | Š    | N      | ATL     | 4  |
|--|--|---|--|---|----------------------------------|---------|------|--------|---------|----|
| FILMS: POLYPROF  | YLENES (VARIABL  | E IMAGI   | NG)  |   |                                  |         |      |        |         |    |
| HERMAL TRANSFER V  | VHITE LABEL-LYTE™  |   |  |   |                                  |         |      |        |         |    |
| White Label-Lyte BOPP  | with a thermal transfer top co   | at. Label-Ly  | rte is a Tradema   | rk of Jindal Films Ame  | erica.                           |         |      |        |         |    |
| 030TT  | 00747  | 40SC  | S5213060   | 199   | C                                |         |      |        |         |    |
| A 3.0 mil BOPP direct th   | DIUM SENSITIVITY FILM nermal film. Medium degree of ge for excellent ability to be re  |   |  | durability. Use when n  | noisture and                     | enviro  | nmen | tal re | sistan  | ce |
| 070MK  | 00720  | 40SC  | S4335060   | 208   | 1                                |         | 1    |        |         |    |
| 070MK  | 00747  | 40SC  | S7600260   | 210   | C                                |         |      |        |         |    |
| 070MK  | 00853  | 40SC  | S5065060   | 204   | C                                |         |      |        |         |    |
| print<br>075WP   | 00747  | 40SC  | be used with the   | 214   | С                                | , iotto |      |        |         |    |
| .3 MIL SYNTHETIC MEI A 3.3 mil BOPP direct th  |  | 40SC  | S8149152   | 214<br>ensitivity. Use when n   | C noisture and                   |         |      |        | sistan  |    |
| .3 MIL SYNTHETIC MEI A 3.3 mil BOPP direct th  | 00747  DIUM SENSITIVITY FILM  nermal film. Top coated for dui  | 40SC  | S8149152   | 214<br>ensitivity. Use when n   | C noisture and                   |         |      |        | sistan  |    |
| .3 MIL SYNTHETIC MEI A 3.3 mil BOPP direct th are important. Good stiff  | 00747  DIUM SENSITIVITY FILM nermal film. Top coated for dur fness for ease of dispensing. I   | 40SC<br>rability. Med<br>Dark image                   | S8149152 ium degree of sofor excellent abil  | 214<br>ensitivity. Use when n<br>lity to be read and sca                              | c noisture and anned.            |         |      |        | sistan  |    |
| 075WP  .3 MIL SYNTHETIC MEI  A 3.3 mil BOPP direct th are important. Good stiff  084MB  084MB  | 00747  DIUM SENSITIVITY FILM nermal film. Top coated for dur fness for ease of dispensing. I  00278  00751   | 40SC rability. Med Dark image 40SC 40SC               | S8149152 ium degree of sefor excellent abil S8872160 S8862460                      | ensitivity. Use when n<br>lity to be read and sca<br>211<br>221                       | noisture and anned.              |         |      |        | sistan  |    |
| 075WP  .3 MIL SYNTHETIC MEI  A 3.3 mil BOPP direct th are important. Good stiff  084MB  084MB  | 00747  DIUM SENSITIVITY FILM nermal film. Top coated for dur fness for ease of dispensing. I  00278  00751   | 40SC rability. Med Dark image 40SC 40SC               | S8149152 ium degree of sefor excellent abil S8872160 S8862460                      | ensitivity. Use when n<br>lity to be read and sca<br>211<br>221                       | noisture and anned.              |         |      |        | sistan  |    |
| 075WP  .3 MIL SYNTHETIC MEI  A 3.3 mil BOPP direct th are important. Good stiff  084MB  084MB  SYNTHETIC MEDIUM SE  4.1 mil white BOPP film      | 00747  DIUM SENSITIVITY FILM nermal film. Top coated for duriness for ease of dispensing. I 00278 00751  ENSITIVITY FILM with direct thermal coating. To | 40SC rability. Med Dark image 40SC 40SC               | S8149152 ium degree of sofor excellent abil S8872160 S8862460 or durability. Med   | ensitivity. Use when notity to be read and social 211 221                             | noisture and anned.              |         |      |        | ssistan |    |
| 075WP  .3 MIL SYNTHETIC MEI A 3.3 mil BOPP direct th are important. Good stiff  084MB  084MB  SYNTHETIC MEDIUM SE 4.1 mil white BOPP film  095RK | DIUM SENSITIVITY FILM nermal film. Top coated for duriness for ease of dispensing. I 00278 00751  ENSITIVITY FILM with direct thermal coating. To        | 40SC rability. Med Dark image 40SC 40SC op coated for | S8149152  ium degree of sofor excellent abil S8872160 S8862460  or durability. Med | 214 ensitivity. Use when n lity to be read and sca 211 221 lium degree of sensiti 237 | noisture and anned.  C  C  vity. |         |      |        | sistan  |    |



|   | BIG ENOUGH         | TO SERVE     | OU, SMALL E      | NOUGH TO KNOW          | YOU                                     |
|---|--------------------|--------------|------------------|------------------------|---|
| Facer   | Adhesive           | Liner        | Item             | Approx Wgt/<br>MMSI    | GB WIN KC ATL ATL                       |
| FILMS: POLYPROPYLENE  | S (VARIABL         | E IMAGII     | NG)              |                        |   |
| TOP COATED KIMDURA® FPG 9   | 5                  |              |                  |                        |   |
| A 4.2 mil (92 g/m²) Kimdura® BOP<br>Trademark of Neenah Paper, Inc. 0         |                    |              |                  | matrix, ion deposition | n and digital printing. Registered      |
| Trademark of Neenan Paper, Inc. (   | S 2007 NPI Ali Rig | nis Reserved | J.               |                        |   |
| 095TK   | 00506              | 40SC         | S3252060         | 256                    |   |
| 095TK   | 00506              | 50SC         | S3256060         | 272                    | C                                       |
| 095TK   | 00538              | 50SC         | S3286060         | 272                    |   |
| 095TK   | 00751              | 50SC         | S5391060         | 273                    |   |
| SYNTHETIC MEDIUM SENSITIVIT   | Y FILM             |              |                  |                        |   |
| 4.1 mil white BOPP film with direct for industrial labeling, ski lift tickets |                    |              | _                |                        | Water and environmental resistant. Use  |
| 096RK   | 00504              | 40SC         | S9194960         | 231                    | C                                       |
| 096RK   | 00720              | 40SC         | S9177360         | 225                    |   |
| 096RK   | 00747              | 40SC         | S9194760         | 229                    | C                                       |
| MATTE WHITE BOPP  |                    |              |                  |                        |   |
| A 3.7 mil top coated matte white Be and other demanding applications.         |                    | For use with | n thermal transf | er and other print me  | thods. Consider for drum label, outdoor |
| 100WP   | 00720              | 40SC         | S8204960         | 227                    | C                                       |
| 100WP   | 00747              | 50SC         | S7604660         | 247                    | C                                       |
| 100WP   | 00747              | 40SC         | S7605960         | 229                    |   |
| 100WP   | 00751              | 40SC         | S7206060         | 226                    | C                                       |

| Locations: | GB - Green Bay, WI   | KC - Kansas City, MO  | ATL - Atlanta, GA    | I - Inventory |
|------------|----------------------|-----------------------|----------------------|---------------|
|            | WIN - Winchester, VA | MIN - Minneapolis, MN | LA - Los Angeles, CA | C - Custom    |
|            |                      |                       |                      | TIP Item      |

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.

|  |  | O SERVE       |                                |                              |                |                             |           |    |
|--|--|---------------|--------------------------------|------------------------------|----------------|-----------------------------|-----------|----|
| Facer  | Adhesive                                   | Liner         | Item                           | Approx Wgt/<br>MMSI          | GB WIN         | S S                         | ATL       | LA |
| FILMS: POLYPROPYLENE   | S (METALIZI                                | ED)           |                                |                              |                |                             |           |    |
| 1.85 MIL SILVER METALIZED BO   | PP   |               |                                |                              |                |                             |           |    |
| 1.85 mil clear BOPP metalized on a<br>Great stiffness for automatic applic |  |               |                                |                              |                | ko, and U\                  | / inkjet. |    |
| 018MT  | 00102                                      | 40SC          | S9129360                       | 182                          | C              |                             |           | 1  |
| 018MT  | 00102                                      | 12NB          | S9133760                       | 148                          | C              |                             |           |    |
| 018MT  | 00720                                      | 40SC          | S9036760                       | 181                          |                |                             |           |    |
| 018MT  | 00751                                      | 40SC          | S9137460                       | 182                          | C              |                             |           |    |
| 018MT  | 00960                                      | 12NB          | S9210460                       | 144                          |                |                             |           |    |
| 018MT  | 00960                                      | 40SC          | S9221660                       | 181                          |                |                             |           | 1  |
| <b>2.0 MIL SILVER METALIZED BOP</b> A 2.0 mil BOPP metalized on the b      |  | y silver appe | earance. Top co                | ated for printability with a | a wide range o | f ink syste                 | ms.       |    |
| 021MU  | 00102                                      | 40SC          | S8056060                       | 188                          | C              |                             |           | 1  |
| 021MU  | 00720                                      | 40SC          | S8031460                       | 186                          |                |                             |           |    |
| 021MU  | 00751                                      | 40SC          | S7345060                       | 191                          | C              |                             |           |    |
| 021MU  | 00960                                      | 40SC          | S9221860                       | 187                          | C              |                             |           | 1  |
| FILMS: POLYSTYRENES  |  |               |                                |                              |                |                             |           |    |
| 1.5 MIL CLEAR POLYSTYRENE  |  |               |                                |                              |                |                             |           |    |
| A 1.5 mil corona treated clear polys                                       | styrene. Perfect for                       | use as a ba   | se for peel-off of             | coupons and booklets.        |                |                             |           |    |
| 015PN  | 00720                                      | 40SC          | S8175860                       | 177                          | C              |                             | I         |    |
| 2.0 MIL CLEAR POLYSTYRENE  |  |               |                                |                              |                |                             |           |    |
| A 2.0 mil corona treated clear polys                                       | styrene. Stiffness                         | allows easy   | converting and                 | dispensing.                  |                |                             |           |    |
| 020PN  | 00103                                      | 50SC          | S6679060                       | 217                          | C              |                             |           |    |
|  | C - Kansas City, MO<br>N - Minneapolis, MN |               | Atlanta, GA<br>.os Angeles, CA |                              |                | Inventory - Custom TIP Item |           |    |



| Facer  | Adhesive  | Liner                           | Item                                  | Approx Wgt/<br>MMSI               | GB               | N N      | 5      | M   | ATL | LA |
|--|---|---------------------------------|---------------------------------------|-----------------------------------|------------------|----------|--------|-----|-----|----|
| FILMS: POLYSTYRI   |   | Lillei                          | item                                  | IWIWIOI                           |                  |          |        |     |     |    |
| 2.5 MIL CLEAR POLYSTY  | RENE  |                                 |                                       |                                   |                  |          |        |     |     |    |
| A 2.5 mil corona treated c   | lear polystyrene. Stiffness   | allows easy                     | converting and o                      | lispensing. Great for             | use as a ma      | iling ta | ab.    |     |     |    |
| 025PN  | 00515   | 50SC                            | S8131852                              | 235                               | C                |          |        |     |     |    |
| 3.5 MIL WHITE SQUEEZE  | OPTICITE®   |                                 |                                       |                                   |                  |          |        |     |     |    |
| A 3.5 mil white squeezable   | e OPTICITE® with a corona   | a treated prin                  | nt surface. Trade                     | mark of The Dow Ch                | emical Comp      | any      |        |     |     |    |
| 035WZ  | 00103   | 50SC                            | S7709052                              | 265                               | C                |          |        |     |     |    |
|  |   |                                 |                                       |                                   |                  |          |        |     |     |    |
| 2.5 MIL WHITE POLYSTYI   | RENE  |                                 |                                       |                                   |                  |          |        |     |     |    |
| A 2.5 mil matte white poly   | RENE styrene. Corona treated for see for coupons and booklets   |                                 | k adhesion. Stif                      | fness allows easy co              | nverting and     | dispei   | nsing. | Use | for |    |
| A 2.5 mil matte white poly   | styrene. Corona treated for   |                                 | k adhesion. Stif                      | fness allows easy cor             | nverting and     | dispe    | nsing. | Use | for |    |
| A 2.5 mil matte white poly primary labels, or as a bas   | styrene. Corona treated for se for coupons and booklets 00506   | S.                              |                                       |                                   | _                | dispe    | nsing. | Use | for |    |
| A 2.5 mil matte white poly primary labels, or as a bas 25PSW  FILMS: POLYESTE  | styrene. Corona treated for see for coupons and booklets 00506  | S.                              |                                       |                                   | _                | disper   | nsing. | Use | for |    |
| A 2.5 mil matte white poly primary labels, or as a bas 25PSW  FILMS: POLYESTER  2 MIL CLEAR TOP COATE  | styrene. Corona treated for see for coupons and booklets 00506  | 40SC                            | S8263960                              | 231                               | С                |          | nsing. | Use | for |    |
| A 2.5 mil matte white poly primary labels, or as a bas 25PSW  FILMS: POLYESTER  2 MIL CLEAR TOP COATE  | styrene. Corona treated for see for coupons and booklets 00506  RS  ED POLYESTER                              | 40SC                            | S8263960                              | 231                               | С                |          | nsing. | Use | for |    |
| A 2.5 mil matte white poly primary labels, or as a bas 25PSW  FILMS: POLYESTER  2 MIL CLEAR TOP COATE A very clear, top coated polygony                            | styrene. Corona treated for se for coupons and booklets 00506  RS  ED POLYESTER olyester film. Top coating al | 40SC lows for prin              | S8263960 ting with most st            | 231<br>andard flexo and UV        | C letterpress in |          | nsing. | Use | for |    |
| primary labels, or as a base 25PSW  FILMS: POLYESTER  2 MIL CLEAR TOP COATE A very clear, top coated p 020MY  2.0 MIL VALUE WHITE PO A matte, white polyester file | styrene. Corona treated for se for coupons and booklets 00506  RS  ED POLYESTER olyester film. Top coating al | dosc  40sc  lows for prin  50sc | S8263960  ting with most st  S7855152 | 231<br>andard flexo and UV<br>242 | C letterpress in | nks.     | =      |     | -   |    |

Locations: GB - Green Bay, WI WIN - Winchester, VA

KC - Kansas City, MO MIN - Minneapolis, MN ATL - Atlanta, GA LA - Los Angeles, CA I - Inventory
C - Custom
TIP Item



| Facer  | Adhesive               | Liner         | Item             | Approx Wgt/<br>MMSI     | GB                | NIM     | y Z      | ATL      | 4     |  |
|--|------------------------|---------------|------------------|-------------------------|-------------------|---------|----------|----------|-------|--|
| FILMS: OVERLAMINA  | TES                    |               |                  |                         |                   |         |          |          |       |  |
| 1.0 MIL CLEAR NTC POLYES A glossy, clear polyester ove                                       |                        | tv. Effective | in durable appl  | ications – resistant to | heat and cher     | micals. | High to  | ear stre | nath. |  |
| 1CLPT  | 00102                  | 12NB          | S9167560         | 130                     | С                 |         |          |          |       |  |
| 1CLPT  | 00751                  | 40SC          | S8131360         | 168                     | C                 |         |          |          |       |  |
| FILMS: CLEAR SPEC  | IALTY                  |               |                  |                         |                   |         |          |          |       |  |
| 2 MIL CLEAR ACETATE  A 2.0 mil clear acetate film w applications. Meets the ASTN             | 0 , 1                  | -             |                  | is relatively low tear  | _                 | is goo  | d for ta | mperpr   | oof   |  |
| 020AC  | 00506                  | 50SC          | S1106052         | 234                     |                   |         |          |          |       |  |
| FILMS: WHITE SPECI   | ALTY                   |               |                  |                         |                   |         |          |          |       |  |
| TYVEK®  DuPont™ Tyvek® (1073D) is  DuPont™ and Tyvek® are tra  trademarks of E.I. du Pont de | ademarks or registered |               | lefin with excep | ional strength and m    | noisture resistal | nce.    |          |          |       |  |

| 046TV | 00103 | 40SC | S6881052 | 230 | 1 |  |
|-------|-------|------|----------|-----|---|--|
| 046TV |       |      | S4354052 | 106 | С |  |

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item



| Facer  | Adhesive                                     | Liner                            | Item                               | Approx Wgt/<br>MMSI                          | GB                                 | W WIN                            | MIN                   | ≤      |
|--|--|----------------------------------|------------------------------------|--|------------------------------------|----------------------------------|-----------------------|--------|
| HOT MELT PRODUCTS  |  |                                  |                                    |  |                                    |                                  |                       |        |
| 054SG/767HM/12PE-DES 54# C1S bright blue-white semi-glos paper. 767HM is a versatile hot melt surfaces. Clear 1.2 mil polyester line | adhesive with quick<br>r with an excellent s | k tack. It star<br>surface for d | nds up to mois<br>lie-cutting. Gre | ture and adheres se<br>at strength for high- | ecurely to low-e<br>speed converti | energy and<br>ng and app         | textured<br>dication. |        |
| Dry Edge Solutionsstocked in 1 maximize productivity on press. Roll  |  |                                  |                                    |  | designally designates              | jnea to min                      | IIIIIZE 002           | e and  |
|  |  |                                  | S9230452                           | 199  | 1                                  |                                  |                       |        |
| 054SG/767HM/40SC-DES   |  |                                  |                                    |  |                                    |                                  |                       |        |
| 54# C1S bright blue-white semi-glos<br>paper.767HM is a versatile hot melt<br>surfaces. Liner is a white densified k                 | adhesive with quick                          | tack. It stan                    | nds up to moist                    | ure and adheres se                           | curely to low-e                    | _                                |                       | tified |
| Dry Edge Solutionsstocked in 1 maximize productivity on press. Roll  |  |                                  |                                    |  | ecifically desig                   | ned to min                       | imize ooz             | e and  |
|  |  |                                  | S9230352                           | 233  | 1                                  |                                  |                       |        |
| 24WCT/767HM/40SC-DES   |  |                                  |                                    |  |                                    |                                  |                       |        |
| 2.4 mil white top-coated BOPP comp<br>savings.767HM is a versatile hot me<br>surfaces. Liner is a white densified k                  | It adhesive with quid                        | ck tack. It sta                  | ands up to moi                     | sture and adheres s                          | securely to low-                   |                                  |                       | i      |
| Dry Edge Solutionsstocked in 1 maximize productivity on press. Roll  |  |                                  |                                    |  | ecifically desig                   | ned to min                       | imize ooz             | e and  |
|  |  |                                  | S9230552                           | 180  | 1                                  |                                  |                       |        |
| 26WCT / 767HM / 12PE   |  |                                  |                                    |  |                                    |                                  |                       |        |
| The 2.6 mil glossy white BOPP face Adheres securely to low-energy and  |  |                                  |                                    |  |                                    |                                  |                       | e.     |
|  |  |                                  | S9167360                           | 154  | 1                                  |                                  |                       |        |
|  |  |                                  |                                    |  |                                    |                                  |                       |        |
|  |  |                                  |                                    |  |                                    |                                  |                       |        |
| -  | Kansas City, MO<br>- Minneapolis, MN         |                                  | lanta, GA<br>Angeles, CA           |  |                                    | I - Inventor C - Custom TIP Item | -                     |        |



| Facer      |  | Adhesive                                      | Liner        | Item                          | Approx Wgt/<br>MMSI | GB | WIN<br>KC   | MIN  | 4    |
|------------|--|---|--------------|-------------------------------|---------------------|----|-------------|------|------|
| HOT N      | IELT PRODUCTS  |   |              |                               |                     |    |             |      |      |
| 2WPET /    | / 254HM / 40SC   |   |              |                               |                     |    |             |      |      |
| hard-t     | mil white polyester with o<br>to-stick-to substrates such<br>ure has a dry edge for ea | h as rough textures, con                      | aminated s   |                               |                     |    |             |      | This |
|            |  |   |              | SC514600                      | 318                 | C  |             |      |      |
| 3WBOPF     | P / 254HMHCW / 40SC  | ;   |              |                               |                     |    |             |      |      |
| other      | il white polypropylene con<br>hard-to-stick-to substrate<br>edge for ease of converti  | s such as rough textures                      | _            |                               |                     |    |             |      |      |
|            |  |   |              | SC509600                      | 286                 | C  |             |      |      |
| 3WBOPF     | P / 298HMHCW / 40SC  | <br>;   |              |                               |                     |    |             |      |      |
| for ou     | mil white polypropylene f<br>tdoor markings of monito<br>structure has a dry edge f    | red crops. Also works we                      | ell on rough |                               |                     |    |             | -    |      |
|            |  |   |              | SC503900                      | 232                 | C  |             |      |      |
| 3WBOPF     | P / 298HMHCW / 78LF  |   |              |                               |                     |    |             |      |      |
| outdo      | mil white polypropylene f<br>or markings of monitored<br>ure has a dry edge for ea     | crops. Also works well of                     | n rough su   |                               |                     |    |             |      |      |
|            |  |   |              | SC503500                      | 318                 | C  |             |      |      |
| 60ML / 2   | 54HMHCW / 40SC   |   |              |                               |                     |    |             |      |      |
|            | Matte Litho paper combito-stick-to substrates such                                     |   |              |                               |                     |    |             |      | ther |
|            |  |   |              | SC514700                      | 338                 | C  |             |      |      |
|            |  |   |              |                               |                     |    |             |      |      |
|            |  |   |              |                               |                     |    |             |      |      |
| Locations: | GB - Green Bay, WI<br>WIN - Winchester, VA   | KC - Kansas City, MO<br>MIN - Minneapolis, MN |              | Atlanta, GA<br>os Angeles, CA |                     |    | I - Invento | n    |      |
|            |  |   |              |                               |                     |    | 111 10      | om - |      |



|                    |                                  |          |       |          | Approx Wgt/ | GB WIN ATL  | _ |
|--------------------|----------------------------------|----------|-------|----------|-------------|---|---|
| Facer              |                                  | Adhesive | Liner | Item     | MMSI        | GB WIN MIN ATL  |   |
| HOT MELT PRO       | DUCTS                            |          |       |          |             |   |   |
| 60ML / 298HMHCW    | Γ / 40SC                         |          |       |          |             |   |   |
|                    | of monitored c                   |          |       |          |             | hesive is approved by the USDA for is structure has a dry edge for ease of          |   |
|                    |                                  |          |       | SC512200 | 284         | C   |   |
| PATTERNED C        | OUPONS                           |          |       |          |             |   |   |
| 1MBSCPP15PET2U     | PW102                            |          |       |          |             |   |   |
|                    | s along the sh                   |          |       |          |             | ons across the web. The pattern provides nt release provides consumer-friendly peel |   |
|                    |                                  |          |       | SC510300 | 162         | C   |   |
| 1MBSCPP15PET3U     | PN102                            |          |       |          |             |   |   |
| provides adhesive- | free areas alo                   |          |       |          |             | cons across the web. The pattern Consistent release provides                        |   |
|                    |                                  |          |       | SC501300 | 162         | C   |   |
| 1MBSCPP15PET4U     | PN102                            |          |       |          |             |   |   |
| provides adhesive- | free areas alo                   |          |       |          |             | oons across the web. The pattern<br>Consistent release provides                     |   |
|                    |                                  |          |       | SC510400 | 162         | C   |   |
| 1MBSCPP15PET4U     | PW102                            |          |       |          |             |   |   |
| 4-up coupon base   | with a 1.4 mil<br>s along the sh |          |       |          |             | ons across the web. The pattern provides at release provides consumer-friendly peel |   |
|                    |                                  |          |       | SC510200 | 162         | C   |   |
|                    |                                  |          |       |          |             |   |   |
|                    |                                  |          |       |          |             |   |   |



| Facer      |  | Adhesive                                      | Liner | Item                                     | Approx Wgt/<br>MMSI | GB WIN KC ATL  | ≤      |
|------------|--|---|-------|--|---------------------|--|--------|
| PATT       | ERNED COUPONS                              | 5   |       |  |                     |  |        |
| 1MBSCI     | PP15PET6UPN102                             |   |       |  |                     |  |        |
| provid     |  | long the long edges, wh                       |       |  |                     | ons across the web. The pattern onsistent release provides               |        |
|            |  |   |       | SC510100                                 | 162                 | C  |        |
| 1MBSCI     | PP40SC2UPW853                              |   |       |  |                     |  |        |
| adhes      |  |   |       |  |                     | across the web. The pattern provid<br>t release provides consumer-friend |        |
|            |  |   |       | SC510800                                 | 186                 | C  |        |
| 1MBSCI     | PP40SC3UPN853                              |   |       |  |                     |  |        |
| adhes      | •  | ·   |       |  | ·                   | s across the web. The pattern prov<br>release provides consumer-friendly |        |
|            |  |   |       | SC510900                                 | 186                 | C  |        |
| 1MBSCI     | PP40SC4UPN853                              |   |       |  |                     |  |        |
| adhes      |  |   |       |  |                     | s across the web. The pattern prov<br>release provides consumer-friendly |        |
|            |  |   |       | SC511000                                 | 186                 | C  |        |
| 1MBSCI     | PP40SC4UPW853                              |   |       |  |                     |  |        |
| adhes      | •  | ·   |       |  | ·                   | across the web. The pattern provict release provides consumer-friend     |        |
| OITO I     |  |   |       |  |                     |  | y peel |
| anar       |  |   |       | SC502600                                 | 186                 | C  | y peel |
| anar       |  |   |       | SC502600                                 | 186                 | C  | y peel |
|            |  |   |       | SC502600                                 | 186                 | C  | y peel |
| Locations: | GB - Green Bay, WI<br>WIN - Winchester, VA | KC - Kansas City, MO<br>MIN - Minneapolis, MN |       | SC502600<br>atlanta, GA<br>s Angeles, CA | 186                 | I - Inventory C - Custom   | y peel |



| Facer   | Adhesive                          | Liner      | Item                        | Approx Wgt/<br>MMSI   | GB               | W WIN                            | MIN        | 4  |
|---|-----------------------------------|------------|-----------------------------|-----------------------|------------------|----------------------------------|------------|----|
| PATTERNED COUPONS   |                                   |            |                             |                       |                  |                                  |            |    |
| 1MBSCPP40SCUNIV   |                                   |            |                             |                       |                  |                                  |            |    |
| Universal coupon base with a 40# St patterned breakaway adhesive provi  |                                   |            |                             |                       |                  |                                  |            |    |
|   |                                   |            | SC502700                    | 186                   | C                |                                  |            |    |
| DURABLE TAGS  |                                   |            |                             |                       |                  |                                  |            |    |
| TAMPERPROOF ECONOMY   |                                   |            |                             |                       |                  |                                  |            |    |
| 60# white FSC® certified paper lami tear-resistant for security purposes,   |                                   |            |                             | n. This durable mate  | rial is designed | for tags the                     | at need to | be |
|   |                                   |            | SC501700                    | 378                   | C                |                                  |            |    |
| INTEGRATED PRODUCTS   |                                   |            |                             |                       |                  |                                  |            |    |
| 30LFL   |                                   |            |                             |                       |                  |                                  |            |    |
| A 30# layflat liner designed for making printing compatible. Custom made for  | -                                 |            | rinter applies              | its own adhesive to t | the back of the  | form. Flexo                      | and laser  | r  |
|   |                                   |            | SC503700                    | 69                    | C                |                                  |            |    |
| 40SC / 757 / 41LF   |                                   |            |                             |                       |                  |                                  |            |    |
| An acrylic adhesive transfer tape pro<br>such as, shipping and return labels f<br>mailed promotions. Available in 60" r | or e-commerce, me                 |            |                             |                       |                  | _                                |            |    |
|   |                                   |            | SC515600                    | 215                   | C                |                                  |            |    |
| 40SC / 767HM / 40SC   |                                   |            |                             |                       |                  |                                  |            |    |
| A hot melt adhesive transfer tape pro-<br>labels in forms such as, shipping and<br>labels included in mailed promotions | d return labels for e             | -commerce, | , medical form              |                       |                  |                                  |            |    |
|   |                                   |            | SC509200                    | 229                   | C                |                                  |            |    |
|   |                                   |            |                             |                       |                  |                                  |            |    |
|   |                                   |            |                             |                       |                  |                                  |            |    |
| -   | Kansas City, MO - Minneapolis, MN |            | tlanta, GA<br>s Angeles, CA |                       |                  | I - Inventor C - Custom TIP Iter |            |    |
|   |                                   |            |                             |                       |                  |                                  |            |    |



| Facer                                     |   | Adhesive  | Liner   | Item   | Approx Wgt/<br>MMSI   | GB WIN WIN ATL  | 4    |
|---|---|---|---|--|---|---|------|
| INTEG                                     | RATED PRODUC  | TS  |   |  |   |   |      |
| BL20CL                                    | R4.0  |   |   |  |   |   |      |
|   | mil clear PET back lamin<br>sive / 40# Paper Liner. W   |   |   |  | lm / Break Away Coa   | ating / 2.0 mil PET Film / 515 Permar   | nent |
|   |   |   |   | SC504300   | 340   | C   |      |
| BL20CL                                    | R7.75   |   |   |  |   |   |      |
|   | mil clear PET back lamin<br>anent Adhesive / 40# Pap  |   |   |  |   | Coating / 2.0 mil PET Film / 515  |      |
|   |   |   |   | SC511100   | 340   | C   |      |
| BL20CL                                    | RFG   |   |   |  |   |   |      |
| A 2.0                                     | mil clear PET back lamin  | ate with full gum adhesiv   | ve up to 30   | inches - 2.0 mil   |   | way Coating / 2.0 mil PET Film / 515  |      |
| Perm                                      | anent Adhesive / 40# Par  | per Liner. When the card  | is removed  | l, a clear windo   | w remains.  |   |      |
| Perm                                      | anent Adhesive / 40# Par  | per Liner. When the card  | is removed  | l, a clear window  | w remains.  | c   |      |
|   |   | per Liner. When the card  | is removed  |  |   | C   |      |
| BLPAPE<br>A 40#                           | ER4.0   | n 4 inch patterned adhes  | ive - 40# Pa  | SC504200   | 340<br>nated to 1.0 mil Clea  | r PET Film / Break Away Coating / 2 window remains.                           | .0   |
| BLPAPE<br>A 40#                           | ER4.0<br># paper back laminate witl   | n 4 inch patterned adhes  | ive - 40# Pa  | SC504200   | 340<br>nated to 1.0 mil Clea  |   | .0   |
| BLPAPE<br>A 40#<br>mil Cl                 | ER4.0<br># paper back laminate witl<br>lear PET Film / 515 Perm   | n 4 inch patterned adhes  | ive - 40# Pa  | SC504200  aper Liner lamir Vhen the card is  | 340<br>nated to 1.0 mil Clea<br>s removed, a paper v  |   | .0   |
| BLPAPE A 40# mil Cl                       | ER4.0<br># paper back laminate witl<br>lear PET Film / 515 Perm   | n 4 inch patterned adhes<br>anent Adhesive / 40# Pa<br>n full gum adhesive up to                            | ive - 40# Pa<br>per Liner. V                                | sC504200  aper Liner lamin When the card is  sC506000  - 40# Paper Lin   | 340 nated to 1.0 mil Clea s removed, a paper v 401 ner laminated to 1.0 r                             | vindow remains.  C  B  B  B  B  B  B  B  B  B  B  B  B                        | _    |
| BLPAPE A 40# mil Cl                       | ER4.0  # paper back laminate witl lear PET Film / 515 Perm  ERFG # paper back laminate witl                             | n 4 inch patterned adhes<br>anent Adhesive / 40# Pa<br>n full gum adhesive up to                            | ive - 40# Pa<br>per Liner. V                                | sC504200  aper Liner lamin When the card is  sC506000  - 40# Paper Lin   | 340 nated to 1.0 mil Clea s removed, a paper v 401 ner laminated to 1.0 r                             | vindow remains.  C  B  B  B  B  B  B  B  B  B  B  B  B                        |      |
| BLPAPE A 40# BLPAPE A 40# / 2.0 i         | ER4.0  # paper back laminate witl lear PET Film / 515 Perm  ERFG # paper back laminate witl                             | n 4 inch patterned adhes<br>anent Adhesive / 40# Pa<br>n full gum adhesive up to                            | ive - 40# Pa<br>per Liner. V                                | aper Liner lamin When the card is SC506000  - 40# Paper Liner. When the co   | ated to 1.0 mil Clea<br>s removed, a paper v<br>401<br>der laminated to 1.0 materials removed, a para | vindow remains.  C  B  B  B  B  B  B  B  B  B  B  B  B                        |      |
| BLPAPE A 40# MII CI  BLPAPE A 40# / 2.0 I | ER4.0  # paper back laminate with lear PET Film / 515 Perm  ERFG # paper back laminate with mil Clear PET Film / 515 I  | n 4 inch patterned adhes<br>anent Adhesive / 40# Pa<br>n full gum adhesive up to                            | ive - 40# Pa<br>per Liner. V                                | aper Liner lamin When the card is SC506000  - 40# Paper Liner. When the co   | ated to 1.0 mil Clea<br>s removed, a paper v<br>401<br>der laminated to 1.0 materials removed, a para | vindow remains.  C  B  B  B  B  B  B  B  B  B  B  B  B                        | _    |
| BLPAPE A 40# MII CI  BLPAPE A 40# / 2.0 I | ER4.0 # paper back laminate witlear PET Film / 515 Perm  ERFG # paper back laminate witl                                | n 4 inch patterned adhes<br>anent Adhesive / 40# Pa<br>n full gum adhesive up to<br>Permanent Adhesive / 40 | ive - 40# Pa<br>per Liner. V<br>9 30 inches<br>9# Paper Lir | sc504200  aper Liner lamin When the card is sc506000  - 40# Paper Liner. When the coscopies with the cost of the c | 340 nated to 1.0 mil Cleas removed, a paper v 401 ner laminated to 1.0 reard is removed, a pa         | window remains.  C  mil Clear PET Film / Break Away Coaper window remains.  C |      |
| BLPAPE A 40# MII CI  BLPAPE A 40# / 2.0 I | ER4.0  # paper back laminate with lear PET Film / 515 Perm  ERFG # paper back laminate with mill Clear PET Film / 515 I | n 4 inch patterned adhes<br>anent Adhesive / 40# Pa<br>n full gum adhesive up to<br>Permanent Adhesive / 40 | ive - 40# Pa<br>per Liner. V<br>9 30 inches<br>9# Paper Lir | sc504200  aper Liner lamin When the card is sc506000  - 40# Paper Liner. When the coscopies with the cost of the c | 340 nated to 1.0 mil Cleas removed, a paper v 401 ner laminated to 1.0 reard is removed, a pa         | window remains.  C  mil Clear PET Film / Break Away Coaper window remains.  C |      |



### BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

| acer  | Adhesive  | Liner   | Item  | Approx Wgt/<br>MMSI  | GB            | N N      | \$       | Σ          | ATL   | ≤     |
|---|---|---|---|--|---------------|----------|----------|------------|-------|-------|
| PIGGYBACKS  | Adilosive   | Ellici  | itom  | NIMO!  |               |          |          |            |       |       |
| 50# EDP SMUDGE RESIST   | ANT   |   |   |  |               |          |          |            |       |       |
| A 50# (74 g/m²) general pu<br>FSC®-certified paper.   | ırpose uncoated paper. Briç   | ght white wit   | th excellent smud   | dge resistance. Desig  | ned for high  | perfori  | mance    |            |       |       |
| 050ED   | 0758M<br>0758M  | 40SC<br>40SC  | S7725060  | 356  | C             |          |          |            |       |       |
| 54# SEMI-GLOSS  |   |   |   |  |               |          |          |            |       |       |
| 54# (78 g/m²) C1S bright b<br>Smooth surface provides e   |   |   |   |  |               | ping a   | nd die-  | -cuttin    | g.    |       |
| 054SG   | 00515<br>00515  | 12NB<br>40SC  | S9075360  | 318  |               |          |          |            |       |       |
| 054SG   | 0758M<br>0758M  | 40SC<br>50SC  | S7686660  | 375  | C             |          |          |            |       |       |
| 054SG   | 0758M<br>0758M  | 40SC<br>40SC  | S8027060  | 354  | 1             |          |          |            |       |       |
| 61# (99 g/m²) decorative p<br>1/32" wide. The area betwe<br>056H7   | een the shim lines measure  | Shim lines/ses 30" mach   |   |  | _             | p in the | e patte  | rn will    | be up | to    |
| 61# (99 g/m²) decorative p. 1/32" wide. The area between  | rismatic diffraction paper. Seen the shim lines measure   | Shim lines/ses 30" mach   | ine direction (MD   | )) and 48" cross direc   | tion (CD)     | p in the | patte    | rn will    | be up | to    |
| 61# (99 g/m²) decorative p. 1/32" wide. The area between  | rismatic diffraction paper. S<br>een the shim lines measure<br>0758M<br>0758M   | Shim lines/se<br>es 30" mach<br>40SC<br>40SC  | S8265860  | o) and 48" cross direct  | tion (CD)     |          |          |            | be up | to    |
| 61# (99 g/m²) decorative p. 1/32" wide. The area betwee 056H7   | rismatic diffraction paper. S<br>een the shim lines measure<br>0758M<br>0758M   | Shim lines/se<br>es 30" mach<br>40SC<br>40SC  | S8265860  | o) and 48" cross direct  | tion (CD)     |          |          |            | be up | to    |
| 61# (99 g/m²) decorative p<br>1/32" wide. The area betwee<br>056H7<br>60# DULL LITHO<br>60# (89 g/m²) high quality,   | rismatic diffraction paper. S<br>een the shim lines measure<br>0758M<br>0758M   | Shim lines/se<br>es 30" mach<br>40SC<br>40SC  | S8265860  | o) and 48" cross direct  | tion (CD)     |          |          |            | be up | to    |
| 61# (99 g/m²) decorative p<br>1/32" wide. The area betwee<br>056H7<br>60# DULL LITHO<br>60# (89 g/m²) high quality,<br>FSC®-certified paper.  | rismatic diffraction paper. Seen the shim lines measure 0758M 0758M dull finish litho offering exc  | Shim lines/se as 30" mach 40SC 40SC ellent print a  | S8265860 and die-cut prope  | 375 erties. Good for flexog  | c graphic and |          |          |            | be up | to to |
| 61# (99 g/m²) decorative p. 1/32" wide. The area betwee  056H7  60# DULL LITHO  60# (89 g/m²) high quality, FSC®-certified paper.  061DL  | rismatic diffraction paper. Seen the shim lines measure 0758M 0758M dull finish litho offering exc 0758M 0758M 0758M  | Shim lines/se as 30" mach  40SC  40SC  ellent print at  40SC  40SC                                    | S8265860  and die-cut prope S8719060                                      | and 48" cross directions of the control of the cont | graphic and C | offset p | printing | <b>]</b> . |       | o to  |
| 61# (99 g/m²) decorative p<br>1/32" wide. The area between<br>056H7  60# DULL LITHO  60# (89 g/m²) high quality, FSC®-certified paper.  061DL  VALUE THERMAL TRANSI  A 42# (62 g/m²) top-coated                               | rismatic diffraction paper. Seen the shim lines measure 0758M 0758M dull finish litho offering exc 0758M 0758M 0758M  | Shim lines/se as 30" mach  40SC  40SC  ellent print at  40SC  40SC                                    | S8265860  and die-cut prope S8719060                                      | and 48" cross directions of the control of the cont | graphic and C | offset p | printing | <b>]</b> . |       | to to |
| 61# (99 g/m²) decorative pr<br>1/32" wide. The area between<br>056H7  60# DULL LITHO 60# (89 g/m²) high quality,<br>FSC®-certified paper.  061DL  VALUE THERMAL TRANSI A 42# (62 g/m²) top-coated conventional thermal transi | rismatic diffraction paper. Seen the shim lines measure 0758M 0758M dull finish litho offering exc 0758M 0758M FER I, thermal transfer sheet the fer facers. Exceptional prin | Shim lines/se as 30" mach 40SC 40SC ellent print a 40SC 40SC at offers high at quality, es 40SC       | S8265860  and die-cut prope S8719060  a performance at pecially for flood | and 48" cross directions and 48" cross directions.  375  arrives. Good for flexograms arrives.  377  a lower cost. Streng coating. FSC®-certifications.  | graphic and C | offset p | printing | <b>]</b> . |       | to to |
| 61# (99 g/m²) decorative pr<br>1/32" wide. The area between<br>056H7  60# DULL LITHO 60# (89 g/m²) high quality,<br>FSC®-certified paper.  061DL  VALUE THERMAL TRANSI A 42# (62 g/m²) top-coated conventional thermal transi | rismatic diffraction paper. Seen the shim lines measure 0758M 0758M dull finish litho offering exc 0758M 0758M FER I, thermal transfer sheet the fer facers. Exceptional prin | Shim lines/se as 30" mach 40SC 40SC ellent print a 40SC 40SC at offers high the quality, es 40SC 40SC | S8265860  and die-cut prope S8719060  a performance at pecially for flood | and 48" cross directions and 48" cross directions.  375  arrives. Good for flexograms arrives.  377  a lower cost. Streng coating. FSC®-certifications.  | graphic and C | offset p | printing | g.         |       | to    |

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



### BIG ENOUGH TO SERVE YOU, SMALL ENOUGH TO KNOW YOU

Facer Adhesive Liner Item Approx Wgt/
MMSI

Approx Wgt/
MMSI

HOT MELT DRY EDGE SOLUTIONS

### 054SG/767HM/12PE-DES

54# C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. FSC®-certified paper. 767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Clear 1.2 mil polyester liner with an excellent surface for die-cutting. Great strength for high-speed converting and application. ---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

**S9230452** 199 I

### 054SG/767HM/40SC-DES

54# C1S bright blue-white semi-gloss. High strength property makes it ideal for wide web high-speed stripping and die-cutting. FSC®-certified paper.767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Liner is a white densified kraft sheet 41# (67 g/m2) with excellent point-to-point caliper control. ---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

**S9230352** 233 I

### 24WCT/767HM/40SC-DES

2.4 mil white top-coated BOPP compatible with water-based, UV flexo, and UV inkjet presses. Thinner for resource and shipping savings.767HM is a versatile hot melt adhesive with quick tack. It stands up to moisture and adheres securely to low-energy and textured surfaces. Liner is a white densified kraft sheet 41# (67 g/m2) with excellent point-to-point caliper control. ---Dry Edge Solutions---stocked in 13" standard width. Features 1/8" dry (adhesive-free) outer edge specifically designed to minimize ooze and maximize productivity on press. Rolls are offered in 5,000 ft lengths at quantities of 780 MSI per roll.

**S9230552** 180 **I** 

Locations: GB - Green Bay, WI KC - Kansas City, MO ATL - Atlanta, GA I - Inventory
WIN - Winchester, VA MIN - Minneapolis, MN LA - Los Angeles, CA
TIP Item

All orders taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. Green Bay Packaging's standard Terms and Conditions as in effect at the time of sale shall control.



### **April**



|                       | WHITE PAP   | ERS - HIC | SH-GLOS  | S                       |                         |                   |              |         |                         |
|-----------------------|---|-----------|--|-------------------------|-------------------------|-------------------|--------------|---------|-------------------------|
| Structure             | Description   | Item #    | Splice<br>Free   | GB                      | WIN                     | кс                | MIN          | ATL     | LA                      |
|                       |   |           |  |                         |                         |                   |              |         |                         |
| 057HG / 720 / 40SC    | 57# CAST COATED HI GLOSS<br>720 ALL TEMP ADHESIVE                     | S7824560  | No   | V                       | $\overline{\checkmark}$ | Ш                 |              |         | $\overline{\checkmark}$ |
| 057HG / 751 / 40SC    | 57# CAST COATED HI GLOSS<br>751 PERMANENT ADHESIVE<br>(HEAVY CT. WT.) | \$8060260 | No   |                         |                         |                   | $\checkmark$ |         |                         |
|                       | WHITE PAP   | ERS - SE  | MI-GLOS  | S                       |                         |                   |              |         |                         |
| Structure             | Description   | Item #    | Splice<br>Free   | GB                      | WIN                     | KC                | MIN          | ATL     | LA                      |
|                       |   |           |  |                         |                         |                   |              |         |                         |
| 054SG / 278 / 40SC    | 54# C1S SEMI GLOSS FSC<br>278 ULTRA REMOVABLE ADH                     | S8164560  | No   | $\checkmark$            |                         |                   |              |         |                         |
| 054SG / 633 / 40SC    | 54# C1S SEMI GLOSS FSC<br>633 REMOVABLE ADHESIVE                      | S9175160  | No   | $\checkmark$            |                         |                   |              |         |                         |
| 054SG / 700 / 40SC    | 54# C1S SEMI GLOSS FSC<br>700 PERMANENT ADHESIVE                      | S7755860  | Yes  | $\checkmark$            |                         |                   |              |         |                         |
| 054SG / 720 / 12NB    | 54# C1S SEMI GLOSS FSC<br>720 ALL-TEMP ADHESIVE                       | S8121860  | No   | $\checkmark$            | $\checkmark$            |                   |              |         | $\checkmark$            |
| 054SG / 720 / 40SC    | 54# C1S SEMI GLOSS FSC<br>720 ALL-TEMP ADHESIVE                       | S7724460  | Yes, Except:<br>WIN-15-No<br>KC-15-No<br>ATL-15-No<br>LA-15-No | 5/10/15                 | 5/10/15                 | 5/10/15           | $\checkmark$ | 5/10/15 | 5/10/15                 |
| F54SG / 720 / 40SC    | FSC 53# C1S SEMI GLOSS<br>720 ALL-TEMP ADHESIVE                       | S8792860  | No   |                         |                         |                   |              |         | $\checkmark$            |
| 054SG / 720M / 40SC   | 54# C1S SEMI GLOSS FSC<br>720M ALL TEMP ADHESIVE                      | S8849360  | Yes, Except:<br>GB-1.25/2.5-N<br>o<br>LA-15-No                 | 1.25/ 2.5/<br>5/ 10/ 15 | 5/10/15                 |                   |              | 5/10/15 | 5/10/15                 |
| 054SG / 747 / 40SC    | 54# C1S SEMI GLOSS FSC<br>747 PERMANENT ADHESIVE                      | S7739560  | Yes  | $\checkmark$            | $\checkmark$            |                   |              |         |                         |
| 054SG / 751 / 40SC    | 54# C1S SEMI GLOSS FSC<br>751 PERMANENT ADHESIVE                      | S7748960  | Yes  | $\checkmark$            | $\checkmark$            | $\checkmark$      | $\checkmark$ |         | $\checkmark$            |
| 054SG / 758M / 41LF   | 54# C1S SEMI GLOSS FSC<br>758M PERMANENT ADHESIVE                     | S9176660  | No   | √ †<br>5/10/15          | à<br>5/10/15            |                   |              |         |                         |
| 054SG / 758M / 0PRLF  | 54# C1S SEMI GLOSS FSC<br>758M PERMANENT ADHESIVE                     | S8082660  | No   | 10/ 15<br>(exact)       | 10/15<br>(exact)        | 10/ 15<br>(exact) |              |         |                         |
| 054SG / 805 / 0PRLF   | 54# C1S SEMI GLOSS FSC<br>805 REMOVABLE ADHESIVE                      | S8941160  | No   | <b>☑</b> †              |                         |                   |              |         |                         |
| 054SG / 80361 / 0PRLF | 54# C1S SEMI GLOSS FSC<br>80361 REMOVABLE ADHESIVE                    | S8001560  | No   | √ †<br>5/10/15          |                         |                   |              |         |                         |

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores



# ¥ 1

|                      |   | •          |                                   |                  | ()()                 |              |              |              |              |
|----------------------|---|------------|-----------------------------------|------------------|----------------------|--------------|--------------|--------------|--------------|
|                      | WHITE PA  | PERS - SE  |                                   | S                |                      |              |              |              |              |
| Structure            | Description   | Item #     | Splice<br>Free                    | GB               | WIN                  | KC           | MIN          | ATL          | LA           |
| 054SA / 720 / 40SC   | 054SG OPAQUE FSC<br>720 ALL-TEMP ADHESIVE           | S8820660   | No                                | V                |                      |              |              |              |              |
| 054WS / 747 / 40SC   | 54# SG WET STRENGTH FSC<br>747 PERMANENT ADHESIVE   | S8901460   | No                                | 2.5/5/10         | $\checkmark$         |              |              |              |              |
| 060PR / 272 / 40SC   | PREFERRED SEMI GLOSS FSC<br>272 ULTRA REMOVABLE ADH | S7018060   | No                                | $\checkmark$     |                      |              |              |              |              |
| 060PR / 275 / 41WK   | PREFERRED SEMI GLOSS FSC<br>275 ULTRA REMOVABLE ADH | S9156360   | No                                | $\checkmark$     | $\checkmark$         |              |              |              |              |
| 060PA / 758M / 40SC  | 060PR OPAQUE FSC<br>758M PERMANENT ADHESIVE         | S7712860   | No                                | $\checkmark$     | $\checkmark$         |              |              |              | $\checkmark$ |
| 060SG / 720 / 40SC   | 58# SEMI GLOSS LITHO FSC<br>720 ALL-TEMP ADHESIVE   | S7804560   | No                                | $\checkmark$     | 5/10/15              |              |              | $\checkmark$ |              |
| 060SG / 720M / 40SC  | 58# SEMI GLOSS LITHO FSC<br>720M ALL TEMP ADHESIVE  | S8899160   | No                                | $\checkmark$     | $\checkmark$         | $\checkmark$ |              |              | $\checkmark$ |
| 060SG / 720 / 12NB   | 58# SEMI GLOSS LITHO FSC<br>720 ALL TEMP ADHESIVE   | S8210060   | No                                |                  |                      | 10           |              |              |              |
| 060SG / 758M / 60LF  | 58# SEMI GLOSS LITHO FSC<br>758M PERMANENT ADHESIVE | S8003760   | No                                |                  | 5/ 10/ 15<br>(exact) |              |              |              |              |
|                      | WHITE   | PAPERS -   | MATTE                             |                  |                      |              |              |              |              |
| Structure            | Description   | Item #     | Splice<br>Free                    | GB               | WIN                  | кс           | MIN          | ATL          | LA           |
| 061DL / 720 / 40SC   | 60# DULL LITHO FSC<br>720 ALL-TEMP ADHESIVE         | S4331060   | No                                | V                |                      |              |              |              |              |
| 061DL / 758M / 0PRLF | 60# DULL LITHO FSC<br>758M PERMANENT ADHESIVE       | S8003060   | Yes, Except:<br>GB-10-No          | <b>√</b> † 10/15 |                      |              |              |              |              |
| 061DL / 758M / 40SC  | 60# DULL LITHO FSC<br>758M PERMANENT ADHESIVE       | S8769360   | Yes, Except:<br>GB-5/10/20-N<br>o | 5/ 10/ 15/<br>20 |                      |              |              |              |              |
|                      | WHITE PAPER   | S - INDIGO |                                   | ATED             |                      |              |              |              |              |
| Structure            | Description   | Item #     | Splice<br>Free                    | GB               | WIN                  | КС           | MIN          | ATL          | LA           |
| D55SG / 751 / 40SC   | FSC DIGITAL SEMI GLOSS<br>751 PERMANENT ADHESIVE    | S8126960   | No                                |                  |                      |              | $\checkmark$ |              |              |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



### **April**

|                      |  | , .p     |                |                         | \ K     |    |     |     |              |
|----------------------|--|----------|----------------|-------------------------|---------|----|-----|-----|--------------|
|                      | Т  | AG STOCK | (              |                         |         |    |     |     |              |
| Structure            | Description  | Item #   | Splice<br>Free | GB                      | WIN     | кс | MIN | ATL | LA           |
|                      |  |          |                |                         |         |    |     |     |              |
| 008GB                | 8 PT TAG C2S FSC   | S7670560 | No             | $\checkmark$            |         |    |     | Ш   | Ш            |
| 008GB / 504 / 40SC   | 8 PT TAG C2S FSC<br>504 PERMANENT ADHESIVE                         | S9941860 | No             | $\overline{\checkmark}$ |         |    |     |     |              |
| 008GB / 751 / 40SC   | 8 PT TAG C2S FSC<br>751 PERMANENT ADHESIVE                         | S7666660 | No             |                         |         |    |     |     |              |
|                      |  | EDP      |                |                         |         |    |     |     |              |
| Structure            | Description  | Item #   | Splice<br>Free | GB                      | WIN     | KC | MIN | ATL | LA           |
| 050ED / 720 / 40SC   | 50# EDP FSC<br>720 ALL-TEMP ADHESIVE                               | S6069060 | No             | $\checkmark$            |         |    |     |     |              |
| 050ED / 720 / 50SC   | 50# EDP FSC<br>720 ALL-TEMP ADHESIVE                               | S6499060 | No*            | $\checkmark$            |         |    |     |     |              |
|                      | PHA  | RMACEUTI | CAL            |                         |         |    |     |     |              |
| Structure            | Description  | Item #   | Splice<br>Free | GB                      | WIN     | кс | MIN | ATL | LA           |
| 021RX / 508 / 40SC   | 3.0 MIL PHARMACY DT FSC  | S9174760 | No*            |                         |         |    |     |     | V            |
| 021RX / 506 / 405C   | 508 PERMANENT ADHESIVE   | 39174760 | NO             | Ш                       | Ш       | V  | Ш   | Ш   | V            |
| 021RX / 751 / 40SC   | 3.0 MIL PHARMACY DT FSC<br>751 PERMANENT ADHESIVE                  | S9174660 | No*            | 5/10/15                 | 5/10/15 |    |     |     |              |
|                      | FLUOR  | ESCENT P | APERS          |                         |         |    |     |     |              |
| Structure            | Description  | Item #   | Splice<br>Free | GB                      | WIN     | кс | MIN | ATL | LA           |
| 054GZ / 720 / 40SC   | FSC GREEN FLUORESCENT<br>720 ALL TEMP ADHESIVE                     | S6231060 | No             | $\checkmark$            |         |    |     |     |              |
| 054GZ / 720 / 40SC   | FSC GREEN FLUORESCENT<br>720 ALL TEMP ADHESIVE<br>(TIGHT RELEASE)  | S7656360 | No             |                         |         |    |     |     | $\checkmark$ |
| 054GZ / 758M / 0PBLF | FSC GREEN FLUORESCENT<br>758M PERMANENT ADHESIVE                   | S8189860 | No             | <b>✓</b> †              |         |    |     |     |              |
| 054OZ / 720 / 40SC   | FSC ORANGE FLUORESCENT<br>720 ALL TEMP ADHESIVE                    | S6235060 | No             | $\checkmark$            |         |    |     |     |              |
| 054OZ / 720 / 40SC   | FSC ORANGE FLUORESCENT<br>720 ALL TEMP ADHESIVE<br>(TIGHT RELEASE) | S7607960 | No             |                         |         |    |     |     | $\checkmark$ |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



# ¥ 1

## **April**

|                      |  |          |                                   |                  | ( )(         |              |     |              |              |
|----------------------|--|----------|-----------------------------------|------------------|--------------|--------------|-----|--------------|--------------|
|                      | FLUOR  | ESCENT P | APERS                             |                  |              |              |     |              |              |
| Structure            | Description  | Item #   | Splice<br>Free                    | GB               | WIN          | кс           | MIN | ATL          | LA           |
| 054OZ / 758M / 0PBLF | FSC ORANGE FLUORESCENT<br>758M PERMANENT ADHESIVE                  | S8190060 | No                                | <b>☑</b> †       |              |              |     |              |              |
| 054PZ / 720 / 40SC   | FSC PINK FLUORESCENT<br>720 ALL TEMP ADHESIVE                      | S8034360 | No                                | $\checkmark$     |              |              |     |              |              |
| 054PZ / 720 / 40SC   | FSC PINK FLUORESCENT<br>720 ALL TEMP ADHESIVE<br>(TIGHT RELEASE)   | S7748660 | No                                |                  |              |              |     |              | $\checkmark$ |
| 054PZ/758M/0PBLF     | FSC PINK FLUORESCENT<br>758M PERMANENT ADHESIVE                    | S8190160 | No                                | <b>✓</b> †       |              |              |     |              |              |
| 054RZ / 720 / 40SC   | FSC RED FLUORESCENT<br>720 ALL TEMP ADHESIVE                       | S6066060 | No                                | $\checkmark$     | $\checkmark$ | $\checkmark$ |     | $\checkmark$ |              |
| 054RZ / 720 / 40SC   | FSC RED FLUORESCENT<br>720 ALL TEMP ADHESIVE<br>(TIGHT RELEASE)    | S7743960 | No                                |                  |              |              |     |              | $\checkmark$ |
| 054RZ / 758M / 0PBLF | FSC RED FLUORESCENT<br>758M PERMANENT ADHESIVE                     | S8190260 | No                                | <b>✓</b> †       |              |              |     |              |              |
| 054YZ / 720 / 40SC   | FSC YELLOW FLUORESCENT<br>720 ALL TEMP ADHESIVE                    | S6237060 | No                                | $\checkmark$     |              |              |     |              |              |
| 054YZ / 720 / 40SC   | FSC YELLOW FLUORESCENT<br>720 ALL TEMP ADHESIVE<br>(TIGHT RELEASE) | S7748760 | No                                |                  |              |              |     |              | $\checkmark$ |
| 054YZ / 758M / 0PBLF | FSC YELLOW FLUORESCENT<br>758M PERMANENT ADHESIVE                  | S8189960 | No                                | <b>☑</b> †       |              |              |     |              |              |
|                      | BEER   | & WINE L | ABEL                              |                  |              |              |     |              |              |
| Structure            | Description  | Item #   | Splice<br>Free                    | GB               | WIN          | KC           | MIN | ATL          | LA           |
| 054WS / 747 / 40SC   | 54# SG WET STRENGTH FSC<br>747 PERMANENT ADHESIVE                  | S8901460 | No                                | 2.5/5/10         | $\checkmark$ |              |     |              |              |
| 061DL / 720 / 40SC   | 60# DULL LITHO FSC<br>720 ALL-TEMP ADHESIVE                        | S4331060 | No                                | $\checkmark$     |              |              |     |              |              |
| 061DL / 758M / 0PRLF | 60# DULL LITHO FSC<br>758M PERMANENT ADHESIVE                      | S8003060 | Yes, Except:<br>GB-10-No          | à<br>10/15       |              |              |     |              |              |
| 061DL / 758M / 40SC  | 60# DULL LITHO FSC<br>758M PERMANENT ADHESIVE                      | S8769360 | Yes, Except:<br>GB-5/10/20-N<br>o | 5/ 10/ 15/<br>20 |              |              |     |              |              |
| 0WEL4 / 747 / 44PM   | ESTATELBL#4 WHI LAID FSC<br>747 PERMANENT ADHESIVE                 | S8748260 | No                                | 2.5/5/10         |              |              |     |              |              |
| 0WEL8 / 747 / 44PM   | FSC ESTATE #8 WH VELLUM<br>747 PERMANENT ADHESIVE                  | S8266860 | No                                | 2.5/5/10         |              |              |     |              | 2.5/5/10     |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



|                     | BEER   | & WINE LA | ABEL           |                         |          |              |     |     |              |
|---------------------|--|-----------|----------------|-------------------------|----------|--------------|-----|-----|--------------|
| Structure           | Description  | Item #    | Splice<br>Free | GB                      | WIN      | KC           | MIN | ATL | LA           |
| OWEL9 / 747 / 44PM  | ESTATELBL#9 CRM LAID FSC<br>747 PERMANENT ADHESIVE | S8742160  | No             | 2.5/5/10                |          |              |     |     | 2.5/5/10     |
| 0WCSW / 747 / 44PM  | FSC CLASSICCRESTSOLAR WH<br>747 PERMANENT ADHESIVE | S8741852  | No             | 2.5/5/10                |          |              |     |     |              |
| 70BWF / 747 / 12NB  | FSC BRIGHT WHITE FELT WS<br>PERMANENT ADHESIVE     | S8903752  | No             | 2.5/5/10                |          |              |     |     |              |
| 70BWF / 747 / 44PM  | FSC BRIGHT WHITE FELT WS<br>747 PERMANENT ADHESIVE | S8903652  | No             | 2.5/5/10                |          |              |     |     |              |
| KONAL / 720 / 39NK  | FSC KONA LIGHT WS<br>720 ALL TEMP ADHESIVE         | S8796760  | No             | 2.5/5/10                |          |              |     |     |              |
| PLRNB / 720 / 39NK  | FSC ECO WHITE WS 100%PCW<br>720 ALL TEMP ADHESIVE  | S9089960  | No             | $\checkmark$            |          |              |     |     |              |
| 56MSW / 720 / 40SC  | SILVER MET PAPER WS<br>720 ALL TEMP ADHESIVE       | S8982560  | No             | $\checkmark$            |          |              |     |     |              |
|                     | SPEC   | IALTY PAF | PERS           |                         |          |              |     |     |              |
| Structure           | Description  | Item #    | Splice<br>Free | GB                      | WIN      | кс           | MIN | ATL | LA           |
| 054WS / 747 / 40SC  | 54# SG WET STRENGTH FSC<br>747 PERMANENT ADHESIVE  | S8901460  | No             | 2.5/5/10                | <b>V</b> |              |     |     |              |
| 060GM / 720 / 40SC  | 60# NATURAL KRAFT PAPER<br>720 ALL-TEMP ADHESIVE   | S8083760  | No*            |                         |          | $\checkmark$ |     |     | $\checkmark$ |
| 060GM / 758M / 40SC | 60# NATURAL KRAFT PAPER<br>758M PERMANENT ADHESIVE | S7649360  | No             | $\checkmark$            |          |              |     |     |              |
| 1HEMP / 720 / 39NK  | HEMP PAPER<br>720 ALL-TEMP ADHESIVE                | S9111352  | No             | 2.5/5/10                |          |              |     |     |              |
| H2ODP / 611 / 40SC  | FSC WATER DISSOLVE PAPER<br>WATER DISSOLVABLE ADH  | S8210460  | No             | 2.5/5/10                |          |              |     |     |              |
| KONAL / 720 / 39NK  | FSC KONA LIGHT WS                                  |           |                | $\overline{\checkmark}$ | _        |              | П   | _   | _            |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



# 1

|                     |   | , .b      |                |              | / X          |              |     |     |              |
|---------------------|---|-----------|----------------|--------------|--------------|--------------|-----|-----|--------------|
|                     | LAM   | INATED FO | OILS           |              |              |              |     |     |              |
| Structure           | Description                                       | Item #    | Splice<br>Free | GB           | WIN          | кс           | MIN | ATL | LA           |
| 055BG / 720 / 40SC  | BRIGHT GOLD LAM FOIL FSC<br>720 ALL TEMP ADHESIVE | S6301060  | No             | $\checkmark$ |              |              |     |     | $\checkmark$ |
| 055BS / 720 / 40SC  | BRIGHT SLVR LAM FOIL FSC<br>720 ALL TEMP ADHESIVE | S6299060  | No             | $\checkmark$ | $\checkmark$ |              |     |     | $\checkmark$ |
| 055DG / 720 / 40SC  | DULL GOLD LAM FOIL FSC<br>720 ALL TEMP ADHESIVE   | S6300060  | No             | $\checkmark$ |              |              |     |     |              |
| 055DS / 720 / 40SC  | DULL SILVER LAM FOIL FSC<br>720 ALL TEMP ADHESIVE | S6306060  | No             | $\checkmark$ | $\checkmark$ |              |     |     | $\checkmark$ |
|                     | FOIL  | SUBSTITU  | TES            |              |              |              |     |     |              |
| Structure           | Description                                       | Item #    | Splice<br>Free | GB           | WIN          | кс           | MIN | ATL | LA           |
| 018MT / 102 / 40SC  | 1.85MIL METALIZED TCBOPP<br>FILMIC ADHESIVE       | S9129360  | No             |              |              |              |     |     | $\checkmark$ |
| 018MT / 720 / 40SC  | 1.85MIL METALIZED TCBOPP<br>720 ALL-TEMP ADHESIVE | S9036760  | No             | $\checkmark$ |              |              |     |     |              |
| 018MT / 960 / 12NB  | 1.85MIL METALIZED TCBOPP<br>GP FILM ADHESIVE      | S9210460  | No             |              |              |              |     |     |              |
| 018MT / 960 / 40SC  | 1.85MIL METALIZED TCBOPP<br>GP FILM ADHESIVE      | S9221660  | No             | $\checkmark$ |              |              |     |     | V            |
| 021MU / 102 / 40SC  | 2 MIL METALIZED TC BOPP<br>FILMIC ADHESIVE        | S8056060  | No             |              |              |              |     |     | $\checkmark$ |
| 021MU / 720 / 40SC  | 2 MIL METALIZED TC BOPP<br>720 ALL-TEMP ADHESIVE  | S8031460  | No             | $\checkmark$ | $\checkmark$ |              |     |     |              |
| 021MU / 960 / 40SC  | 2 MIL METALIZED TC BOPP<br>GP FILM ADHESIVE       | S9221860  | No             |              |              |              |     |     | $\checkmark$ |
| 056H5 / 751 / 40SC  | RAINBOW HOLOGRAM PAPER<br>751 PERMANENT ADHESIVE  | S4607060  | No             | $\checkmark$ |              |              |     |     |              |
| 057MS / 720 / 40SC  | SILVER METALLIZED PAPER<br>720 ALL TEMP ADHESIVE  | S6203060  | No             | $\checkmark$ |              | $\checkmark$ |     |     | $\checkmark$ |
| 057MS / 720M / 40SC | SILVER METALLIZED PAPER<br>720M ALL TEMP ADHESIVE | S9208260  | No             | $\checkmark$ |              |              |     |     |              |
| 56MSW / 720 / 40SC  | SILVER MET PAPER WS<br>720 ALL TEMP ADHESIVE      | S8982560  | No             | $\checkmark$ |              |              |     |     |              |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



## i i

### **April**

|                     | TUEDI   | MAL TRAN  | ISEED   |              | H            |              |              |              |              |
|---------------------|---|-----------|---|--------------|--------------|--------------|--------------|--------------|--------------|
| Structure           | Description THER  | ltem #    | Splice  | GB           | WIN          | KC           | MIN          | ATL          | LA           |
|                     |   |           | Free  |              |              |              |              |              |              |
| 026TT / 747 / 40SC  | 2.6 MIL WHITE TT BOPP<br>747 PERMANENT ADHESIVE                                 | S8773660  | No*   | $\checkmark$ |              |              |              |              | $\checkmark$ |
| 030TT / 747 / 40SC  | 3 MIL THERMAL TRANS BOPP<br>747 PERMANENT ADHESIVE                              | S5213060  | No*   |              |              |              |              |              | $\checkmark$ |
| 050HS / 272 / 40SC  | HI SPEED THER TRANS FSC<br>272 ULTRA REMOVABLE ADH                              | S7019060  | No  | $\checkmark$ |              |              |              |              | $\checkmark$ |
| 050HS / 275 / 41WK  | HI SPEED THER TRANS FSC<br>275 ULTRA REMOVABLE ADH                              | S9156260  | No  | $\checkmark$ |              |              |              |              |              |
| 095TK / 538 / 50SC  | 107 MICRON TC KIMDURA<br>538 REMOVABLE ADHESIVE                                 | S3286060  | No  | $\checkmark$ |              |              |              |              |              |
| 095TK / 751 / 50SC  | 107 MICRON TC KIMDURA<br>751 PERMANENT ADHESIVE                                 | S5391060  | No  | $\checkmark$ |              |              |              |              |              |
| 0TTFP / 531 / 40SC  | SELECT THERMAL TRANS FSC<br>531 REMOVABLE ADHESIVE                              | S7843160  | No*   | $\checkmark$ |              |              |              |              |              |
| 0TTFP / 720 / 40SC  | SELECT THERMAL TRANS FSC<br>720 ALL-TEMP ADHESIVE                               | S7833160  | Yes   | $\checkmark$ |              | $\checkmark$ | $\checkmark$ | $\checkmark$ |              |
| 0TTFP / 758M / 40SC | SELECT THERMAL TRANS FSC<br>758M PERMANENT ADHESIVE                             | S7664660  | Yes   | $\checkmark$ | $\checkmark$ | $\checkmark$ | $\checkmark$ |              | $\checkmark$ |
| 0TTFA / 758M / 40SC | 0TTFP OPAQUE FSC<br>758M PERMANENT ADHESIVE                                     | S7711260  | No  | $\checkmark$ |              |              |              |              |              |
| 100WP / 747 / 40SC  | 3.7 ML THERMAL TRAN BOPP<br>747 PERMANENT ADHESIVE                              | S7605960  | No*   | $\checkmark$ |              |              |              |              |              |
| VALUT / 278 / 40SC  | FSC-VALUE THERMAL TRANS<br>278 ULTRA REMOVABLE ADH                              | S8175760  | No  | $\checkmark$ |              |              |              |              |              |
| VALUT / 531 / 40SC  | FSC-VALUE THERMAL TRANS<br>531 REMOVABLE ADHESIVE                               | S9109660  | No*   | $\checkmark$ |              |              |              |              |              |
| VALUT / 720 / 40SC  | FSC-VALUE THERMAL TRANS<br>720 ALL-TEMP ADHESIVE                                | S7851360  | Yes, Except:<br>GB-5/15-No*<br>WIN-5/15-No*<br>KC-No*<br>ATL-5/15-No*<br>LA-5/15-No*      | 5/10/15      | 5/10/15      | 5/10/15      |              | 5/10/15      | 5/10/15      |
| VALUT / 751 / 40SC  | FSC-VALUE THERMAL TRANS<br>751 PERMANENT ADHESIVE                               | S7841560  | No*   |              |              |              | $\checkmark$ |              |              |
| VALUT / 751 / 40SC  | FSC-VALUE THERMAL TRANS<br>751 PERMANENT ADHESIVE                               | S8278660  | No*   |              | $\checkmark$ |              |              |              |              |
| VALUT / 757 / 40SC  | FSC-VALUE THERMAL TRANS<br>TACKIFIED PERM ADH                                   | \$9013660 | Yes, Except:<br>GB-No*<br>WIN-5/15-No*<br>ATL-5/15-No*                                    | 5/10/15      | 5/10/15      |              |              | 5/10/15      |              |
| VALUT / 758M / 40SC | FSC-VALUE THERMAL TRANS 758M PERMANENT ADHESIVE ** Indicatos vollow splice tape | \$7839660 | Yes, Except:<br>GB-5/15-No*<br>WIN-5/15-No*<br>KC-5/15-No*<br>MN-5/15-No*<br>ATL-5/15-No* | 5/10/15      | 5/10/15      | 5/10/15      | 5/10/15      | 5/10/15      | 5/10/15      |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10, LA-5/15-No\* standard unless otherwise noted - † 6" Cores

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

FAX ORDERS 1-800-705-0111

**CAN'T FIND IT?** 

CALL 1-800-445-4269



## \*\*\*

### **April**

|                     |   | •        |   |                  | ( A              |         |         |         |              |
|---------------------|---|----------|---|------------------|------------------|---------|---------|---------|--------------|
|                     | THERI   | MAL TRAN | ISFER   |                  |                  |         |         |         |              |
| Structure           | Description                                       | Item #   | Splice<br>Free  | GB               | WIN              | кс      | MIN     | ATL     | LA           |
| VALUT / 720 / 12NB  | FSC-VALUE THERMAL TRANS<br>720 ALL-TEMP ADHESIVE  | S9178360 | No  |                  |                  |         |         |         |              |
|                     | DIRE  | CT THERI | MAL   |                  |                  |         |         |         |              |
| Structure           | Description                                       | Item #   | Splice<br>Free  | GB               | WIN              | кс      | MIN     | ATL     | LA           |
| 021RX / 508 / 40SC  | 3.0 MIL PHARMACY DT FSC<br>508 PERMANENT ADHESIVE | S9174760 | No*   |                  |                  | V       |         |         | $\checkmark$ |
| 021RX / 751 / 40SC  | 3.0 MIL PHARMACY DT FSC<br>751 PERMANENT ADHESIVE | S9174660 | No*   | <b>√</b> 5/10/15 | 5/10/15          |         |         |         |              |
| 022TD / 720 / 40SC  | HI SENSITIVITY DT FSC<br>720 ALL TEMP ADHESIVE    | S6290060 | No*   | <b>√</b> 5/10/15 |                  |         |         |         |              |
| 024DT / 720 / 40SC  | TC RESISTANT DT FSC<br>720 ALL TEMP ADHESIVE      | S8814460 | Yes, Except:<br>GB-5/10/15-N<br>o*<br>KC-No*<br>LA-No*  | 5/ 10/ 15/<br>20 |                  | 5/10/15 |         |         | 5/10/15      |
| 024NT / 720 / 40SC  | NTC DIR THERMAL FSC<br>720 ALL TEMP ADHESIVE      | S9195479 | No  | <b>√</b> 5/10/15 |                  |         |         |         |              |
| 025DT / 531 / 40SC  | TC RESISTANT DT FSC<br>531 REMOVABLE ADHESIVE     | S8975760 | No  | $\checkmark$     |                  |         |         |         |              |
| 025DT / 720 / 40SC  | TC RESISTANT DT FSC<br>720 ALL TEMP ADHESIVE      | S8975560 | Yes, Except:<br>GB-5/10-No*<br>WIN-No*<br>KC-5/10-No*<br>MN-No*<br>ATL-No*<br>LA-No*                | 5/10/15          | 5/10/15          | 5/10/15 |         | 5/10/15 | 5/10/15      |
| 025DT / 751 / 40SC  | TC RESISTANT DT FSC<br>751 PERMANENT ADHESIVE     | S8976560 | No  | 10               |                  |         |         |         |              |
| 025DT / 757 / 40SC  | TC RESISTANT DT FSC<br>TACKIFIED PERM ADH         | S9018260 | No  | √<br>5/10/15     | 5/10/15          |         |         | 10      |              |
| 025NT / 531 / 40SC  | NTC DIRECT THERMAL FSC<br>531 REMOVABLE ADHESIVE  | S8274460 | No*   | <b>√</b> 5/10/15 |                  |         |         |         |              |
| 025NT / 720 / 40SC  | NTC DIRECT THERMAL FSC<br>720 ALL TEMP ADHESIVE   | S8153252 | Yes, Except:<br>GB-5/15-No*<br>WIN-5/15-No*<br>KC-5/15-No*<br>MN-5/15-No*<br>ATL-No*<br>LA-5/15-No* | 5/10/15          | 5/10/15          | 5/10/15 | 5/10/15 | 5/10/15 | 5/10/15      |
| 025NT / 758M / 40SC | NTC DIRECT THERMAL FSC<br>758M PERMANENT ADHESIVE | S8155352 | No*   | <b>√</b> 5/10/15 | <b>√</b> 5/10/15 |         |         | 5/10/15 |              |

FAX ORDERS 1-800-705-0111

**CAN'T FIND IT?** 

shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

CALL 1-800-445-4269

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt



# ¥ 1

## **April**

|                      |  | ,        |                       |                  | / X          |              |     |                  |                 |
|----------------------|--|----------|-----------------------|------------------|--------------|--------------|-----|------------------|-----------------|
|                      | DIRE   | ECT THER | MAL                   |                  |              |              |     |                  |                 |
| Structure            | Description  | Item #   | Splice<br>Free        | GB               | WIN          | кс           | MIN | ATL              | LA              |
| 24VTB / 720 / 40SC   | VALUE TC DIRECT THER FSC<br>720 ALL TEMP ADHESIVE                    | S9030960 | No*                   | 5/10/15          | 5/10/15      | 5/10/15      |     | <b>√</b> 5/10/15 | <b>5</b> /10/15 |
| 24VTB / 853 / 40SC   | VALUE TC DIRECT THER FSC<br>853 ALL TEMP ADHESIVE                    | S9169560 | No*                   | $\checkmark$     |              |              |     |                  |                 |
| 24VTB / 853 / 40SC   | VALUE TC DIRECT THER FSC<br>853 ALL TEMP ADHESIVE<br>(TIGHT RELEASE) | S9170460 | No*                   | 10               |              |              |     |                  |                 |
| 070MK / 720 / 40SC   | 76 MICRON SYN DIR THERMA<br>720 ALL-TEMP ADHESIVE                    | S4335060 | No                    | $\checkmark$     |              | $\checkmark$ |     |                  |                 |
| 095RK / 720 / 40SC   | 4.1 ML DIRECT THERM BOPP<br>720 ALL-TEMP ADHESIVE                    | S4101060 | No*                   | $\checkmark$     | $\checkmark$ | $\checkmark$ |     | $\checkmark$     |                 |
| 096RK / 720 / 40SC   | 4.1 ML DIRECT THERM BOPP<br>720 ALL-TEMP ADHESIVE                    | S9177360 | No                    |                  |              |              |     |                  |                 |
|                      | INK  | JET/LAS  | ER                    |                  |              |              |     |                  |                 |
| Structure            | Description  | Item #   | Splice<br>Free        | GB               | WIN          | кс           | MIN | ATL              | LA              |
| 050LJ / 758M / 41LF  | SUPER BRIGHT LJ FSC<br>758M PERMANENT ADHESIVE                       | S8238360 | No                    | <b>☑</b> † 10/15 |              |              |     |                  |                 |
| 050LJ / 758M / 53CRT | SUPER BRIGHT LJ FSC<br>758M PERMANENT ADHESIVE                       | S9184660 | No                    | √ †<br>10        |              |              |     |                  |                 |
| 050LJ / 720 / 0PBLF  | SUPER BRIGHT LJ FSC<br>720 ALL-TEMP ADHESIVE                         | S8214960 | Yes                   | <b>✓</b> †       |              |              |     |                  |                 |
| 050LJ / 751 / 0PBLF  | SUPER BRIGHT LJ FSC<br>751 PERMANENT ADHESIVE                        | S8218060 | Yes                   | √ †<br>10        |              | <b>√</b> †   |     |                  | <b>√</b> † 10   |
| 050LJ / 757 / 0PBLF  | SUPER BRIGHT LJ FSC<br>TACKIFIED PERM ADH                            | S9207460 | No                    | <b>▽</b> †       |              |              |     |                  |                 |
| 050LJ/758M/0PBLF     | SUPER BRIGHT LJ FSC<br>758M PERMANENT ADHESIVE                       | S8165060 | Yes, Except:<br>LA-No | √ †<br>10        | <b>√</b> †   |              |     |                  | <b>✓</b> †      |
| F47LJ / 757 / 41LF   | FSC SUPER BRIGHT LJ<br>TACKIFIED PERM ADH                            | S9077660 | No                    |                  | √<br>10/15   |              |     |                  |                 |
| F47LJ / 758M / 41LF  | FSC SUPER BRIGHT LJ<br>758M PERMANENT ADHESIVE                       | S9171560 | No                    | à<br>10/15       |              |              |     |                  |                 |
| F47LJ / 758M / 0PBLF | FSC SUPER BRIGHT LJ<br>758M PERMANENT ADHESIVE                       | S9172060 | No                    | √ †<br>10/15     |              |              |     |                  |                 |
| 054GZ / 758M / 0PBLF | FSC GREEN FLUORESCENT  | S8189860 | No                    | <b>✓</b> †       |              |              | П   |                  |                 |

FAX ORDERS 1-800-705-0111

**CAN'T FIND IT?** 

CALL 1-800-445-4269

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



## **April**

|  |  | , .p  |                            |                     | \ \C |    |     |     |  |
|--|--|---|----------------------------|---------------------|------|----|-----|-----|--|
|  | INK  | JET/LAS   | ER                         |                     |      |    |     |     |  |
| Structure  | Description  | Item #  | Splice<br>Free             | GB                  | WIN  | кс | MIN | ATL | LA   |
| 054OZ/758M/0PBLF   | FSC ORANGE FLUORESCENT<br>758M PERMANENT ADHESIVE  | S8190060  | No                         | <b></b> ✓ †         |      |    |     |     |  |
| 054PZ / 758M / 0PBLF   | FSC PINK FLUORESCENT<br>758M PERMANENT ADHESIVE  | S8190160  | No                         |                     |      |    |     |     |  |
| 054RZ/758M/0PBLF   | FSC RED FLUORESCENT<br>758M PERMANENT ADHESIVE   | S8190260  | No                         | $\checkmark$        |      |    |     |     |  |
| 054YZ / 758M / 0PBLF   | FSC YELLOW FLUORESCENT<br>758M PERMANENT ADHESIVE  | S8189960  | No                         |                     |      |    |     |     |  |
| 1GINK / 720 / 40SC   | FSC HIGH GLOSS INKJET<br>720 ALL TEMP ADHESIVE   | S8721460  | No                         | 1.25/ 2.5/<br>5/ 10 |      |    |     |     |  |
| 34WIJ / 720 / 40SC   | 3.4 MIL MATTE WH IJ BOPP<br>720 ALL TEMP ADHESIVE  | S9177960  | No                         | 2.5/5/10            |      |    |     |     |  |
| SG2NK / 720M / 40SC  | SEMI-GLOSS WB INKJET FSC<br>720M ALL TEMP ADHESIVE   | S9189560  | No                         | 2.5/5/10            |      |    |     |     |  |
| 07INK / 720 / 40SC   | 60# MATTE COATED INKJET<br>720 ALL TEMP ADHESIVE   | S9206460  | No                         | 1.25/ 2.5/<br>5/ 10 |      |    |     |     | 1.25/ 2.5/<br>5/ 10  |
|  |  |   |                            |                     |      |    |     |     |  |
|  | FILMS: POLY  | PROPYLE   | NES (CL                    | EAR)                |      |    |     |     |  |
| Structure  | FILMS: POLY Description  | PROPYLEN  | NES (CLI<br>Splice<br>Free | EAR)<br>GB          | WIN  | КС | MIN | ATL | LA   |
| Structure 018CT / 102 / 12NB   |  |   | Splice                     | •                   | WIN  | кс | MIN | ATL | LA   |
|  | <b>Description</b> 1.85 MIL TC CLEAR BOPP  | Item #  | Splice<br>Free             | GB                  |      |    |     |     |  |
| 018CT / 102 / 12NB   | Description  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP  | <b>Item #</b> \$9092460                                       | Splice<br>Free             | GB                  |      |    |     |     | ☑†   |
| 018CT / 102 / 12NB<br>018CT / 102 / 39NK   | Description  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP  | S9092460<br>S9064660  | Splice<br>Free<br>No       | GB                  |      |    |     |     | ☑†<br>☑  |
| 018CT / 102 / 12NB<br>018CT / 102 / 39NK<br>018CT / 720 / 40SC   | 1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP 720 ALL-TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP   | S9092460<br>S9064660<br>S9064560                              | Splice<br>Free<br>No<br>No | GB                  |      |    |     |     | ☑ <sup>†</sup><br>☑  |
| 018CT / 102 / 12NB<br>018CT / 102 / 39NK<br>018CT / 720 / 40SC<br>018CT / 720M / 40SC  | 1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP 720 ALL-TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP 720M ALL TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP 720M ALL TEMP ADHESIVE   | S9092460<br>S9064660<br>S9064560<br>S9090660                  | No No No                   | GB  □ □ □ □ □ □ □   |      |    |     |     | ☑†<br>☑<br>□   |
| 018CT / 102 / 12NB<br>018CT / 102 / 39NK<br>018CT / 720 / 40SC<br>018CT / 720M / 40SC<br>018CT / 751 / 40SC                        | 1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP 720 ALL-TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP 720M ALL TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP 751 PERMANENT ADHESIVE  1.85 MIL TC CLEAR BOPP   | \$9092460<br>\$9064660<br>\$9064560<br>\$9090660<br>\$9092760 | No No No No                | GB                  |      |    |     |     |  |
| 018CT / 102 / 12NB<br>018CT / 102 / 39NK<br>018CT / 720 / 40SC<br>018CT / 720M / 40SC<br>018CT / 751 / 40SC<br>018CT / 776S / 40SC | 1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP FILMIC ADHESIVE  1.85 MIL TC CLEAR BOPP 720 ALL-TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP 720M ALL TEMP ADHESIVE  1.85 MIL TC CLEAR BOPP 751 PERMANENT ADHESIVE  1.85 MIL TC CLEAR BOPP PET RECYCLABLE ADHESIVE  1.85 MIL TC CLEAR BOPP | S9092460 S9064660 S9064560 S9090660 S9092760 S9095260         | No No No No No             | GB                  |      |    |     |     | <ul><li>✓ †</li><li>✓</li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li></li><li>&lt;</li></ul> |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

FAX ORDERS 1-800-705-0111

**CAN'T FIND IT?** 

CALL 1-800-445-4269



FAX ORDERS 1-800-705-0111

### **Tailored Inventory Products (T.I.P.)**

## **April**

|   |   | •   |                        |                     | ()()         |              |              |     |              |
|---|---|---|------------------------|---------------------|--------------|--------------|--------------|-----|--------------|
|   | FILMS: POLY   | PROPYLE   | -                      | EAR)                |              |              |              |     |              |
| Structure   | Description   | Item #  | Splice<br>Free         | GB                  | WIN          | KC           | MIN          | ATL | LA           |
|   |   |   |                        |                     |              |              |              |     |              |
| 020CL / 720 / 40SC  | 2.0 MIL TC CLEAR BOPP<br>720 ALL-TEMP ADHESIVE  | S8766360  | No                     | $\checkmark$        |              |              |              |     |              |
| 020CL / 720M / 40SC   | 2.0 MIL TC CLEAR BOPP<br>720M ALL TEMP ADHESIVE   | S8997360  | No                     |                     |              |              |              |     | $\checkmark$ |
| 020CL / 751 / 40SC  | 2.0 MIL TC CLEAR BOPP<br>751 PERMANENT ADHESIVE   | S8782260  | No                     |                     |              |              | $\checkmark$ |     |              |
| 020CL / 960 / 12NB  | 2.0 MIL TC CLEAR BOPP<br>GP FILM ADHESIVE   | S9222060  | No                     | $\checkmark$        |              |              |              |     |              |
| 020CL / 960 / 40SC  | 2.0 MIL TC CLEAR BOPP<br>GP FILM ADHESIVE   | S9221160  | No                     | $\checkmark$        | $\checkmark$ | $\checkmark$ | $\checkmark$ |     | $\checkmark$ |
| 036CG / 347 / 50SC  | 3.6 ML CLEAR TC BOPP<br>GLASS REMOVABLE ADHESIVE  | S6883060  | No                     | 2.5/5/10            |              |              |              |     |              |
| 036CG / 347 / 74LF  | 3.6 ML CLEAR TC BOPP<br>GLASS REMOVABLE ADHESIVE  | S9127360  | No                     |                     |              |              |              |     |              |
|   | 50 MO BOLV  |   | 150 /14/1              | \                   |              |              |              |     |              |
|   | FILMS: POLY   |   | NES (WH<br>Splice      | •                   |              |              |              |     |              |
|   |   |   |                        |                     |              |              |              |     |              |
| Structure   | Description   | Item #  | Free                   | GB                  | WIN          | KC           | MIN          | ATL | LA           |
| 023WP / 102 / 40SC  | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE   | S7731160  | -                      | GB ✓                | WIN          | КС           | MIN          | ATL |              |
|   | 2.3 MIL TC WHITE BOPP   |   | Free                   |                     |              |              | _            | _   | _            |
| 023WP / 102 / 40SC  | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE 2.3 MIL TC WHITE BOPP   | S7731160  | <b>Free</b> Yes        | <b>V</b>            | abla         |              |              |     |              |
| 023WP / 102 / 40SC<br>023WP / 720 / 40SC  | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720 ALL-TEMP ADHESIVE  2.3 MIL TC WHITE BOPP   | S7731160<br>S7630960  | Yes<br>Yes             | <ul><li>✓</li></ul> | <b>V</b>     |              |              |     |              |
| 023WP / 102 / 40SC<br>023WP / 720 / 40SC<br>023WP / 950 / 40SC  | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720 ALL-TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.3 MIL TC WHITE BOPP   | S7731160<br>S7630960<br>S9221260  | Yes<br>Yes<br>No       |                     |              |              |              |     |              |
| 023WP / 102 / 40SC<br>023WP / 720 / 40SC<br>023WP / 950 / 40SC<br>023WT / 102 / 40SC  | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720 ALL-TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP  | S7731160<br>S7630960<br>S9221260<br>S9126860  | Yes Yes No             |                     |              |              |              |     |              |
| 023WP / 102 / 40SC<br>023WP / 720 / 40SC<br>023WP / 950 / 40SC<br>023WT / 102 / 40SC<br>023WT / 720M / 40SC   | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720 ALL-TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE  2.3 MIL TC WHITE BOPP  | \$7731160<br>\$7630960<br>\$9221260<br>\$9126860<br>\$9133560                           | Yes Yes No No          |                     |              |              |              |     |              |
| 023WP / 102 / 40SC<br>023WP / 720 / 40SC<br>023WP / 950 / 40SC<br>023WT / 102 / 40SC<br>023WT / 720M / 40SC<br>023WT / 950 / 40SC                       | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720 ALL-TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.4 MIL WHITE BOPP                                     | \$7731160<br>\$7630960<br>\$9221260<br>\$9126860<br>\$9133560<br>\$9221560              | Yes Yes No No No       |                     |              |              |              |     |              |
| 023WP / 102 / 40SC<br>023WP / 720 / 40SC<br>023WP / 950 / 40SC<br>023WT / 102 / 40SC<br>023WT / 720M / 40SC<br>023WT / 950 / 40SC<br>024TL / 102 / 40SC | 2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720 ALL-TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.3 MIL TC WHITE BOPP FILMIC ADHESIVE  2.3 MIL TC WHITE BOPP 720M ALL TEMP ADHESIVE  2.3 MIL TC WHITE BOPP GP FILM ADHESIVE  2.4 MIL WHITE BOPP FILMIC ADHESIVE  2.4 MIL WHITE BOPP | \$7731160<br>\$7630960<br>\$9221260<br>\$9126860<br>\$9133560<br>\$9221560<br>\$8775660 | Yes Yes No No No No No |                     |              |              |              |     |              |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

**CAN'T FIND IT?** 

CALL 1-800-445-4269



# 4

### **April**

| <b>7-P···</b>       |  |          |                                 |                  |              |              |              |              |              |  |  |
|---------------------|--|----------|---------------------------------|------------------|--------------|--------------|--------------|--------------|--------------|--|--|
|                     | FILMS: POLYPROPYLENES (WHITE)                    |          |                                 |                  |              |              |              |              |              |  |  |
| Structure           | Description                                      | Item #   | Splice<br>Free                  | GB               | WIN          | кс           | MIN          | ATL          | LA           |  |  |
| 024TL / 751 / 40SC  | 2.4 MIL WHITE BOPP<br>751 PERMANENT ADHESIVE     | S8787060 | No                              |                  |              |              |              |              |              |  |  |
| 024TL / 751 / 12NB  | 2.4 MIL WHITE BOPP<br>751 PERMANENT ADHESIVE     | S8832660 | No                              | $\checkmark$     |              |              |              |              |              |  |  |
| 024TL / 950 / 12NB  | 2.4 MIL WHITE BOPP<br>GP FILM ADHESIVE           | S9222260 | No                              |                  |              |              |              |              |              |  |  |
| 024TL / 950 / 40SC  | 2.4 MIL WHITE BOPP<br>GP FILM ADHESIVE           | S9221060 | No                              | $\checkmark$     | $\checkmark$ | $\checkmark$ | V            |              | $\checkmark$ |  |  |
| 024TL / 950 / 92NB  | 2.4 MIL WHITE BOPP<br>GP FILM ADHESIVE           | S9215060 | No                              | <b>✓</b> †       |              |              |              |              |              |  |  |
| 24WCT / 102 / 12NB  | 2.4 MIL TC WHITE BOPP<br>FILMIC ADHESIVE         | S9113660 | No                              |                  |              |              |              |              | <b>✓</b> †   |  |  |
| 24WCT / 102 / 40SC  | 2.4 MIL TC WHITE BOPP<br>FILMIC ADHESIVE         | S9110760 | No                              |                  | $\checkmark$ |              |              | $\checkmark$ | $\checkmark$ |  |  |
| 24WCT / 720 / 40SC  | 2.4 MIL TC WHITE BOPP<br>720 ALL-TEMP ADHESIVE   | S9134360 | No                              | $\checkmark$     |              |              |              |              | $\checkmark$ |  |  |
| 24WCT / 720M / 40SC | 2.4 MIL TC WHITE BOPP<br>720M ALL TEMP ADHESIVE  | S9119160 | No                              | $\checkmark$     |              |              |              |              |              |  |  |
| 24WCT / 751 / 40SC  | 2.4 MIL TC WHITE BOPP<br>751 PERMANENT ADHESIVE  | S9123660 | No                              | $\checkmark$     |              |              |              |              |              |  |  |
| 24WCT / 776S / 40SC | 2.4 MIL TC WHITE BOPP<br>PET RECYCLABLE ADHESIVE | S9120460 | No                              | $\checkmark$     |              |              |              |              | $\checkmark$ |  |  |
| 24WCT / 950 / 12NB  | 2.4 MIL TC WHITE BOPP<br>GP FILM ADHESIVE        | S9221460 | No                              | <b>✓</b> †       |              |              |              |              | <b>✓</b> †   |  |  |
| 24WCT / 950 / 40SC  | 2.4 MIL TC WHITE BOPP<br>GP FILM ADHESIVE        | S9215260 | No                              | $\checkmark$     | $\checkmark$ | $\checkmark$ |              | $\checkmark$ | $\checkmark$ |  |  |
| 026TL               | 2.6 MIL WHITE TC BOPP                            | S6397560 | No                              | <b>√</b> 5/10/20 |              |              |              |              |              |  |  |
| 026TL / 102 / 40SC  | 2.6 MIL WHITE TC BOPP<br>FILMIC ADHESIVE         | S7802360 | Yes, Except:<br>KC-No<br>ATL-No |                  | $\checkmark$ | $\checkmark$ |              | $\checkmark$ |              |  |  |
| 026TL / 103 / 40SC  | 2.6 MIL WHITE TC BOPP<br>103 PERMANENT ADHESIVE  | S6174060 | No                              | $\checkmark$     |              |              | $\checkmark$ |              |              |  |  |
| 026TL / 720 / 40SC  | 2.6 MIL WHITE TC BOPP<br>720 ALL-TEMP ADHESIVE   | S6173060 | No                              | $\checkmark$     |              |              |              |              |              |  |  |
| 026TL / 747 / 40SC  | 2.6 MIL WHITE TC BOPP<br>747 PERMANENT ADHESIVE  | S7600560 | No                              | $\checkmark$     |              |              |              |              | $\checkmark$ |  |  |
| 026TL / 751 / 40SC  | 2.6 MIL WHITE TC BOPP<br>751 PERMANENT ADHESIVE  | S5384060 | No                              | $\checkmark$     | $\checkmark$ |              |              |              | $\checkmark$ |  |  |

FAX ORDERS 1-800-705-0111

**CAN'T FIND IT?** 

shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

CALL 1-800-445-4269

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt



## **April**

|                               |  |          |                |              | ()(C)        |              |              |              |              |
|-------------------------------|--|----------|----------------|--------------|--------------|--------------|--------------|--------------|--------------|
| FILMS: POLYPROPYLENES (WHITE) |  |          |                |              |              |              |              |              |              |
| Structure                     | Description  | Item #   | Splice<br>Free | GB           | WIN          | KC           | MIN          | ATL          | LA           |
| 026TL / 950 / 12NB            | 2.6 MIL WHITE TC BOPP<br>GP FILM ADHESIVE          | S9222160 | No             | <b>√</b> †   |              |              |              |              |              |
| 026TL / 950 / 40SC            | 2.6 MIL WHITE TC BOPP<br>GP FILM ADHESIVE          | S9215460 | No             | $\checkmark$ | $\checkmark$ | $\checkmark$ | $\checkmark$ | $\checkmark$ | $\checkmark$ |
| 26WCT / 102 / 40SC            | 2.6 MIL TC WHITE BOPP<br>FILMIC ADHESIVE           | S9021460 | No             |              | $\checkmark$ |              |              |              | $\checkmark$ |
| 26WCT / 720 / 12NB            | 2.6 MIL TC WHITE BOPP<br>720 ALL TEMP ADHESIVE     | S9125460 | No             | <b>✓</b> †   |              |              |              |              |              |
| 26WCT / 720 / 40SC            | 2.6 MIL TC WHITE BOPP<br>720 ALL-TEMP ADHESIVE     | S9121160 | No             | $\checkmark$ |              |              |              |              |              |
| 26WCT / 751 / 40SC            | 2.6 MIL TC WHITE BOPP<br>751 PERMANENT ADHESIVE    | S9021560 | No             | $\checkmark$ |              |              |              |              |              |
| 26WCT / 767HM / 12PET         | 2.6TCWBOPP76712PET                                 | S9167360 | No*            | <b>✓</b> †   |              |              |              |              |              |
| 036WG / 347 / 50SC            | 3.6 ML WHITE TC BOPP<br>GLASS REMOVABLE ADHESIVE   | S6888060 | No             | 2.5/5/10     |              |              |              |              |              |
| 036WG / 347 / 74LF            | 3.6 ML WHITE TC BOPP<br>GLASS REMOVABLE ADHESIVE   | S9157660 | No             |              |              |              |              |              |              |
| 34WIJ / 720 / 40SC            | 3.4 MIL MATTE WH IJ BOPP<br>720 ALL TEMP ADHESIVE  | S9177960 | No             | 2.5/5/10     |              |              |              |              |              |
| 26WCT / 720M / 40SC           | 2.6 MIL TC WHITE BOPP<br>720M ALL TEMP ADHESIVE    | S9168060 | No             | $\checkmark$ |              |              |              |              |              |
| 26WCT / 950 / 12NB            | 2.6 MIL TC WHITE BOPP<br>GP FILM ADHESIVE          | S9222360 | No             | $\checkmark$ |              |              |              |              |              |
| 26WCT / 950 / 40SC            | 2.6 MIL TC WHITE BOPP<br>GP FILM ADHESIVE          | S9215360 | No             | V            | <b>V</b>     |              |              |              | $\checkmark$ |
|                               | FILMS: POLYPROPY                                   | LENES (V | ARIABLE        | E IMAG       | SING)        |              |              |              |              |
| Structure                     | Description  | Item #   | Splice<br>Free | GB           | WIN          | кс           | MIN          | ATL          | LA           |
| 026TT / 747 / 40SC            | 2.6 MIL WHITE TT BOPP<br>747 PERMANENT ADHESIVE    | S8773660 | No*            | $\checkmark$ |              |              |              |              | V            |
| 030TT / 747 / 40SC            | 3 MIL THERMAL TRANS BOPP<br>747 PERMANENT ADHESIVE | S5213060 | No*            |              |              |              |              |              | $\checkmark$ |
| 070MK / 720 / 40SC            | 76 MICRON SYN DIR THERMA<br>720 ALL-TEMP ADHESIVE  | S4335060 | No             | $\checkmark$ |              | $\checkmark$ |              |              |              |
| 095RK / 720 / 40SC            | 4.1 ML DIRECT THERM BOPP<br>720 ALL-TEMP ADHESIVE  | S4101060 | No*            | $\checkmark$ | $\checkmark$ | $\checkmark$ |              | $\checkmark$ |              |

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

**CAN'T FIND IT?** 

FAX ORDERS 1-800-705-0111

<sup>\*</sup> Indicates a runnable splice \*\* Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores



## ¥ 1

|  |   |  |  | ( )(  |  |  |  |  |  |
|--|---|--|--|---|--|--|--|--|--|
| FILMS: POLYPROPYLENES (VARIABLE IMAGING)           |   |  |  |   |  |  |  |  |  |
| Description  | Item #  | Splice<br>Free   | GB   | WIN   | кс   | MIN  | ATL  | LA                                       |  |
|  |   |  |  |   |  |  |  |  |  |
| 3.7 ML THERMAL TRAN BOPP<br>747 PERMANENT ADHESIVE | S7605960  | No*  |  |   |  |  |  |  |  |
| 4.1 ML DIRECT THERM BOPP<br>720 ALL-TEMP ADHESIVE  | S9177360  | No   | $\checkmark$   | $\checkmark$  |  |  |  |  |  |
| 107 MICRON TC KIMDURA<br>538 REMOVABLE ADHESIVE    | S3286060  | No   | $\checkmark$   |   |  |  |  |  |  |
| 107 MICRON TC KIMDURA<br>751 PERMANENT ADHESIVE    | S5391060  | No   | $\checkmark$   |   |  |  |  |  |  |
| EII ME. DOL VDD                                    | ODVI ENE  | C/META   | I IZED   | <b>.</b>  |  |  |  |  |  |
|  |   |  |  |   |  |  |  |  |  |
| Description  | Item #  | Free   | GB   | WIN   | KC   | MIN  | ATL  | LA                                       |  |
|  |   |  |  |   |  |  |  |  |  |
| 1.85MIL METALIZED TCBOPP<br>FILMIC ADHESIVE        | S9129360  | No   |  |   |  |  |  | V  |  |
| 1.85MIL METALIZED TCBOPP<br>720 ALL-TEMP ADHESIVE  | S9036760  | No   | $\checkmark$   |   |  |  |  |  |  |
| 1.85MIL METALIZED TCBOPP<br>GP FILM ADHESIVE       | S9210460  | No   | $\checkmark$   |   |  |  |  |  |  |
| 1.85MIL METALIZED TCBOPP<br>GP FILM ADHESIVE       | S9221660  | No   | $\checkmark$   |   |  |  |  | $\checkmark$                             |  |
| 2 MIL METALIZED TC BOPP<br>FILMIC ADHESIVE         | S8056060  | No   |  |   |  |  |  | $\checkmark$                             |  |
| 2 MIL METALIZED TC BOPP<br>720 ALL-TEMP ADHESIVE   | S8031460  | No   | $\checkmark$   | $\checkmark$  |  |  |  |  |  |
| 2 MIL METALIZED TC BOPP<br>GP FILM ADHESIVE        | S9221860  | No   |  |   |  |  |  | $\checkmark$                             |  |
| EII Me.  | DOI VETVI   | DENES  |  |   |  |  |  |  |  |
| FILIVIO.   | OLISIT  |  |  |   |  |  |  |  |  |
| Description  | Item #  | Free   | GB   | WIN   | KC   | MIN  | ATL  | LA                                       |  |
| 1.5MIL CLEAR POLYSTYRENE<br>720 ALL TEMP ADHESIVE  | S8175860  | No   |  |   |  | $\checkmark$   |  |  |  |
|  | 3.7 ML THERMAL TRAN BOPP 747 PERMANENT ADHESIVE  4.1 ML DIRECT THERM BOPP 720 ALL-TEMP ADHESIVE  107 MICRON TC KIMDURA 538 REMOVABLE ADHESIVE  107 MICRON TC KIMDURA 751 PERMANENT ADHESIVE  FILMS: POLYPR Description  1.85MIL METALIZED TCBOPP FILMIC ADHESIVE  1.85MIL METALIZED TCBOPP 720 ALL-TEMP ADHESIVE  1.85MIL METALIZED TCBOPP GP FILM ADHESIVE  2 MIL METALIZED TC BOPP FILMIC ADHESIVE  2 MIL METALIZED TC BOPP 720 ALL-TEMP ADHESIVE  3 MIL METALIZED TC BOPP 720 ALL-TEMP ADHESIVE  4 MIL METALIZED TC BOPP 720 ALL-TEMP ADHESIVE  5 MIL METALIZED TC BOPP 740 ALL-TEMP ADHESIVE  1.5MIL CLEAR POLYSTYRENE | Description  Item #  3.7 ML THERMAL TRAN BOPP 747 PERMANENT ADHESIVE  4.1 ML DIRECT THERM BOPP 720 ALL-TEMP ADHESIVE  107 MICRON TC KIMDURA 538 REMOVABLE ADHESIVE  107 MICRON TC KIMDURA 751 PERMANENT ADHESIVE  FILMS: POLYPROPYLENE  Description  Item #  1.85MIL METALIZED TCBOPP 720 ALL-TEMP ADHESIVE  1.85MIL METALIZED TCBOPP 720 ALL-TEMP ADHESIVE  1.85MIL METALIZED TCBOPP GP FILM ADHESIVE  1.85MIL METALIZED TCBOPP GP FILM ADHESIVE  2 MIL METALIZED TCBOPP GP FILM ADHESIVE  2 MIL METALIZED TCBOPP FILMIC ADHESIVE  2 MIL METALIZED TCBOPP FILMIC ADHESIVE  2 MIL METALIZED TC BOPP 720 ALL-TEMP ADHESIVE  3 S8031460  FILMS: POLYSTY Description  Item # | DescriptionItem #Splice Free3.7 ML THERMAL TRAN BOPP 747 PERMANENT ADHESIVE\$7605960No*4.1 ML DIRECT THERM BOPP 720 ALL-TEMP ADHESIVE\$9177360No107 MICRON TC KIMDURA 538 REMOVABLE ADHESIVE\$3286060No107 MICRON TC KIMDURA 751 PERMANENT ADHESIVE\$5391060NoFILMS: POLYPROPYLENES (META Splice Free1.85MIL METALIZED TCBOPP FILMIC ADHESIVE\$9129360No1.85MIL METALIZED TCBOPP GP FILM ADHESIVE\$9936760No1.85MIL METALIZED TCBOPP GP FILM ADHESIVE\$92210460No1.85MIL METALIZED TCBOPP GP FILM ADHESIVE\$9221660No2 MIL METALIZED TC BOPP FILMIC ADHESIVE\$8056060No2 MIL METALIZED TC BOPP FILMIC ADHESIVE\$8031460No2 MIL METALIZED TC BOPP GP FILM ADHESIVE\$9221860No2 MIL METALIZED TC BOPP GP FILM ADHESIVE\$9221860No2 MIL METALIZED TC BOPP GP FILM ADHESIVE\$9221860NoDescriptionItem #\$plice Free1.5MIL CLEAR POLYSTYRENE\$8175860No | Description       Item #       Splice Free       GB         3.7 ML THERMAL TRAN BOPP 747 PERMANENT ADHESIVE       \$7605960       No*       ✓         4.1 ML DIRECT THERM BOPP 720 ALL-TEMP ADHESIVE       \$9177360       No       ✓         107 MICRON TC KIMDURA 538 REMOVABLE ADHESIVE       \$3286060       No       ✓         107 MICRON TC KIMDURA 751 PERMANENT ADHESIVE       \$5391060       No       ✓         FILMS: POLYPROPYLENES (METALIZED DESCRIPTION       Item #       Splice Free       GB         1.85MIL METALIZED TCBOPP FILMIC ADHESIVE       \$9129360       No       ✓         1.85MIL METALIZED TCBOPP FILMIC ADHESIVE       \$9936760       No       ✓         1.85MIL METALIZED TCBOPP GP FILM ADHESIVE       \$92210460       No       ✓         1.85MIL METALIZED TCBOPP GP FILM ADHESIVE       \$8056060       No       ✓         2 MIL METALIZED TC BOPP FILMIC ADHESIVE       \$8031460       No       ✓         2 MIL METALIZED TC BOPP GP FILM ADHESIVE       \$9221860       No       ✓         FILMS: POLYSTYRENES Splice Free       GB         Description       Item #       \$P100 GP       GB | FILMS: POLYPROPYLENES (VARIABLE IMAGING)         Description       Item #       Splice Free       GB       WIN         3.7 ML THERMAL TRAN BOPP 747 PERMANENT ADHESIVE       \$7605960       No*       ✓       □         4.1 ML DIRECT THERM BOPP 720 ALL-TEMP ADHESIVE       \$9177360       No       ✓       ✓         107 MICRON TC KIMDURA 538 REMOVABLE ADHESIVE       \$3286060       No       ✓       □         107 MICRON TC KIMDURA 751 PERMANENT ADHESIVE       \$5391060       No       ✓       □         FILMS: POLYPROPYLENES (METALIZED)         Description       Item #       Splice Free       GB       WIN         1.85MIL METALIZED TCBOPP FILMIC ADHESIVE       \$99129360       No       □       □         1.85MIL METALIZED TCBOPP FILM ADHESIVE       \$9936760       No       □       □         1.85MIL METALIZED TCBOPP GP FILM ADHESIVE       \$99210460       No       □       □         1.85MIL METALIZED TCBOPP GP FILM ADHESIVE       \$8056060       No       □       □         2 MIL METALIZED TC BOPP FILMIC ADHESIVE       \$8031460       No       □       □         2 MIL METALIZED TC BOPP FILM ADHESIVE       \$99221860       No       □       □         2 MIL METALIZED TC BOPP GP FILM ADHESIVE | Description   Item #   Splice   Free   GB   WIN   KC | Description   Item #   Splice Free   GB   WIN   KC   MIN | PILMS: POLYPROPYLENES (VARIABLE IMAGING) |  |

<sup>\*</sup> Indicates a runnable splice \*\* Indicates <u>yellow</u> splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores
All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.



## 4

### **April**

| Structure                         | FILMS  Description                                 | : POLYES | TERS<br>Splice<br>Free | GB           | WIN | кс | MIN | ATL | LA |
|-----------------------------------|--|----------|------------------------|--------------|-----|----|-----|-----|----|
| 2VWPT / 406 / 50SC                | 2 MIL VALUE WHITE PET<br>TACKIFIED PERM ADHESIVE   | S8089560 | No                     | 2.5/5/10     |     |    |     |     |    |
| PIGGYBACKS                        |  |          |                        |              |     |    |     |     |    |
| Structure                         | Description  | Item #   | Splice<br>Free         | GB           | WIN | KC | MIN | ATL | LA |
| 054SG / 515 / 12NB / 515 / 40SC   | 54# C1S SEMI GLOSS FSC<br>FILMIC ADHESIVE          | S9075360 | No                     | $\checkmark$ |     |    |     |     |    |
| 054SG / 758M / 40SC / 758M / 40SC | 54# C1S SEMI GLOSS FSC<br>758M PERMANENT ADHESIVE  | S8027060 | No                     | $\checkmark$ |     |    |     |     |    |
| VALUT / 757 / 40SC / 757 / 40SC   | FSC-VALUE THERMAL TRANS<br>TACKIFIED PERM ADH      | S9137960 | No                     | $\checkmark$ |     |    |     |     |    |
| VALUT / 758M / 40SC / 758M / 40SC | FSC-VALUE THERMAL TRANS<br>758M PERMANENT ADHESIVE | S8138960 | No                     | $\checkmark$ |     |    |     |     |    |

- Minimum one slit roll at 3", minimum length varies by product.
- Rolls 5,000' or less are palletized poker chip (stacked on slit edge) with 45 inch maximum height including pallet.
- Rolls 10,000' or greater are palletized on the round (cradle packed).
- All pallets will be stretch wrapped.
- All rolls on 3 inch cores, except as noted.

- Orders placed by 3:00 PM (time zone applicable to location from which shipment originates) will be shipped next business day.
- Orders placed before cutoff time cannot be changed or cancelled after cutoff time.
- No early pickup arrangements, please.

GB=Green Bay, WI WIN=Winchester, VA KC=Kansas City, MO MIN=Minneapolis, MN ATL=Atlanta, GA LA=Los Angeles, CA

All orders are taken subject to final acceptance at Green Bay, Wisconsin, and no agent or representative has authority to accept any order or in any way bind the company relative thereto. These prices are for prompt shipment and are subject to change without notice. The company's standard Terms and Conditions as in effect at the time of sale shall control.

FAX ORDERS 1-800-705-0111

**CAN'T FIND IT?** 

CALL 1-800-445-4269

<sup>\*</sup> Indicates a runnable splice \*\*Indicates yellow splice tape - 5,000' and 10,000' rolls standard unless otherwise noted - † 6" Cores